[illegible]
A-A-1738
February 9, 1996
SUPERSEDING
A-A-1738A
September 27, 1990

COMMERCIAL ITEM DESCRIPTION

BOX, SMALL PARTS (PLASTIC, COMPARTMENTED)

The General Services Administration has authorized the use of this commercial item description for all Federal agencies.

1. SCOPE:

This description covers requirements for a transparent plastic box with compartments and a hinged cover to be used in military field chests, kits, and assemblies to contain readily visible small parts.

2. SALIENT CHARACTERISTICS:

2.1 The box shall be fabricated from a transparent, colorless, plastic molding material used commercially in making plastic boxes.

2.2. The box shall be a plain, rectangular design, consisting of a rigid body and rigid cover with suitable hinges and an integral locking device. The body of the box shall be divided into six equal compartments by means of five partitions.

2.3. The hinges and hinge pins shall be fabricated of corrosion-resisting annealed steel or integrally molded plastic.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: General Services Administration, Federal Supply Service, Engineering Branch, New York, NY 10278

FSC 8115

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:16Z
Check the source to verify that this is the current version before use.

2.4. The outside bottom of the finished plastic box shall be legibly and permanently marked with the manufacturer's name or readily identifiable trademark. The methods used for marking of the plastic box shall be molding or etching.

2.5 The box shall have the following dimensions in centimeters as minimums:

	Length	Width	Depth	Wall Thickness
Box (outside, overall)	21.25	11.25	3.33	
Cover (outside)	21.25	11.25	1.10	0.09
Body (inside)	-----	10.60	3.00	0.09
Partitions (5)	-----	10.60	3.00	0.10
Compartments (6)	10.60	3.30	3.00	

2.6 A sample of the molding material used in making the box shall be tested in accordance with ASTM D256, method A. The molding material shall have a minimum impact strength of 2 foot-pounds per inch of notch.

2.7 If hinges or hinge pins are made of annealed steel, they shall be tested in accordance with ASTM B117 for a period of 24 hours, with no rust permitted.

2.8 Workmanship. The surface of the finished plastic box shall be smooth, free of sharp edges, blisters, old marks, prominent weld marks or sinks, holes, cracks, dirt or any other defects which may affect its durability, serviceability, or appearance. The parting line between the box and cover must fit uniformly without showing any visible gaps. Minor color variations present as a result of recycled polystyrene plastic will be acceptable.

3. REGULATORY REQUIREMENTS:

3.1 The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:16Z
Check the source to verify that this is the current version before use.

3.2 The contractor shall certify that if polystyrene is used in the manufacture of this item, it shall contain a minimum of 25% post consumer recovered materials in accordance with 40 Code of Federal Regulations Part 247, Comprehensive Guideline for Procurement of Products containing Recovered Materials; Final Rule. The government reserves the right to require proof of such conformance prior to first delivery, and thereafter as may be otherwise provided for under the provisions of the contract.

4. QUALITY ASSURANCE:

4.1 The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of applicable documents, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same product offered for sale in the commercial marketplace. The government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

4.2 Suppliers are encouraged to use quality control (QC) techniques that exhibit control over their processes (e.g. (Statistical Process Control) SPC techniques) as defined in American National Standards Institute (ANSI) Z1.1, Z1.2 and Z1.3/ American Society for Quality Control (ASQC) B.1, B.2 and B.3 that systematically reduce excess variations. Objective evidence shall be available that demonstrates overall measurement adequacy, techniques and controls. These techniques shall ensure quality levels equal to, or greater than, those cited in applicable technical document or, herein.

4.3 End item inspection/testing may be used by the offeror or the Government representative, as a means to determine the effectiveness of the in process quality controls. In process controls shall not be substituted for end item performance testing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:16Z
Check the source to verify that this is the current version before use.

4.4 For those characteristics for which there are no such controls, or for end item performance test, lot by lot sampling for inspection/test shall be required. Sampling shall be in accordance with the American National Standards Institute (ANSI)/ American Society for Quality Control (ASQC) Z1.4, Sampling Procedures and Tables for Inspection by Attributes.

4.5 An inspection lot shall consist of all like items submitted for inspection at one time. The inspection level shall be S-2 with an AQL of 4.0 percent defective. The supplier must provide objective evidence (tests and inspection records) that the presented material meets the requirements of the sampling plan as indicated above.

5. PACKAGING:

Preservation, Packaging, Packing, Labeling, and Marking shall be as specified in the contract or purchase order.

6. NOTES:

6.1 Addresses for obtaining copies of referenced documents:

The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this commercial item description to the extent specified herein:

6.1.1 Sampling Procedures and Tables for Inspection by Attributes can be obtained from American Society for Quality Control, P.O. Box 3005, 611 E. Wisconsin Avenue, Milwaukee, WI 53201-4606.

6.1.2 ASTM test methods are available from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:16Z
Check the source to verify that this is the current version before use.

6.1.3 Federal Acquisition Regulations (FAR) is available through the Superintendent of Documents, U.S. Government Printing Office, Washington DC 20402.

6.1.4 Title 40, Code of Federal Regulations, Protection of Environment, Part 247, may be purchased with a Visa, Mastercard, or prepaid check from Government printing Office, Washington, DC. Phone: 202-783 3238

6.2 Ordering data. Procurement documents shall specify the following:

(a) Title, number and date of this commercial item description.
(b) Quantity required.

6.3 NSN LIST:

8115-00-761-8912

Military Coordinating Activity

Army - GL

Preparing Activity

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:16Z
Check the source to verify that this is the current version before use.