[Metric]
A-A-2965
March 11, 1996

COMMERCIAL ITEM DESCRIPTION
CORRECTION MARKER, TUBE TYPE, OPAQUE COATING
(CORRECTION STX & REFILLS)

The General Services Administration has authorized the use of this commercial item description, for all federal agencies.

1. **Scope:** This commercial item description covers non-toxic refillable, crayon type markers and refills used to white out or obliterate markings on paper.

2. **Salient Characteristics:**

2.1 The correction marker shall consist of a replaceable cartridge, holder (barrel) with a twist type mechanism for securing, propelling and repelling the cartridge, and a cap with pocket clip.

2.2 The marking medium cartridge shall be non-toxic, odorless, quick drying, and shall not bleed through paper.

2.3 The manufacturer's name or trademark shall be exhibited on the marker. Placement of these permanent markings shall be at the option of the manufacturer, provided they are prominently displayed.

2.4 The dispenser shall be made of plastic or metal or a combination of these materials. The cap shall be tight fitting to provide protection against evaporation of the marking medium.

2.5 The overall length of the correction marker shall be not less than 122 mm ± 2 mm (4.8 inch ± .08 inch) measured with the cap attached and a diameter of 15 mm ± 2 mm (.6 inches ± .08 inches) measured at its largest diameter.

2.6 Refill cartridges shall consist of a cartridge with a plastic holding device attached. The writing end of the cartridge shall be beveled to prevent chipping. The cartridge shall be enclosed inside a plastic tube with cap to prevent evaporation of the ink. The cartridge and holding device shall be no greater than 50.7 mm ± 1 mm (1.99 inch ± .003 inch) in length. The plastic tube with cap attached shall not be greater than 53.4 mm ± 1 mm (2.1 inch ± .003 inch) in length.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to General Services Administration, Federal Supply Service, Engineering Branch, 26 Federal Plaza, New York, NY 10278.

FSC 7510

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

2.7 Shelf Life. The markers shall have a shelf life of one year after delivery and shall be capable of withstanding normal usage and handling.

2.8 Workmanship. The markers shall be securely assembled so that parts do not become loose or displaced and shall be free from defects or imperfections which may affect appearance serviceability or performance.

3. Regulatory Requirements:

The offerer/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4. Quality Assurance Requirements:

4.1 Contractor Certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The government reserves the right to require proof of such conformance prior to first delivery and therefore as may be otherwise provided for under the provisions of the contract.

4.2 Examination and Testing:

4.2.1 Suppliers are encouraged to use quality control (QC) techniques that exhibit control over their processes (e.g. (Statistical Process Control) SPC Techniques) as defined in American National Standards Institute (ANSI) Z1.1, Z1.2 and Z1.3 / American Society for Quality Control (ASQC) B.1, B.2 and B.3 that systematically reduce excess variations. If used, objective evidence shall be available that demonstrates overall measurement adequacy techniques and controls. These techniques shall ensure quality levels equal to, or greater than, those cited in applicable technical document or, herein.

4.2.2 End item inspection/testing may be used by the offeror or the Government representative, as a means to determine the effectiveness of the in process quality controls. While in process controls shall not be substituted for end item performance testing, they may be used for visual and dimensional sampling.

4.2.3 For those characteristics for which there are no such controls, or for end item performance testing lot by lot sampling for inspection/test shall be required. The sample unit shall be one marker and refill cartridge. Sampling shall be in accordance with the American National Standards Institute (ANSI) / American Society for Quality Control (ASQC) Z1.4, Sampling Procedures and Tables for Inspection by Attributes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

4.2.4 An inspection lot shall consist of all like items submitted for inspection at one time. The inspection level for visual & dimensional examination shall be S-3 with an AQL of 2.5 percent defective. For performance testing, the level shall be S-2 with an AQL of 4.0 percent defective. The supplier must provide objective evidence (tests and inspection records) that the presented material meets the requirements of the sampling plan as indicated above.

4.3 Performance Testing:

4.3.1 Breaking Strength. Extend the ink cartridge 4.5 mm (0.180 inch) from the point of the marker. The test shall be performed on an electronic scale equipped with horizontal platform upon which the test pressure shall be applied. The platform shall offer no resistance to the point moving across its surface. The test shall be performed while maintaining a 45° angle The marking, above the horizontal, between the marker and the platform of the scale. This test may be performed by holding the marker between the fingertips or by using a mechanical device to insure the 45° angle is maintained. Place the point of the marking medium upon the platform of the scale. Apply vertical pressure by pressing the marker down gradually and uniformly, avoiding variations and shock. The marking medium shall show an average breaking strength of not less than 550 grams with no single break of less than 500 grams when tested as specified. Readings shall be taken at the instant of breaking, provided the breaking point is definite. A slow, mushy deformation or crumbling shall not be considered as a break. The breaking strength shall be based on the average of all tests made. Three markers shall be used for this test and each shall be subjected to not less than two tests, one on each side of the marking medium.

4.3.2 Drying Time. Lines shall dry within 5 seconds on bond paper. There shall be no smearing. Test paper shall be in accordance with A-A-2804A, type III white bond paper having a pH of 5.0 with a basis weight of 60 grams per square meter (16 pound, 17 x 22 - 500). A tolerance of 5% is allowable. Alternately, paper conforming to JCP-O-60 can be used as an alternate source.

4.3.3 Obliteration Quality. Apply three light smooth strokes across text, let dry 3 seconds. Additional applications may be required for rollerball inks. Repeat if necessary. Examine the text to insure obliteration quality. Test paper shall be in accordance with A-A-2804A, type III white bond paper having a pH of 5.0 with a basis weight of 60 grams per square meter (16 pound, 17 x 22 - 500). A tolerance of 5% is allowable. Alternately, paper conforming to JCP-O-60 can be used as an alternate source.

5. Packaging:

5.1 Preservation, packing and marking shall be as specified in the contract or order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

6. Notes:

6.1 Source of Documents. Issues of the following documents in effect on the date of invitation for bids or request for proposal form a part of this document to the extent specified herein.

6.1.1 Federal Acquisition Regulation (FAR) may be obtained from the Superintendent of Documents, Government Printing Office, Washington. DC 20402.

6.1.2 Application for copies of (ANSI) Z1.1, Z1.2 and Z1.3 and (ASQC) B.1, B.2 and B.3 may be obtained from the American Society for Quality Control. PO Box 3005, 611 E. Wisconsin Avenue, Milwaukee, WI 53201-4606.

6.1.3 JCP Specifications may be obtained from Chief Paper Procurement Section, MMPP, US Government Printing Office, North Capital and H Street, NW, Washington DC 20401.

6.1.4 Federal Standards and Specifications may be obtained from the General Services Administration Specifications Section (3FBO-W) in Suite 8100 at 490 L'Enfant Plaza, SW Washington DC 20407.

6.2 National Stock Number Listing(NSN). The following is a list of Nsn's assigned which correspond to this CID. The list may not be indicative of all possible nsn's associated with the CID.

Correction Marker, Tube Type

7510-01-390-0708
7510-01-390-0704

Refill, Correction

7510-01-390-0705

MILITARY INTERESTS:

NONE: DoD has no registered interest in revisions and amendments to this Commercial Item Description until further notice.

Preparing Activity:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.