[INCH-POUND]
A-A-2969
AUGUST 28, 1996
SUPERSEDING
GGG-C-735B
FEBRUARY 29, 1988

COMMERCIAL ITEM DESCRIPTION

CUTTER, ANGLE, HAND OPERATED

The General Services Administration has authorized the use of this Commercial Item Description for procurement of the Class 1(right angle feed) angle cutter specified in GGG-C-735B for all federal agencies.

1. SCOPE

1.1 Scope. This Commercial Item Description covers a hand operated angle cutter used to cut angle iron and slotted angle material.

2. CLASSIFICATION

2.1 Classification. Not applicable.

3. SALIENT CHARACTERISTICS

3.1 Material. The material shall be as specified herein.

3.2 Finish. The cutter shall have smooth, even surfaces and shall be free from scale, pits, nodules, burrs, crack, or other defects.

3.3 Coating. All surfaces shall be a protective coating of enamel, lacquer, or paint to prevent corrosion.

3.4 Identification marking. The cutter shall be marked with the manufacturer's name or identifying symbol, and the state or country of manufacture, unless otherwise specified. All identification markings shall be engraved, etched, molded, or indented directly on the item's surface in such a manner that it remains clearly legible throughout the life of the item.

3.5 Replacement parts. All parts having the same manufacturer's part number shall be constructed to definite standards, tolerances, and clearances in order that such parts may be completely interchangeable, replaced, or adjusted without requiring modification to the part or cutter.

3.6 Screw threads. The screw threads shall be in accordance with Fed Standard. H-28.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document be sent to: General Services Administration, Federal Supply Service, Tools and Appliances Commodity Center, Washington, DC 20406

FSC 5110

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

3.7 Hardness requirement. Both the upper and lower cutting jaws shall be hardened to 55 to 60 on the Rockwell C hardness scale, when tested in accordance with ASTM E-18. The hardness readings shall be made on each blade as close to the cutting edge as possible.

3.8 Design. The cutter shall consist of an upper handle and upper cutting jaw, a lower handle and lower cutting jaw, and a work guide (Figure 1). The cutter shall be designed for cutting and aligning steel and aluminum slotted angle. The cutter capacity shall be 1-1/2 by 3 inches, 12 gauge steel material. The cutting test shall consist of cutting 4 pieces of 1-1/2 by 3 inches 12 gauge slotted steel angle. The material shall be cut at 90 degrees, plus or minus two degrees, and shall be cut on the arrow or indicating mark. Any burrs found at the edges of the material cut shall not exceed 0.010 inch. After the test, all component parts of the cutter shall be examined for any evidence of fracture, distortion, or permanent set.

3.8.1 Work guide. The work guide shall be mounted at a right angle to the longitudinal axis of the cutter. The work guide shall be a minimum of six inches long. The work guide shall have a minimum of one locator pin and one threaded locator hole. The locator pin(s) and locator hole(s) shall be designed and spaced so that they will properly align and index the slotted angle material.

3.8.2 Upper handle and upper jaw. The upper handle shall be made of steel with one end firmly fixed to the linkage. The linkage shall be connected so that the upper jaw opens and closes as the upper handle is raised and lowered.

Figure 1

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:28Z
Check the source to verify that this is the currentversion before use.

3.8.3 Lower handle and lower jaw. One end of the lower handle shall be firmly fixed to the lower jaw. The lower handle shall be of steel designed to steady the cutter during operation.

3.8.4 Weight. The cutter shall weigh a maximum of 20 pounds.

3.8.5 Length. The cutter shall be a minimum of 38 inches in length.

3.9 Workmanship. Details of workmanship shall be in accordance with the best commercial practice. Paints, coatings, platings, and finishes shall be smooth, adherent, continuous, and not stained or discolored. External surfaces shall be free of tool and gouge marks, nicks, or other surface imperfections. The item shall be free from manufacturing workmanship defects (e.g. sharp or rough external edges, corners, or surfaces) and material workmanship defects (e.g. pits, excessive scale, rips, fins, burrs, tears, nodules, cracks, blisters) which may adversely impact the item's serviceability, durability, safety, or appearance.

4. REGULATORY REQUIREMENTS

4.1 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulations (FAR).

4.2 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within the tolerances specified (using conversion tables contained in the latest revision of Federal Standard 376) and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.

5. QUALITY ASSURANCE PROVISIONS

5.1 Contractor conformance. The item delivered to the Government shall conform to the contractually specified requirements. For item characteristics and requirements which are not contractually specified, the delivered item shall conform to the producer's drawings, standards, specifications, and quality assurance practices for the highest quality items provided by the producer to the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as provided for under the provisions of the contract.

5.2 Responsibility for inspection. Unless otherwise specified, the contractor is responsible for the performance of all inspection requirements and may use any commercial facilities (including the contractor's own facilities) suitable for performance of the inspection requirements, unless disapproved by the Government. The Government reserves the right to perform any inspections deemed necessary to assure the item conforms to the specified requirements."

5.3 Bid sample(s). When a bid sample requirement is specified in the solicitation, the bid sample(s) shall be inspected for all salient characteristics. A failure of any bid sample to meet the salient characteristics shall be cause for rejection.

5.4 First article sample(s). When a first article requirement is specified in the contract, the first article sample(s) shall be inspected for all salient characteristics. A failure of any first article sample to meet the salient characteristics shall be cause for rejection.

6. PACKAGING.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:28Z
Check the source to verify that this is the current version before use.

6.1 Packaging. Requirements for preservation, packing, packaging, and marking of packages shall be as specified in the contract or order.

7. NOTES.
(This section contains information of a general or explanatory nature that is not mandatory.)

7.1 Addresses for obtaining copies of referenced documents.

Federal Specifications and Standards: Federal Supply Service Bureau, Specification Section, Suite 8100, 470 L'Enfant Plaza, SW, Washington, DC, 20407.

Federal Acquisition Regulations (FAR): Government Printing Office Superintendent of Documents, Washington, DC 20401-9371.

ANSI/ASQC Z1.4: American Society For Quality Control, PO Box 3005, 611 E. Wisconsin Ave., Milwaukee, WI 43201-4606.

ASTM E18: American Society For Testing Materials, 100 Barr Harbor Dr., West Conshohocken, PA 19428-2959..

7.2 Ordering data.

(a) Title, number, and date of this Commercial Item Description.

(b) When applicable, the appropriate NSN.

(c) When applicable, the specific type, styles, classes, sizes, etc., as specified in the Commercial Item Description.

(d) If bid samples are required and the number of samples required.

(e) If first article samples are required and the number of samples required.

(f) If lot sampling inspection is required and the applicable lot sampling requirements. For example:

Sampling for inspection. Sampling for inspection (both examinations and testing) shall be in accordance with ANSI/ASQC Z1.4.

Inspections. Each sample cutter shall be examined and tested for all salient characteristics. The Inspection Level shall be S-2 with an Acceptable Quality Level of 4.0 expressed in terms of defects per hundred units.

(g) What preservation, packing, packaging, and marking are required.

7.3 National Stock Numbers (NSNs). The following NSN is associated with this CID. This list may not be indicative of all possible NSNs associated with this CID:

NSN 5110-00-662-8868

MILITARY INTERESTS:
NONE: DoD has no registered interest in revisions or notices to this Commercial Item Description until further notice.

Preparing Activity
GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:28Z
Check the source to verify that this is the current version before use.