[INCH-POUND]
A-A-2976
May 1, 1996
PROPOSED
SUPERSEDING
NN-H-85
June 18, 1964

COMMERCIAL ITEM DESCRIPTION

HANDLE, FILE (ADJUSTABLE TYPE)

The General Services Administration has authorized the use of this Commercial Item Description for procurement of the file handles specified in Federal Specification NN-H-85 for all federal agencies.

1. SCOPE

1.1 Scope. This Commercial Item Description covers an adjustable-type handle for use with files or similar tools having tang-type shanks.

2. CLASSIFICATION

2.1 Classification. Not Applicable

3. SALIENT CHARACTERISTICS

3.1 Components and design. The handle shall consist of a body containing jaws or chuck, and an actuating mechanism for securely gripping and holding the jaws during filing operation. It shall be shaped and proportioned to provide a comfortable handgrip.

3.2 Material. The handle shall be of wood and metal construction, or formed entirely from metal, as specified herein.

3.2.1 Wood and Metal. If the handle is made of a combination of wood and metal, the handle shall be of made of hickory, white birch, maple, or beech wood. The jaws shall be made of stamped metal and the ferrule adjusting mechanism shall be made from die cast zinc or a maximum of 22 gauge steel.. The wood portion of the handle shall have no splits, cracks, or knots. The moisture content of the wood shall not exceed 15 percent when measured with an electric moisture meter or other equally suitable method used to determine moisture content.

3.2.1.1 Ferrule. The ferrule shall be made of 22 gage or greater steel and shall be securely impressed around the jaw end of the handle to prevent splitting of the wood.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: General Services Administration, Federal Supply Service, Tools and Appliances Commodity Center (6FETE-C0), Washington, DC 20406

FSC 5110

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

3.2.2 Metal. If the handle is made entirely of metal, the handle may be of aluminum or other metal of sufficient strength and durability for repeated filing operations. The hand-holding portion of the handle shall be knurled or serrated to facilitate gripping of the handle.

3.3 Tang size. The handle shall be capable of holding tangs with widths of 1/8 inch thru 5/16 inch.

3.4 Dimensions. With the tang-holding jaws retracted into the handle to the lowest position, the handle shall have a length of 4-1/8 inch plus or minus 1/2 inch. The diameter at the largest portion of the handle body shall be 1 inch or greater.

3.5 Jaws. The handle shall be fitted with tang-holding jaws extending axially into the handle body. The jaws shall be of proper size and configuration to provide adequate support and grip of the file tang. The jaws shall be properly hardened to prevent deformation and wear under service conditions and file tang-holding surfaces shall be notched or serrated to assure holding the file securely. When a file tang with a 1/8 inch width is placed in the handle, and the adjusting mechanism is tightened hand tight, the file shall not slip or move when a force of 40 pounds is used to pull and push the file along the axis of the handle

3.6 Adjusting Mechanism. The adjusting mechanism shall consist of a threaded metal sleeve or screw, and adjusting cap, which shall open and close the jaws. Screw threads shall be a minimum of 1/2-20 NF.

3.7 Finish.

3.7.1 Wood and metal handles. The handle shall be smoothly finished (except for areas knurled for adjusting mechanism operation). No cracks or splinters shall be acceptable. All metal portions shall be free from burrs and sharp edges.

3.7.2 Metal Handles. Except for the knurled or serrated portions, the handle shall be smoothly finished. The handle shall be free from burrs and sharp edges.

3.8 Identification marking. The handle shall be marked with the manufacturer's name or identifying symbol, and the state or country of manufacture. All marking shall be engraved, etched, molded, or indented directly on the item's surface in such a manner that it remains clearly legible throughout the life of the item.

3.9 Workmanship. Details of workmanship shall be in accordance with the best commercial practice. Coatings and finishes shall be smooth, adherent, continuous, and not stained or discolored. External surfaces shall be free from tool and gouge marks, nicks, or other surface imperfections. The item shall be free from manufacturing workmanship defects (e.g., sharp or rough external edges, corners, or surfaces) and material workmanship defects (e.g., pits, rips, fins, burrs, tears, nodules, cracks, blisters) which may adversely impact the item's serviceability, durability, safety or appearance.

4. REGULATORY REQUIREMENTS

4.1 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4.2 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within the tolerances specified (using conversion tables contained in the latest revision of Federal Standard 376) and all other requirements of this document are met. If a product is manufactured to

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:28Z
Check the source to verify that this is the current version before use.

metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.

5. QUALITY ASSURANCE PROVISIONS

5.1 Contractor conformance. The item delivered to the Government shall conform to the contractually specified requirements. For item characteristics and requirements which are not contractually specified, the delivered item shall conform to the producer's own drawings, specifications, standards, and quality assurance practices for the highest quality items provided by the producer to the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as provided for under the provisions of the contract.

5.2 Responsibility for inspection. Unless otherwise specified, the contractor is responsible for the performance of all inspection requirements and may use any commercial facilities (including the contractor's own facilities) suitable for performance of the inspection requirements, unless disapproved by the Government. The Government reserves the right to perform any inspections deemed necessary to assure the item conforms to the specified requirements.

5.3 Bid sample(s). When a bid sample requirement is specified in the solicitation, the bid sample (s) may be inspected for all salient characteristics by the Government. A failure of any bid sample to meet the salient characteristics shall be cause for rejection.

5.4 First article sample(s). When a first article requirement is specified in the contract, the first article sample(s) shall be inspected for all salient characteristics. A failure of any first article sample to meet the salient characteristics shall be cause for rejection.

6. PACKAGING

6.1 Packaging. Requirements for preservation, packing, packaging, and marking of packages shall be as specified in the contract or order.

7. NOTES

(This section contains information of a general or explanatory nature that is not mandatory.)

7.1 Addresses for obtaining copies of referenced documents.

Federal Acquisition Regulation (FAR): Government Printing Office. Superintendent of Documents, Washington, DC 20402-9371.

ANSI/ASQC Z1.4: American Society For Quality Control, P.O. Box 3005, 611 East Wisconsin Avenue, Milwaukee, WI 43201-4606.

National Bureau of Standards Handbook H28: Government Printing Office. Superintendent of Documents, Washington, DC 20402-9371.

7.2 Ordering data. Purchasers should select the preferred options permitted herein and shall include the following information in procurement documents:

(a). Title, number, and date of this Commercial Item Description.

(b) If bid samples are required and the number of samples required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

(c) If first article samples are required the number of samples required.

(d) If lot inspection is required and the applicable lot sampling requirements.

For example, the following typical lot sampling requirements would be specified in the contract:

Sampling for inspection. Sampling for inspection (both examinations and testing) shall be in accordance with ANSI/ASQC Z1.4.

Inspection. Each sample handle shall be examined and tested for all salient characteristics. The inspection Level shall be Level I with an Acceptable Quality Level of 4.0 expressed in percent defective.

7.3 National Stock Numbers (NSNs). The following NSN is associated with this CID. This list may not be indicative of all possible NSNs associated with this CID.

5110-00-595-8325

Military Interests:

NONE: DoD has no registered interest in revisions or notices to this Commercial Item Description until further notice.

Preparing Activity:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:28Z
Check the source to verify that this is the currentversion before use.