
MILITARY SPECIFICATION SHEET

CONTACTS, ELECTRICAL CONNECTOR, SOCKET, CRIMP REMOVABLE, (FOR MIL-C-81511 SERIES 4 CONNECTORS)


This specification is approved for use by Naval Air Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the contacts described herein shall consist of this document and the latest issue of Specification MIL-C-39029


INACTIVE FOR NEW DESIGN



SIZE 12, 16 & 20 WIRE BARREL



SECTION OF VIEW X



NOTES
1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are based upon 1.00 inch = 25.4 mm.
3 Metric equivalents are in parentheses for overall length and diameter only.
4 Dimensions shown apply after plating
5 Point of initial engagement
6 Maximum cap of .010 inch between hood and body of the contact

© denotes changes

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:31Z
Check the source to verify that this is the current version before use.

TABLE I. Dimensions.

BIN code	A DIA	B DIA	C DIA	D MAX DIA	E MIN DIA ONLY	H DIA	L (REF)	M	N	P	R	S	T	U MAX	W CHAM
166	.0480	.0200	.0555 (1.41)	.055	.028	.022	.607 (15.42)	.115	.155	.218	.145	.396	.250	.038	.006
	.0465	.0180	.0540 (1.37)			.018		.095	.145	.208	.139	.392	.190		.003
167	.0480	.0355	.0555 (1.41)	.055	.028	.022	.607 (15.42)	.115	.155	.218	.145	.396	.250	.038	.006
	.0465	.0335	.0540 (1.37)			.018		.095	.145	.208	.139	.392	.190		.003
168	.0615	.0450	.0760 (1.93)	.076	.0415	.027	.607 (15.42)	.065	.195	.218	.165	.396	.360	.045	.007
	.0600	.0430	.0745 (1.89)			.023		.045	.185	.208	.159	.392	.270		.004
169	.0925	.0645	.1080 (2.74)	.108	.064	.027	.607 (15.42)	.040	.195	.218	.165	.396	.360	.045	.010
	.0910	.0625	.1065 (2.71)			.023		.020	.185	.208	.159	.392	.270		.006
170	.1515	.1020	.1695 (4.31)	.169	.0955	.042	.624 (15.85)	.040	.232	.245	.196	.386	.360	.050	.006
	.1500	.0980	.1680 (4.27)			.038		.020	.216	.235	.190	.382	.250		.012

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:31Z
Check the source to verify that this is the current version before use.

TABLE II. Design characteristics.

BIN code	Color bands			Mating end size	Wire barrel size	Type	Class
	1st	2nd	3rd				
166	Brown	Blue	Blue	23	28	A	B
167	Brown	Blue	Violet	23	22		
168	Brown	Blue	Gray	20	20		
169	Brown	Blue	White	16	16		
170	Brown	Violet	Black	12	12		

TABLE III. Tools.

BIN code	Basic crimping tool	Positioner	Installing tool	Removal tool	
				Wired contact	Unwired contact
166	M22520/2-01	M22520/2-13	M81969/16-04	M81969/16-04	M81969/30-01
167	M22520/2-01	M22520/2-13	M81969/16-04	M81969/16-04	M81969/30-01
168	M22520/2-01 M22520/7-01	M22520/2-14 M22520/7-02	M81969/16-01	M81969/16-01	M81969/30-02
169	M22520/2-01 M22520/7-01	M22520/2-15 M22520/7-03	M81969/16-02	M81969/16-02	M81969/30-03
170	M22520/1-01	M22520/1-09	M81969/16-03	M81969/16-03	M81969/30-04

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:31Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

Dimensions, design characteristics, and configuration See figure and tables I and II.

Tools. See table III.

(C) Vibration Method 2005 of MIL-STD-1344, test condition IV.

(C) Shock (specified pulse): Method 2004 of MIL-STD-1344, test condition A.

Mating contact MIL-C-39029/18.

QPL evaluating activity Naval Avionics Center, Code D-914, Indianapolis, Indiana 46218.

Military part numbers See table IV.

(C) TABLE IV. Military part number

BIN code	Military part number	Supersedes
166	M39029/16-166	M39029/16-23-28
167	M39029/16-167	M39029/16-23-22
168	M39029/16-168	M39029/16-20-20
169	M39029/16-169	M39029/16-16-16
170	M39029/16-170	M39029/16-12-12

Custodians
Navy - AS

Review activities
Navy - EC, SH, MC
DLA - ES

User activities
Navy - OS

Preparing activity
Navy - AS

Agent
DLA - ES

(Project 5935-N109-1)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:31Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE NAVY
DoD-316

U.S. MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Engineering Specifications & Standards Department
Naval Air Engineering Center
Lakehurst, NJ 08733

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:31Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS This form is provided to solicit beneficial comments which may improve this document and enhance its use DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government Fold on lines on reverse side, staple in corner, and send to preparing activity Attach any pertinent data which may be of use in improving this document If there are additional papers, attach to form and place both in an envelope addressed to preparing activity A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed

NOTE This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements

DOCUMENT IDENTIFIER *(Number)* AND TITLE MIL-C39029/16C Contacts, Electrical Connector, Socket, Crimp Removable

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1 ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID RESTRICTIVE LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW

A GIVE PARAGRAPH NUMBER AND WORDING

B RECOMMENDED WORDING CHANGE

C REASON FOR RECOMMENDED CHANGE(S)

2 REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO

DATE

DD FORM 1 OCT 76 1426 Replaces edition of 1 Jan 72 which may be used S/N 0102 LF-001-4260

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:31Z
Check the source to verify that this is the current version before use.