INCH-POUND
MIL-C-39029/28C
AMENDMENT 4
16 July, 1997
SUPERSEDING
AMENDMENT 3
31 March 1994

MILITARY SPECIFICATION SHEET

CONTACTS, ELECTRICAL CONNECTOR, PIN, CRIMP REMOVABLE, SHIELDED, SIZE 12 (FOR MIL-C-38999 SERIES I, II, III AND IV CONNECTORS)

This amendment forms a part of MIL-C-39029/28C, dated 2 March 1979, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* Amendment 3, title, delete "(FOR MIL-C-38999 SERIES I, III AND IV CONNECTORS)" and substitute as shown in this amendment.

PAGE 2

* Figure 1, bin code 414, F dimension, delete ".144" and substitute ".138".
* Figure 1, bin code 414, G dimension, delete ".169" and substitute ".174".

PAGE 3

* Table I, bin code 414, Cable accommodated column, add "M17/152-00001".
Table 1, bin code 415, cable column, delete "MIL-C-915/42" and substitute "MIL-C-24643/28".
Table II, "Installing tool" and "Removal tool", add "1/"; at end of table add:

"1/ Metal tool for MIL-STD-1760 application is to be developed."

PAGE 4

* Table III, bin code 414, Cable accommodated column, add "M17/152-00001".
Table III, bin code 415, cable column, delete "MIL-C-915/42" and substitute "MIL-C-24643/28".

PAGE 5

* Table IV, bin code 414, Cable accommodated column, add "M17/152-00001".
Table IV, bin code 415, cable column, delete "MIL-C-915/42" and substitute "MIL-C-24643/28".

* Table V, bin code 414, Cable accommodated column, add "M17/152-00001".
Table V, bin code 415, cable column, delete "MIL-C-915/42" and substitute "MIL-C-24643/28".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:33Z
Check the source to verify that this is the current version before use.

After "Shock (specified pulse)", add the following new paragraph:

"High impact shock: All contacts shall be wired in a series circuit with 100 milliamperes maximum current flow through the series circuit during shock. Connectors shall be monitored for any discontinuities. A detector capable of detecting all discontinuities in excess of 1 microsecond shall be used. Wired and mated connectors shall be subjected to the test specified in MIL-S-901, grade A with the following modifications and additions. Mounting fixture shall be in accordance with MIL-S-901, light weight. The cable or wire bundle shall be supported on a stationary frame to provide a free flexing cable length between the frame and fixture of not less than 30 inches (914.4 mm):

a. Coupling. Coupled by normal mounting means.

b. Test condition A. Plug shall be terminated with at least 80 percent of wire contacts. The wire bundle shall be provided with straight, open frame, strain relief accessory hardware."

TABLE VI; delete and substitute:

"TABLE VI. Military part number.

Bin code	Military part number	Supersedes
211	M39029/28-211	M39029/28-12A
409	M39029/28-409	M39029/28-12B
410	M39029/28-410	M39029/28-12C
411	M39029/28-411	M39029/28-12D
412	M39029/28-412	M39029/28-12E
413	M39029/28-413	M39029/28-12F
414	M39029/28-414	M39029/28-12G
415	M39029/28-415	M39029/28-12F

"

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assume no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:33Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - AS
Air Force - 85

Review activities:
Army - AR
Navy - EC, MC, OS
Air Force - 11, 15, 17, 99

Preparing activity:
DLA - CC

(Project 5935-4098)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:33Z
Check the source to verify that this is the current version before use.