MIL-C-18875A(Wep)

27 March 1963

Superseding
MIL-C-18875(NORD)
30 June 1955

MILITARY SPECIFICATION

CONTAINER, SIGNAL, MARK 3 MOD 0 (FOR SIGNAL, SMOKE AND ILLUMINATION, MARINE AN, MARK 13 MOD 0)

This specification has been approved by the Bureau of Naval Weapons, Department of the Navy.

1. SCOPE

1.1 Scope - This specification covers air and watertight containers designated as Mark 3 Mod 0 Signal Containers which are intended to serve as combination storage and shipping containers for the Marine AN, Mark 13 Mod 0, Smoke and Illumination Signal. (See 6.1.)

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitations for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

Federal

QQ-Z-325	Zinc Coating, Electrodeposited; Requirements for
PPP-B-601	Boxes, Fiberboard, Wood-Cleated

Military

MIL-C-5541	Chemical Films for Aluminum and Aluminum Alloys
MIL-W-6858	Welding, Aluminum, Magnesium, Non-Hardening Steels or Alloys, and Titanium, Spot, Seam and Stitch
MIL-P-8585	Primer Coating, Zinc Chromate, Low-Moisture-Sensitivity

FSC 8140

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:02Z
Check the source to verify that this is the current version before use.

Military (Continued)

MIL-A-8625(ASG)	Anodic-Coatings, for Aluminum and Aluminum Alloys
MIL-T-9107	Test Reports, Preparation of
MIL-E-16663	Enamel, Semi-Gloss, For Metal Surfaces of Ammunition and Ammunition Containers

STANDARDS

Federal

FED-STD-141	Paints, Varnish, Lacquer and Related Materials, Methods of Inspection, Sampling and Testing
FED-STD-595	Colors

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	Marking for Shipment and Storage

DRAWINGS

Bureau of Naval Weapons

NAVORD LD Sketch 2255173	Container, Signal, Mk 3 Mod 0 (for Signal Smoke and Illumination, Marine AN, Mk 13 Mod 0)

(When requesting any of the applicable documents, refer to both title and number. All requests should be made via the cognizant Government quality control representative. Copies of this specification and other unclassified specifications and drawings required by the contractor in connection with specific procurement functions should be obtained upon application to the Commanding Officer, Naval Supply Depot (Code CDS), 5801 Tabor Avenue, Philadelphia 20, Pennsylvania. All other documents should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:02Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Preproduction - The containers furnished under this specification shall be a product, samples of which have been subjected to and passed the preproduction tests specified herein.

3.2 Design - The containers furnished under this specification shall conform in design to the applicable drawings and shall consist basically of a cover, a body, a gasket and draw pull catches. These containers shall be capable of air and watertight storage for twelve Marine AN, Mk 13 Mod 0, Smoke and Illumination Signals. The drawings applicable to the containers covered by this specification are all those drawings listed on BuWeps Drawing No. NAVORD LD Sketch 255173, Container, Signal, Mark 3 Mod 0 (for Signal, Smoke and Illumination, Marine, AN Mk 13 Mod 0).

3.3 Material - Materials shall be as specified herein and on the applicable drawings, unless specific approval in writing, covering departure therefrom, has been obtained from the Bureau of Naval Weapons prior to manufacture. When alternate materials or methods of manufacture are specified on the drawings, the bidder's selections shall be stated clearly in the proposal.

3.4 Construction - The containers shall be constructed to the dimensions and tolerances specified and assembled in the manner specified on the applicable drawings and as specified herein.

3.4.1 Interchangeability - All parts shall be capable of interchangeable assembly without interference, binding, or misalignment. All parts comprising a permanently joined unit (as by welding) shall be capable of interchangeable joining in the assembled unit and assembly.

3.4.2 Gasket and gasket bearing surface - The gasket shall be cemented in the cover with an adhesive cement approved by the Bureau of Naval Weapons, and the exposed bearing surface shall be coated with talc or graphite to prevent sticking to the bearing surface of the body. The gasket bearing surface of the body shall be a smooth continuous surface perpendicular to the axis of the body within the tolerances specified on the applicable drawings and shall be free of burrs, nicks, voids, scratches, or gouges. The bearing surface shall not injure the gasket during closing and opening of the container and shall ensure proper seating of the gasket. The gasket shall provide sealing on closure of the cover.

3.4.3 Welding - Spot welding shall be in accordance with Specification MIL-W-6858 and shall be accomplished after the metal surfaces have been thoroughly cleaned to ensure sound welds.

3.4.4 Finish - The containers shall be finished as specified herein so as to resist corrosion due to salt spray or atmospheric conditions to which the containers may be subjected when in storage or during normal service life. There shall be no evidence of corrosion on any exposed surface of the assembled container when tested as specified in 4.5.2.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:02Z
Check the source to verify that this is the current version before use.

3.4.4.1 Body and cover - After welding the draw brackets to the body, with the rings assembled, the assembly shall be electro-chemically treated (anodized) to form a dense, thick, uniform oxide finish in accordance with Specification MIL-A-8625 (chromic-acid coating). Immediately following the anodizing, the units shall be primed with one coat of zinc chromate primer conforming to Specification MIL-P-8585.

3.4.4.2 Draw pull catches - Prior to assembly of the catch assembly, the strike, pivot pin, draw pull, and draw pull ring shall be zinc-plated in accordance with Specification QQ-Z-325, Type I, Class 2. Immediately following phosphate treatment the units shall be primed with one coat of zinc chromate primer conforming to Specification MIL-P-8585, Type I.

3.4.4.3 Assembly - After final assembly, the entire outside of the container, excluding the gasket and inner carton, shall have a chemical film applied in accordance with Specification MIL-C-5541. The chemical films shall be produced by treatments controlled and operated to give a uniform product and shall be continuous and free from breaks, scratches, or other damage affecting the serviceability of the film. After chemical treatment, the assembly shall be given one coat of enamel conforming to Specification MIL-E-16663, Color Number 26231 of Standard FED-STD-595. The enamel shall provide a smooth, hard, tough finish with a dry film thickness of 1.5 to 2.0 mils. Draw catches shall function freely after enameling.

3.4.4.4 Surface roughness - All burrs and sharp edges shall be removed. Edges shall be machined to the radius or chamfer indicated on the applicable drawing. Surface roughness on rolled or drawn, cut, punched or machined surfaces shall be as specified on the applicable drawings. All surfaces shall be free from rough spots, protrusions, dents, or similar defects which could interfere with the assembly of the container components, interfere with stacking or loading of the container, cause injury to personnel or damage contents during loading, handling and shipping.

3.5 Interior packing - Interior fiberboard packing shall be furnished by the manufacturer only when directed by the contract or order. (See 6.2.)

3.6 Performance -

3.6.1 Airtightness - The containers shall maintain a positive pressure of 2 pounds per square inch without leakage when tested as specified in 4.5.1.

3.7 Marking - All marking or stamping on the container shall be as shown on the applicable drawings. Stamped or embossed lettering shall be legible after the container has been completely finished.

3.8 Workmanship - The container and its components shall be of clean design, well made, and free of any defects which may affect durability, strength, and serviceability.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:02Z
Check the source to verify that this is the current version before use.

3.9 Gages - The contractor shall provide whatever production gages are necessary and adequate to ensure complete interchangeability of all parts, and to determine that all dimensions are within the tolerances shown on the applicable drawings. If so stipulated in the procurement document, the Bureau of Naval Weapons will furnish drawings of pertinent Navy Final Inspection Gages for guidance in design of the contractor's inspection gages. Such a procedure shall not serve to relieve the contractor of his responsibility in design and manufacture of other production gages as may be required for the satisfactory fulfillment of contract requirements.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor responsibility - Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspection set forth in the Specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.2 Classification of tests - The inspection and testing of containers shall be classified as follows:

(a) Acceptance tests.
(b) Preproduction tests.

4.3 Acceptance tests - Acceptance tests shall consist of the following:

(a) Individual tests.
(b) Sampling plan and tests.

4.3.1 Individual tests - Each cover and each body of each container shall be subjected to the airtightness test of 4.5.1

4.3.2 Sampling plan and tests -

4.3.2.1 Lot - All containers manufactured under substantially the same conditions and presented for acceptance at one time shall be considered an inspection lot. The unit of inspection shall be one container.

4.3.2.2 Sampling - Except as specified in 4.3.2.2.1, a random sample of containers shall be selected from each lot offered for acceptance in accordance with Standard MIL-STD-105 at Inspection Level II and AQL of 1.0 percent for major defects and 2.5 percent for minor defects. Samples selected shall be subjected to the visual and dimensional inspection of 4.3.3.

4.3.2.2.1 Sampling for paint test - For the paint test of 4.5.2 a random sample shall be selected in accordance with Standard MIL-STD-105, Appendix I, Inspection Level L4, with an AQL of one percent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:02Z
Check the source to verify that this is the current version before use.

4.3.3 Visual and dimensional inspection - The sampled containers of 4.3.2.2 shall be visually and dimensionally inspected to verify compliance with the applicable drawings and the requirements of this specification not covered by tests. The classification of defects, Table I, shall be used as a basis for the acceptance or rejection of the lot.

Table I

Classification of Defects for Visual Examination of Containers

Examine	Method of Inspection	Defect	Major	Minor
Any component	Visual	Not present	X	
		Not secure	X	
Any dimension	SMI	Not as specified on applicable drawings		X
Any part	Visual	Not interchangeable		X
Gaskets	Visual	Not coated		X
Plating	Visual	Not present	X	
Chemical films	Visual	Not present	X	
Primer	Visual	Not present	X	
Enamel	Visual	Not present	X	
	SMI	Thickness not as specified		X
Draw pull catches	Visual	Do not function freely		X
Surface roughness	SMI	Not as specified		X
Marking	Visual	Not as specified		X
		Illegible		X
Workmanship	Visual	Defect which will affect durability, strength, or serviceability	X	
		Defect not affecting durability, strength or serviceability		X

4.4 Test conditions - Unless otherwise specified, all tests shall be performed at a temperature between 65 degrees and 95 degrees Fahrenheit with ambient humidity.

4.5 Test methods -

4.5.1 Airtightness test - Each cover with its gasket shall be assembled with a master body or its equivalent and each body shall be assembled with a master cover and gasket or their equivalent. The master body and master cover shall be provided with a means for applying air under

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:02Z
Check the source to verify that this is the current version before use.

pressure to the cover or the body being tested and for maintaining 2 pounds per square inch pressure for a minimum of 30 seconds. While under this pressure, the test bodies or covers shall be submerged in water containing one of the following wetting agents; Tween 20, Tween 40, Renex, Duponol or alkylsulfonate used at a concentration of 1 or 2 percent. Observation of evolution of air bubbles shall be made. Bubbles which appear on the surface of the test cover or body but are not released are not to be construed as indicative of failure. A steady or recurring succession of bubbles from any surface or seam shall be cause for rejection.

4.5.2 Paint tests -

4.5.2.1 Knife test - Painted, but otherwise untested containers, shall be tested for paint film flexibility and toughness in accordance with Standard FED-STD-141, Method 617 - Knife test. After testing there shall be no evidence of wrinkling, blistering, cracking, powdering, or flaking of paint in areas adjacent to the scribing.

4.5.2.2 Salt spray test - Containers subjected to the Knife test of 4.5.2.1 shall be further subjected to a 150 hour salt spray test in accordance with Specification TT-P-141, Method 606. On completion of the test there shall be no evidences of corrosion on any exposed surface of the assembled container.

4.5.3 Preproduction testing -

4.5.3.1 Preproduction test sample test by the contractor - Unless otherwise specified, the contractor shall furnish, for preproduction testing, five complete containers. The preproduction test samples shall be manufactured using the methods and procedures prepared for full production. The contractor shall have subjected each of the preproduction sample containers to all of the tests of this specification. Containers subjected to the preproduction tests shall not be offered to the Government unless reworked to bring to a new condition and submitted to the Acceptance tests of this specification.

4.5.3.2 Preproduction test reports - After the contractor completes the preproduction tests, he shall prepare a preproduction test report in accordance with Specification MIL-T-9107 and furnish three complete copies of photographs and of the report (including one reproducible copy of the report), to an activity designated in the contract or by the procuring agency, for the purpose of determining compliance with all requirements of the contract, this specification, and the applicable drawings. Further production of the containers by the contractor prior to approval of the contracting activity or the completion of the tests on preproduction samples shall be at the contractor's risk.

4.6 Resubmittal of samples - When lots of material are resubmitted for production inspection in accordance with contractual directives, samples shall be selected so as to employ tightened inspection (Level III) as described in Standard MIL-STD-105, for visual inspection and the resubmitted samples for production sample tests, after reworking of rejected lots by the contractor, shall be increased proportionally to the original sample size selected for tightened inspection as outlined in

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:02Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packing - Unless otherwise specified in the contract or order, packing shall be Level C. (See 6.2.)

5.1.1 Level C -

5.1.1.1 Containers covered by this specification shall be packed in a manner which will provide protection from damage during direct shipment from the contractor to the first receiving activity for immediate use.

5.2 Marking -

5.2.1 In addition to any special marking required by the contract or order, all marking shall be in accordance with Standard MIL-STD-129.

6. NOTES

6.1 Intended use - The containers covered by this specification are intended to serve as combination storage and shipping containers for protection during handling, shipping, and storage of the Marine AN, Mark 13 Mod 0, Smoke and Illumination Signal.

6.2 Ordering data - Procurement documents should specify the following:

(a) Title, number, and date of this specification.

(b) Notation that drawings applicable to this procurement are all those drawings listed on BuWeps Drawing No. NAVORD LD Sketch 255173, Container, Signal, Mk 3 Mod 0 (for Signal - Smoke and Illumination, Marine, AN Mk 13 Mod 0).

(c) Quantity desired.

(d) Whether interior packing is desired (3.5).

(e) Level of packing, if other than Level C (5.1).

Notice - When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, theUnited States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:02Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET
NAVWEPS FORM 4121/3 (8-62)

FORM APPROVED
BUDGET BUREAU NO 45-R309

INSTRUCTIONS

This sheet is to be filled out by Government or contractor personnel involved in the use of this specification in procurement of products for ultimate use by the activity shown or the reverse of this sheet.

This sheet is provided for obtaining information which will aid the activity shown in insuring that through use of this specification suitable products can be procured with a minimum amount of delay, and at the least cost.

Comments and the return of this sheet will be appreciated

Fold on dotted lines on reverse side, staple in corner, and send to the activity shown

SPECIFICATION *(No and abbrev title)*

ORGANIZATION	CITY	STATE

CONTRACT NUMBER	QUANTITY OF ITE IS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A DIRECT GOVERNMENT CONTRACT ☐ OR A SUBCONTRACT ☐

1 HAS ANY PART OF THIS SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
(If so give paragraph number and wording and recommendations for correcting the deficiencies)

2 COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3 IS THE SPECIFICATION RESTRICTIVE?
☐ YES ☐ NO IF YES IN WHAT WAY?

4 REMARKS *(Attach any pertinent data which may be of use in improving this specification If additional papers are attached send this form and papers in an envelope This form is addressed for use in window envelope when appropriate)*

SUBMITTED BY *(Print name and title)*	DATE

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:02Z
Check the source to verify that this is the current version before use.

Fold

DEPARTMENT OF THE NAVY
BUREAU OF NAVAL WEAPONS
WASHINGTON 25, D C

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
NAVY DEPARTMENT

Chief, Bureau of Naval Weapons (RREN-5)

Navy Department

Washington 25, D C

Fold

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:02Z
Check the source to verify that this is the current version before use.