| INCH POUND |

MIL-T-18803D(YD)
AMENDMENT 1
9 NOVEMBER 1989

MILITARY SPECIFICATION

TORCH OUTFIT, CUTTING AND WELDING

This amendment forms a part of MIL-T-18803D(YD), dated 22 July 1986 and is approved for use by the Naval Facilities Engineering Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1.1 Specifications and standards. Delete "MIL-V-13877 and title", and substitute "MIL-R-13877 - Regulator, Oxygen, Acetylene, Welding Application." Delete "MIL-C-17223 and title", and substitute "A-A-1153 - Cleaning Sets, Oxygen and Acetylene, Welding and Cutting Torch Tips."

PAGE 5

3.6.1 Design. First sentence - Change to read "All parts of the equipment shall be suitable for use with both oxygen and acetylene, and oxygen and MAPP when assembled, and used as intended in this document."

PAGE 8

3.11 Pressure regulators. Delete and substitute:

"3.11 Pressure regulators. Two regulators shall be supplied, one for use with acetylene and MAPP gas and one for use with oxygen. Each regulator shall be equipped with two pressure gages, one for the cylinder pressure and one for the delivery pressure. All regulators shall be suitable for use with the welding and cutting torch described herein while using oxygen and acetylene, and oxygen and MAPP. The regulators shall be one or two stage design as specified (see 6.2) and shall conform to MIL-R-13877 type I for the acetylene and MAPP regulator, and MIL-R-13877 type III for oxygen. The fuel gas regulator need not carry the UL approval for use with MAPP gas. The interior and internal parts of the regulators shall be neutral to the effects of oxygen, acetylene, and MAPP."

AMSC N/A FSC 3433

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:57Z
Check the source to verify that this is the current version before use.

3.12 Gages. Delete and substitute:

"3.12 Gages. The gages shall be suitable for use with oxygen, acetylene, and MAPP as indicated for the regulators specified in 3.11. Gages shall conform to the requirements of MIL-R-13877 and ANSI B40.1 (with an accuracy of grade A or better) as applicable, except for the features or requirements as modified herein. Gages need not carry UL approval for use with MAPP gas. Each gage shall be built to withstand the rough handling normally encountered in service on a construction project."

3.13.1 Hose connection accessories. Add the following to the end of paragraph "These accessories are in addition to that required in 3.13."

PAGE 13

4.5.4 Delete "MIL-V-13877" and substitute "MIL-R-13877" at two places. Delete "MIL-C-17223" and substitute "A-A-1153."

PAGE 14

6.2.1 e. Change to read - "Type of regulator(s) required (see 3.11)."

Custodian:
Navy - YD

Preparing Activity:
Navy - YD

(Project 3433-N116)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:57Z
Check the source to verify that this is the current version before use.