MIL-T-18830B(SHIPS)
AMENDMENT-2
15 February 1978
SUPERSEDING
Amendment-1
23 April 1975

MILITARY SPECIFICATION

TILE, PLASTIC, FIRE-RETARDANT

This amendment forms a part of Military Specification MIL-T-18830B(SHIPS), dated 18 September 1974, and is approved for use by the Naval Sea Systems Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1, under STANDARDS, MILITARY: Add "MIL-STD-147 - Palletized Unit Loads for 40" x 48" Pallets".

PAGE 2

Table I, fifth column: Delete "3111[1/]" and "3111[2/]" and substitute "3131[1/]" and "3131[2/]".

PAGE 5

4.6.8: Delete and substitute:

"4.6.8 Flexibility (before aging). The specimens shall be conditioned as described in 4.6.1, and tested as described in method 3131 of FED-STD-501. Two specimens, one with the long dimension parallel to the grain of the tile, and one with the long dimension perpendicular to the grain of the tile, shall be tested (see 3.9).

PAGE 10

5.2.1: Delete and substitute:

"5.2.1 Level A. Forty-five 12-inch or eighty 9-inch tiles of one thickness (see 3.5), color, and pattern (see 3.18) shall be packed in a fiberboard box conforming to PPP-B-636, type CF, class-weather-resistant. The box variety, grade, and style selection shall be at the contractor's option. Box closure, waterproofing, and reinforcing shall be in accordance with Method V of the Appendix to the box specification."

5.2.2: Delete and substitute:

"5.2.2 Level B. Forty-five 12-inch or eighty 9-inch tiles of one thickness (see 3.5), color, and pattern (see 3.18) shall be packed in a fiberboard box conforming to PPP-B-636, type CF, class-domestic. The box variety, grade, and style selection shall be at the contractor's option. Box closure shall be in accordance with the Appendix to the box specification."

5.2.4: Add new paragraph:

"5.2.4 Palletization. Tiles, packed as specified (see 5.2), shall be palletized for shipment. Pallets, except as specified herein, shall be of the four-way or partial four-way entry construction. Boxes shall be arranged in a snug and non-shifting manner. Pallet loads shall consist of tiles of one color and pattern (see 3.18), one size (see 3.4), and one thickness (see 3.5), shall be of uniform height, and shall have a full top course. The gross weight of the palletized load shall not exceed 2,500 pounds. Unless otherwise specified (see 6.1.1), shipments to storage/stocking activities and Naval shore-based activities shall be on pallets of the expendable type. Shipments to Naval Forces afloat shall be on wood/plywood pallets of the winged-type construction. Pallet length and width nominally shall be as follows, at the contractor's option: 24 inches by 36 inches, 36 inches by 36 inches, 38 inches by 38 inches, or 40 inches by 40 inches. The pallet load shall be bonded in accordance with the guidelines of MIL-STD-147, load type I. Method of bonding shall be at the contractor's option."

FSC 7220

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:59Z
Check the source to verify that this is the current version before use.

5.3: Delete and substitute:

"5.3 Marking. In addition to any special marking required by the contract or order (see 6.1.1), containers and palletized loads shall be marked for shipment in accordance with MIL-STD-129."

6.1.1: Add: "(g) When pallets other than expendable are required (see 5.2.4)".

NOTE: The margins of this amendment are marked "#" to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing activity:
Navy - SH
(Project 7220-N206)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T11:59Z
Check the source to verify that this is the current version before use.