MIL-G-48226B (AR)
27 October 1982
SUPERSEDING
MIL-G-48226A (PA)
3 October 1975

MILITARY SPECIFICATION

GRENADES, GP: M42 and M46
LEAD CUP ASSEMBLY FOR

This specification is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all departments and agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers requirements and provides quality assurance provisions for loading, assembling and packaging of one type of lead cup assembly for Grenades, GP: M42 and M46.

2. APPLICABLE DOCUMENTS

2.1 Government documents

2.1.1 Specifications and standards - Unless otherwise specified, the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078	- Ammunition, Standard Quality Assurance Provisions, General Specification For
MIL-P-45486	- Pellets, RDX

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspections by Attributes

FSC 1330

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:18Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings, and publications - The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS (See 6.7)

U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND (ARRADCOM)

8798331	- Detonator, Stab: M55
8841278	- Pin
9215330	- Lead Cup Assembly

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications - The following document(s) form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

CODE OF FEDERAL REGULATIONS

Title 49 - Transportation, Parts 100-199

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402. Orders should specify, "49 CFR 100-199 (latest revision)").

2.3 Order of precedence - In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Material - Materials and parts shall be in accordance with the applicable drawings and specifications.

3.2 Lead cup assembly - The lead cup assembly shall comply with all requirements specified on Drawing (Dwg.) 9215330, all associated drawings, and with all requirements specified in applicable speficiations.

3.3 Moisture content of explosive material for loading lead cup - The moisture content of explosive at the time and site of loading shall not exceed 0.10 percent when determined as specified in 4.5.1.

3.4 Functioning test - The lead cup assembly shall be capable of high order initiation by an M55 stab detonator (dwg. 8798331) across a minimum air gap of 0.060 inches. High order detonation will be evidenced by a minimum indentation of .012 inches in a steel witness block when tested as specified in 4.5.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:18Z
Check the source to verify that this is the current version before use.

3.5 Cracks or laminations - The lead cup assembly, including the surface of the explosive, shall be free of all cracks or laminations.

3.6 First article inspection - This inspection contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.7 Workmanship - All parts and assemblies shall be fabricated, loaded and assembled in a thorough, workmanlike manner. They shall be free of burrs, sharp edges, cracks, dirt, grease, rust and other foreign matter. The cleaning method used shall not be injurious to any part, nor shall the parts be contaminated by the cleaning agents. Exterior surface coatings shall be continuous; however a few light scratches not exposing base material may be permitted. All required marking and stamping shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions - Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections - The following types of inspection shall be conducted on this item:

a. First Article Inspection
b. Quality Conformance Inspection

4.3 First article inspection -

4.3.1 Submission - The contractor shall submit a first article sample as designed by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part description	Drawings	Quantity
Lead cup assemblies	9215330	315
Lead cups	9215329	35

4.3.2 Inspections to be performed - See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection - See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:18Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-G-48226B (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Lead Cup Assembly and Components				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Lead Cup Assemblies (Dwg. 9215330)				
	Examination of Defects	315	-	3.2	4.4.2.2
	Functioning Test	315	-	3.4	4.5.3
	Specific Gravity (Information only)	25	-	3.2	4.5.2
	Lead Cups (Dwg. 9215329)	(1)			
	Examination for Defects	35	-	3.2	4.4.2.1

NOTES:

(1) All tooling used in production shall be represented in this sample.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil - Downloaded: 2026-10-22T19:18Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection

4.4.1 Inspection lot formation - Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of Lead Cup Assemblies shall contain:

a. Lead cup of one lot interfix number from one manufacturer.
b. RDX from one batch or blending of batches which results in homogeneity of material used in loading the lead cups.

4.4.2 Examination - See MIL-A-48078.

a. Sampling plans - Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:18Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9215329
4.4.2.1	Cup, lead (prior to loading)				NEXT HIGHER ASSEMBLY 9215330
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Thickness at bottom of cavity (see 4.5.4)		0.40%	3.2	Gage
102	Distance from closed end to flange (see 4.5.4)		0.40%	3.2	Gage
103	Flange diameter, min. (see 4.5.4)		0.40%	3.2	Gage
104	True position of flange diameter to outside diameter (see 4.5.4)		0.40%	3.2	Gage
105	Diameter at longest basic length from closed end (see 4.5.4)		0.40%	3.2	Gage
106	Puncture or deep scratch		0.40%	3.2	Visual
Minor					
201	Thickness of cup wall (see 4.5.4)		0.65%	3.2	Gage
202	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:18Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Lead Cup Assembly				9215330
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Cup cut, split, cracked or laminated		100%	3.5	Visual
Major					
101	Moisture content of explosive material	(1)		3.2	4.5.1
102	Specific gravity of lead cup charge	5/4 hrs	See 4.5.2	3.2	4.5.2
103	Functioning test	(2)		3.2	4.5.3
104	Distance from closed end to flange, max.		0.40%	3.2	Gage
105	Charge above or excessively below flush		0.40%	3.2	Gage
106	Outside diameter		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.7	Visual

NOTES: (1) Sampling plan shall be in accordance with MIL-P-45486.
(2) Sampling shall be 200 assemblies per lot accept on 2 failures reject on 3 failures. An alternate sampling plan shall be 20 assemblies (5 per machine per hour) from each four hours production. If any one fails, the four hours production shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:18Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.3	Box, set-up, inner (prior to sealing)		See Section 5
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Lead cup missing or incorrectly positioned		0.40%	3.2	Visual
102	Cushion missing		0.40%	3.2	Visual
Minor	None defined				

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:18Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.4	Box, set-up, inner		See Section 5
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Box damaged to the extent that contents are exposed		0.40%	3.2	Visual
Minor					
201	Contents loose		0.65%	3.2	Manual
202	Marking misleading or unidentifiable		0.65%	3.2	Visual
203	Label missing or badly wrinkled		0.65%	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:18Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Outer set-up box				See Section 5
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Box damaged to the extent that contents are exposed		0.40%	3.2	Visual
102	Sealing strip incomplete, badly wrinkled or missing		0.40%	3.2	Visual
Minor					
201	Contents loose		0.65%	3.2	Manual
202	Marking misleading or unidentifiable, including incorrect color code		0.65%	3.2	Visual
203	Label missing or badly wrinkled		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:18Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Sealed Barrier Bag				See Section 5
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Waterproofness destroyed by separation of heat seal, or rip, tear or puncture		0.40%	3.2	Visual
Minor 201	Marking misleading or unidentifiable, including incorrect color code		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:18Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.7	Box, unsealed wooden packing				See Section 5
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Incorrect number of cartons		0.40%	3.2	Visual
102	Fillers missing		0.40%	3.2	Visual
Minor	None defined				

NOTES:

DRD[illegible]-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:18Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.8	Box, Sealed Wooden Packing				See Section 5
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Hardware missing, broken or loose		0.40%	3.2	Visual/Manual
102	Strapping missing, broken or loose		0.40%	3.2	Visual/Manual
103	Contents exposed		0.40%	3.2	Visual
104	Board broken or split		0.40%	3.2	Visual
105	DOD symbol misleading or unidentifiable		0.40%	3.2	Visual
Minor					
201	Hardware improperly engaged		0.65%	3.2	Visual/Manual
202	Contents loose		0.65%	3.2	Manual
203	Strapping improperly assembled		0.65%	3.2	Visual
204	Marking misleading or unidentifiable including incorrect color code		0.65%	3.2	Visual
205	Car seal missing, unsealed or improperly positioned		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:18Z
Check the source to verify that this is the current version before use.

4.4.3 Testing - This section is not applicable to this specification.

4.4.4 Inspection equipment - The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078, and 6.3 herein.

4.5 Test methods and procedures -

4.5.1 Moisture content of explosive material for loaded lead cup - The contractor shall provide adequate controls to insure compliance with the applicable requirements. The moisture content of each lot of explosive material shall be determined at the loading station at the time of loading the lead cups. This determination shall be made at least once each eight (8) hours of production. Sampling shall be in accordance with MIL-P-45486. In addition, if the moisture content fails to comply with the requirement specified on the applicable drawing and loading has not begun, the charge lot shall be rejected until corrective action has been taken as verified by repeating the moisture content determination. If loading has begun, lead cups loaded with the non-conforming explosive material shall be rejected.

4.5.2 Specific gravity of lead cup charge - A sample of five (5) loaded lead cup assemblies shall be selected from each four (4) hours production. The loaded lead cup shall be weighed in air and the weight shall be recorded as A. The loaded lead cup shall be weighed in water at a temperature of 25°C, and the weight shall be recorded as B. The volume of the loaded cup shall be determined by subtracting B from A (A-B) and the volume shall be recorded as C. The RDX composition shall be removed from the lead cup by washing the cup with acetone. The empty cup shall be weighed in air and the weight shall be recorded as D. The empty cup shall be weighed in water at 25°C, and the weight shall be recorded as E. The volume of the empty cup shall be determined by subtracting E from D (D-E), and the volume shall be recorded as F. The volume of the RDX shall be determined by subtracting the volume of the empty cup (F) from the volume of the loaded lead cup (C), (C-F), and the volume shall be recorded as G, (C-F=G). The weight of the RDX composition shall be determined by subtracting the weight of the empty lead cup in air (D) from the loaded lead cup in air (A), and the weight shall be recorded as H, (A-D=H). The specific gravity shall be determined as follows:

$$\text{Specific Gravity} = \frac{H}{G}$$

G = Volume of RDX
H = Weight of RDX

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:18Z
Check the source to verify that this is the current version before use.

If any sample fails to conform to the drawing requirements, the four (4) hours production shall be rejected.

NOTE: Analytical balance shall be capable of reading weights in milligrams with a sensitivity of 0.2 of a milligram.

4.5.3 Functioning test - The lead cup shall be placed in a test fixture, over a steel block (1" X 3/4" X 1/4", grade 1018 or 1020, Rockwell B 85-95). A weight of 1.00 ± 0.01 ounce shall be dropped from a maximum height of one (1) foot on the firing pin. (Dwg. 8841278) or approved alternate. Observation shall be made for satisfactory functioning evidenced by the depth of the indentation in the steel block (see 3.4). In the event that the detonator does not fire, the test shall be considered a "no test."

4.5.4 Dimensional control of stamped parts - In place of the normal sampling associated with the Classification of Defects, and with the approval of the Contracting Officer, a sample of at least ten (10) parts may be dimensionally inspected to qualify the tool used in the stamping process for use in production. In addition, a random sample of five (5) parts shall be selected from the last portion of each hour's production for dimensional inspection as a control of the tool during production.

If any defective parts are found during qualification of the tool, the tool producing the defective part shall not be used in production.

If any defective parts are found when inspection is performed for control of the tool, the tool producing the defective part shall be removed from production. Further, that portion of production since the last tool control check shall be returned to the contractor for corrective action.

All tools removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test above. The Contractor may request a change of inspection frequency providing he presents objective evidence to the Contracting Officer to substantiate the request.

5. PACKAGING

5.1 Preservation

5.1.1 Level C - The lead cup assemblies shall be preserved and packaged in accordance with the Code of Federal Regulations, Title 49, Parts 100-199.

5.2 Packing -

5.2.1 Level C - The lead cup assemblies preserved and packaged as specified in 5.1, shall be packed in accordance with the Code of Federal Regulations, Title 49, Parts 100-199.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:18Z
Check the source to verify that this is the current version before use.

5.3 Marking - Marking shall be in accordance with the Code of Federal Regulations, Title 49, Parts 100-199.

5.4 Shipping - When assemblies from more than one lot are shipped at one time, such as in a carload, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Intended use - The components covered by this specification are intended for use on Grenades, GP: M42 and M46.

6.2 Ordering data - See MIL-A-48078.

6.3 Submission of inspection equipment designs for approval - See MIL-A-48078. Submit equipment designs, as required, to Commander, US Army ARRADCOM, ATTN: DRDAR-QAR-I, Dover, NJ 07801.

6.4 Submission of test data - In addition to the normal distribution of records, when the lead cup is procured by the U.S. Army Armament Command, one (1) copy of all ballistic data and ammunition data cards shall be forwarded to: Commander, US Army ARRADCOM, ATTN: DRDAR-QAR-Q, Dover, NJ 07801.

6.5 Submission of results of contractor-conducted examinations and tests - Data shall be submitted in accordance with data item DI-R-1721 on the DD Form 1423 for the contract.

6.6 Check test for possible deterioration - The following test is designed to prevent lead cups that have deteriorated from being assembled into major ammunition items. The test shall be performed on lead cups from each lot which have been stored for more than two years, or under adverse conditions for any period of time. If the specification for the ammunition item into which the lead cups are assembled does not require that the check test be performed, the contracting officer should insert in the contract a provision for the performance of the check test. The contracting officer will arrange for the contractor to be reimbursed for expense incurred in his performance of the check test for possible deterioration.

6.6.1 Functioning - The sampling plan for the test shall be in accordance with Standard MIL-STD-105, using Code letter K and an AQL of 0.65 percent. The test shall be performed as specified in 4.5.3 using equipment in accordance with 4.4.4.

6.7 Drawings - Drawings listed in Section 2 of this specification under the headings U.S. Army Armament Research and

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:18Z
Check the source to verify that this is the current version before use.

Development Command (ARRADCOM) may also include drawings prepared by and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

6.8 Changes from previous issue - The margins of this specification are marked with vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army-AR

Preparing activity:
Army-AR

Project 1330-A171

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:18Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armamemnt R&D Command
ATTN: DRDAR-QAR
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:18Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-G-48226B Grenades, GP; M42 and M46 Lead Cup Assembly For

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ *IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.*

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:18Z
Check the source to verify that this is the current version before use.