INCH-POUND

MIL-L-70751A(AR)
11 September 1992
SUPERSEDING
MIL-L-70751(AR)
25 August 1989

MILITARY SPECIFICATION

LEAD, PARTS, ASSEMBLY AND PACKAGING FOR

This specification is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification contains the requirements and quality assurance provisions for fabrication of parts, assembly and packing for a Lead Assembly (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards and handbooks. The following specifications, standards and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issue of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

MILITARY

MIL-A-2550	-Ammunition and Special Weapons, General Specification for
MIL-A-48078	-Ammunition, Standard Quality Assurance Provisions, General Specification for

STANDARDS

MILITARY

MIL-STD-109	-Quality Assurance Terms and Definitions

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army ARDEC, ATTN: SMCAR-BAC-S, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1305

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

MIL-STD-1168	-Lot Numbering of Ammunition.
MIL-STD-1169	-Packaging, Packing and Marking for Shipment of Inert Ammunition Components.
MIL-STD-1190	-Minimum Guidelines for Level C Preservation, Packing and Marking.

(Unless otherwise indicated, copies of federal and military specifications, standards and handbooks are available from the Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094).

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues shall be those on effect of the date of solicitation.

DRAWINGS (see 6.5)

U.S. ARMY ARMAMENT, RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

PRODUCT

9384824	-Lead Assembly.

PACKAGING

7548101	-Box, Packing Ammo for Primer and Delay Assembly.
7548103	-Box, Set-Up Packing, Ammo Outer, for Small Explosive Components w/o Primary Explosives.
7548104	-Box, Set-Up Packing, Ammo Inner, for Small Explosive Components w/o Primary Explosives.

INSPECTION

12913007	-Lead Propagation Test Assembly.
12913004	-Weight

(Copies of other Government documents, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

2.1.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in the document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings and specifications. (See 4.5.1).

3.2 Components and assemblies. The components and assemblies to be used in first article samples and production lots shall comply with all requirements specified on Drawing 9384824 and associated specifications and standards. (See 4.5.1).

3.3 Manufacturing process. All parts and assemblies shall be manufactured by the equivalent process used for first article approval and no deviations from that process shall be made without contracting officer approval.

3.4 Function.

3.4.1 Sensitivity and output. The lead assembly when initiated by a high order detonator output will function high order and will indent the steel witness block to a minimum depth of 0.021 inch when tested as specified in 4.5.2.1.

3.5 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection in accordance with the technical provisions herein (see 4.3 and 6.3).

3.6 Workmanship. All parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner, and all manufacturing, processing, and assembly operations shall be correctly performed. All parts and assemblies shall be clean and free of burrs, sharp edges, unblended radii, surface defects, chips, dirt, grease and oil, corrosion products and other foreign matter that may impair proper functioning. The cleaning method used shall not be injurious to any part or assembly, nor shall they be contaminated by the cleaning agent. Exterior surface shall be continuous except for a few light scratches not exposing base material. All required markings and stampings shall be neat and sharply defined. Required packing shall be dry.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may utilize his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of Sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 General provisions. Unless otherwise specified herein, the provisions of MIL-A-48078 and MIL-A-2550 shall apply and form a part of this specification. Reference shall be made to MIL-STD-109 to define quality assurance terms used herein.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First Article Inspection (See 4.3).

b. Quality Conformance Inspection (See 4.4).

4.2.1 Inspection conditions. Unless otherwise specified, all inspections shall be performed in accordance with the test conditions specified in the requirements and test method paragraphs in this specification.

4.3 First article inspection.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:56Z
Check the source to verify that this is the current version before use.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2 and 4.3.3. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawing	Quantity
Lead Assemblies	9384824	315 (min.)

4.3.2 Inspections to be performed. The examinations and tests listed in Table I shall be performed on the first article sample (See MIL-A-48078).

4.3.3 Rejection. If any of the applicable components, subassembly or assembly fails to comply with the requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon the failure of lead components, subassembly or assembly to comply with any of the stated requirements. In the event of rejection, the Government reserves the right to require the contractor to take corrected action and submit a new first article quantity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF CHARACTERISTICS

MIL-L-70751A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
	Lead Assembly	1 OF 1	9384824
			NEXT HIGHER ASSEMBLY
			--

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Lead Assembly			
	Examination for Defects	315 1/	3.2, 3.3	4.4.2.1 and 4.4.2.2
	Functioning - Sensitivity & Output	315 2/	3.4.1	4.5.2.1

NOTES:

1/ Accept with three or less defects, reject on four or more defects.
2/ Accept with two or less defects, reject on three or more defects.

AMSMC Form 1570a, 1 Jul 89

Replaces AMSMC Form 1570a, 1 Apr 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:56Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. The term "inspection lot" is defined as a homogeneous collection of units of product from which a representative sample is drawn or which is inspected 100 percent to determine conformance with applicable requirements. Units of product selected for inspection shall represent only the inspection lot from which drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, using the same materials and methods, in accordance with the same drawing, same drawing revisions, same specifications and same specification revisions. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein, regardless of the type of inspection procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168. Each lot shall contain PBXN-5 from an acceptable lot from one manufacturer with one lot interfix number.

4.4.2 Examinations and tests. The examinations listed herein shall be performed on inspection lots as defined in 4.4.1. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.4.4.

a. Classification of characteristics. Quality conformance examinations and tests are specified in the following Classification of Characteristics paragraphs. The contractor's quality program or detailed inspection plan shall provide assurance of compliance of all characteristics with the applicable drawing and specification requirements utilizing as a minimum the conformance criteria specified herein. When cited herein, attributes sampling inspection shall be conducted in accordance with Table II below, using the inspection levels stated in the Classification of Characteristics paragraphs.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

TABLE II. Attributes sampling inspection

Lot Size	Inspection Levels					
	I	II	III	IV	V	VI
2 to 8	*	*	*	*	5	3
9 to 15	*	*	*	13	5	3
16 to 25	*	*	*	13	5	3
26 to 50	*	*	32	13	5	3
51 to 90	*	*	32	13	13	5
91 to 150	*	125	32	13	13	5
151 to 280	*	125	32	32	20	8
281 to 500	*	125	32	32	20	8
501 to 1200	*	125	80	50	20	13
1201 to 3200	1250	125	80	50	32	13
3201 to 10000	1250	125	125	50	32	13
10001 to 35000	1250	315	125	80	50	13
35001 to 150000	1250	315	125	80	50	13
150000 to 500000	1250	500	200	125	50	13
500001 and over	1250	500	200	125	50	13

Numbers under inspection levels indicate sample size; asterisks (*) indicate one hundred percent inspection. If sample size exceeds lot size, perform one hundred percent inspection. Accept on zero and reject on one or more for all inspection levels.

b. Alternative quality conformance provisions. Unless otherwise specified or provided for in the contract, alternative quality conformance procedures, methods, or equipment, such as statistical process control, tool control, other types of sampling procedures, etc., may be used by the contractor when they provide, as a minimum, the level of quality assurance required by the provisions specified herein. Prior to applying such alternative procedures, methods, or equipment, the contractor shall describe them in a written proposal submitted to the Government for evaluation (see 6.7). When required, the contractor shall demonstrate that the effectiveness of the proposed alternative(s) is equal to or better than the specified quality assurance provisions herein. In cases of dispute as to whether the contractor's proposed alternative(s) provide equal assurance, the provisions of this specification shall apply. All approved alternative inspection provisions shall be specifically incorporated into the contractor's quality program plan or detailed inspection system, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-L-70751A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Lead Assembly (Non-destructive Test)	1 OF 1	9384824
			NEXT HIGHER ASSEMBLY: 11820609

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
CRITICAL	None defined.			
MAJOR				
101	Total height	Level II	3.2	SMTE
102	Outside diameter	Level II	3.2	SMTE
103	Cracks or splits	100%	3.2	Visual
104	Caked explosives on exterior	100%	3.2	Visual
MINOR				
201	Crimp not full 360 degrees	Level IV	3.2	Visual
202	Stencil, ink, anodize, missing or wrong color	Level IV	3.2	Visual
203	Poor workmanship other than critical above	Level IV	3.6	Visual

NOTES:

AMSMC Form 1570a, 1 Jul 89 Replaces AMSMC Form 1570a, 1 Apr 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Lead Assembly (Destructive Test)	1 OF 1	9384824
			NEXT HIGHER ASSEMBLY 11820609

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
CRITICAL	None defined.			
MAJOR				
101	Sensitivity and output	Level II	3.4.1	4.5.2.1
MINOR	None defined.			

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. The tests (First article and Quality Conformance) shall be performed on inspection lots as defined in 4.4.1. The sampling plans for the test shall conform to the provisions of 4.4.2.b.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column starting with paragraph 4.4.2.1. The contractor shall use inspection equipment in accordance with drawing 12913007 and 12913004. See Section 6.2 of MIL-A-48078 and 6.2 herein.

4.5 Methods of inspection.

PRECAUTION - The specification covers sampling and testing of explosive materials which are potentially hazardous to personnel. Accordingly, it is emphasized that all applicable safety rules, regulations and procedures must be followed in handling and processing these materials.

4.5.1 Materials, components and processes. Compliance with all requirements of Section 3 of this specification shall be ascertained by current and continuing examination of inspection and test data to determine that all components (parts, subassemblies, and materials) have been inspected and tested and found to comply with their respective drawing and specification requirements, and that all specified manufacturing processes have been followed.

4.5.1.1 Visual and mechanical inspections. The visual, manual and mechanical inspections and tests shall verify compliance with the requirements of Section 3 and 5 of this specification in accordance with 4.4.2 herein and Table I.

4.5.2 Functioning.

4.5.2.1 Sensitivity and output. A random sample of leads shall be selected from each lot. The lead shall be assembled with a detonator (Dwg. 9384806) into the test setup specified in Dwg. 28202214, a 0.25 ± 0.01 ounce weight shall be dropped on the firing pin from a height of four inches, maximum. A lead that fails to fire or fires but fails to produce a dent in the steel witness block of the required depth shall be classed as defective if the detonator confinement sleeve expansion is 0.330 inch diameter or greater. If the confinement sleeve expansion is less than 0.330 inch diameter, the lead assembly shall not be classed defective, but the detonator shall be classed defective and the result a no-test. The indentation depth shall be measured using a probe with a 0.005 inch plus or minus 0.017 inch spherical radius tip.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:56Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Unit Packaging.

5.1.1 Level A. Not available.

5.1.2 Level B. Unit packaging for the Lead Assembly shall be in accordance with Drawing 7548104 SH2 Line 8.

5.1.3 Level C. Same as Level B.

5.2 Packaging.

5.2.1 Level A. Not available.

5.2.2 Level B. Packaging for the Lead Assembly shall be in accordance with Drawing 7548103 SH2 Line 8.

5.2.3 Level C. Same as Level B.

5.3 Packing.

5.3.1 Level A. Not available.

5.3.2 Level B. Packing for the Lead Assembly shall be in accordance with Drawing 7548101 SH3.

5.3.3 Level C. Same as Level B.

5.4 Marking.

5.4.1 Level A. Not available.

5.4.2 Level B. Unit packaging, packaging, and packing shall be in accordance with Drawing 7548103, 7548104 and 7548101.

5.4.3 Level C. Same as Level B.

5.5 Packaging, packing and marking for inert lead assembly parts.

5.5.1 Packaging, packing and marking. Inert lead parts shall be in accordance with MIL-STD-1169 for all applicable levels of packaging.

5.6 Shipping. When Lead from more than one lot are shipped at one time, each lot shall be kept separate and the division between lots clearly indicated to prevent mixing of lots in transit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

5.6.1 Unitization. Unitization shall be in accordance with MIL-STD-1190.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The lead assemblies are intended for use in the following fuze:

25mm	M758	11820609

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number and date of this specification.

b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.2).

c. Requirements for submission of first article sample (see 3.5).

6.3 Submission of inspection equipment designs for approval. (See MIL-A-48078). Submit two copies of designs as required to Commander, U.S. Army ARDEC, ATTN: SMCAR-QAF-I(D), Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract.

6.4 Check test for possible deterioration. The following test is designed to prevent leads that have deteriorated from being assembled into major ammunition items. The test shall be performed on detonators from each lot which have been stored under normal conditions for more than two years, or under adverse conditions for any period of time. If the specification for the ammunition item into which the leads are assembled does not require that the check test be performed, the Contracting Officer should insert in the contract, a provision for the performance of the check test. The Contracting Officer will arrange for the contractor to be reimbursed for expense incurred in his performance of the check test for possible deterioration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

6.4.1 Functioning. The sample size and acceptance or rejection criteria shall be in accordance with Table II. Test shall be performed as specified in 4.5.4, using equipment in accordance with 4.4.4.

6.5 Drawings. Drawings listed in Section 2 of this specification under the heading U.S. Army Armament Research, Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as U.S. Army Armament, Research and Development Command (ARRADCOM), Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.6 Subject term (keyword) listing.

Sensitivity & Output
Caked explosives
Anodize

6.7 Submission of alternative quality conformance provisions. Unless otherwise specified in the contract, proposed alternative quality evaluation by the technical activity responsible for the preparation of this specification.

6.8 Changes from previous issue. Marginal notations are not used in the revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1305-AE34)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:56Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-L-70751	2. DOCUMENT DATE (YYMMDD) 11 SEPTEMBER 1992

3. DOCUMENT TITLE
LEAD, PARTS, ASSEMBLY AND PACKAGING FOR

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets if needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (if applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME U. S. Army ARDEC Specifications And Standardization Office/Bldg. 6	b. TELEPHONE (Include Area Code) (1) Commercial (201) 724-6675 (2) AUTOVON 880-6675
c. ADDRESS (Include Zip Code) ATTN: SMCAR-BAC-S Picatinny Arsenal, N. J. 07806-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

DD Form 1426, OCT 89 *Previous editions are obsolete.* 198/290

Source: https://assist.dla.mil -- Downloaded: 20261O-23T03:56Z
Check the source to verify that this is the current version before use.