MILITARY SPECIFICATION

POWER SUPPLY ASSEMBLY, FOR MINES, M718A1/M741A1, SYSTEM

This specification is approved for use within U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification contains requirements and provides Quality Assurance provisions for the fabrication of parts, assembly and packing of Power Supply Assembly used in the M718A1\M741A1 Mines, Electronic Assembly.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specification and standards. The following documents of the issue in effect on date of invitation for bids or request for proposals, from a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of specifications and Standards (DoDISS) and supplement thereto, listed in the solicitation.

SPECIFICATIONS

MILITARY

MIL-S-45743	-	Soldering, Manual Type, High Reliability Electrical and Electronic Equipment.
MIL-A-48078	-	Ammunition, Standard Quality Assurance Provisions, General Specifications For.

STANDARDS

MIL-STD-105	Sampling Procedures and Tables For Inspection By Attributes.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to Commander, U.S Army Armament, Munitions and Chemical Command, Attn AMSMC-QA, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter

AMSC N/A FSC 1345

DISTRIBUTION STATEMENT' A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026l0-23T03:50Z
Check the source to verify that this is the currentversion before use.

MIL-STD-202 - Test Methods for Electronic and Electrical Component Parts.
MIL-STD-1168 - Lot Numbering of Ammunition
MIL-STD-1169 - Packaging, Packing and Marking For Shipment Of Inert Ammunition Components.

2.1.2 Other Government documents, drawings, and publications; The following other Government documents, drawings and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

US ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

9287159 Molding, Power Supply
9342580 Power Supply Assembly

(Copies of specifications, standards drawings and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the Contracting Officer).

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings and specifications.

3.2 Components and assemblies. The components and assemblies shall comply with all requirements specified on drawing 9342580 and 9287159 with all requirements specified in applicable specifications and standards.

3.3 Electrical requirement.

3.3.1 Non-activated voltage. Each battery cell shall be inactivated and measure less than .005 volts.

3.3.2 Shorting bar resistance. The shorting bar and connector assembly shall have less than 0.8 ohm resistance measured between the terminals.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:50Z
Check the source to verify that this is the current version before use.

3.4 Battery lead weld pull test. The battery assembly lead welds shall not fail or show any evidence of tearing or breaking when the leads are subjected to a five (5) pound plus two (2) pounds pull.

3.5 Battery lead weld integrity. The battery assembly lead welds shall not show any evidence of fracture, crack or any damage to the battery case (hole in case).

3.6 Soldering.

3.6.1 Shorting bar and connector assembly solder workmanship. Soldering of the shorting bar and connector assembly shall be in accordance with MIL-S-45743.

3.6.2 Solderability. The power supply assemblies ribbon leads shall comply with solderability requirements of MIL-S-45743.

3.7 First article inspection. When specified in the contract or purchase order, a sample shall be subjected to first article inspection in accordance with technical provisions herein. (See 4.3)

3.8 Workmanship. All parts and assemblies shall be fabricated and finished in a thorough workmanlike manner and all manufacturing processing and assembly operations shall be correctly performed. All parts shall be free from chips, dirt, grease, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the part be contaminated by the cleaning agents. All marking and stamping shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Unless otherwise specified herein, or in the contract, the provisions of MIL-A-48078 shall apply, and are hereby made a part of this detail specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:50Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items must meet all requirements of section 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item.

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample, as designated by the Contracting Officer, for evaluation in accordance with the provisions of 4.3.2 and 4.3.3. The first article sample shall consist of the parts/assemblies listed below in the quantities indicated.

Part Description	Drawing	Quantity
Power Supply Assembly	9342580	25
Shorting Bar, Ceramic	9292157	25
Shorting Bar and Connector Assembly	9292158	25
Molding, Power Supply	9287159	25

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:50Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-70675(AR)

PARAGRAPH	TITLE: Power Supply Assembly		SHEET 1 OF 1		DRAWING NUMBER: See below NEXT HIGHER ASSEMBLY: --- PARAGRAPH REFERENCE /INSPECTION METHOD
CATEGORY	EXAMINATION OR TEST	NO OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	
	Molding, Power Supply (Dwg. 9287159)				
	Examination for defects	25		3.2	4.4.2.1/4.4.2.6
	Shorting Bar, Ceramic (Dwg. 9292157)				
	Examination for defects	25		3.2	4.4.2.3
	Shorting Bar and Connector Assembly (Dwg. 9292158)				
	Examination for defects	25		3.2	4.4.2.4
	Solderability	25		3.6.1	4.4.2.4
	Power Supply Assembly (Dwg. 9342580)				
	Examination for defects	25		3.2	4.4.2.7
	Pull test	25		3.4	4.5.3/4.5.4
	Solderability	10		3.6.2	4.5.6

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:50Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provision of MIL-A-48078. In addition, inspection lots of Power Supply Assemblies shall contain batteries bearing the same lot interfix number from one manufacturer.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:50Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-70675(AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.1	Power Supply Molding				9287159
					NEXT HIGHER ASSEMBLY 9342580
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	I.D. of middle hole (Sect AA)		0.40%	3.2	Gage/4.4.5
102	I.D. of bottom post (max)		0.40%	3.2	Gage/4.4.5
103	True position of post		0.40%	3.2	Gage/4.4.5
104	Width of bridge		0.40%	3.2	Gage/4.4.5
105	True position of bridge		0.40%	3.2	Gage/4.4.5
106	I.D. of large center hole		0.40%	3.2	Gage/4.4.5
107	True position of largest hole		0.40%	3.2	Gage/4.4.5
108	Height from bottom to top of bridge		0.40%	3.2	Gage/4.4.5
109	Material		0.40%	3.2	Certificate/6.2
110	Distance from center line to edge of shorting bar hole (Section B-B)		0.40%	3.2	Gage/4.4.5
111	Length of bottom post		0.40%	3.2	Gage/4.4.5
112	I.D. of smallest hole		0.40%	3.2	Gage/4.4.5
Minor					
201	Length from bridge to closed end (2 places)		0.65%	3.2	Gage/4.4.5
202	True position of inside width of cell cavity (2 places)		0.65%	3.2	Gage/4.4.5
203	Width of shorting bar hole (Sect. B-B)		0.65%	3.2	Gage/4.4.5
204	Length of shorting bar slot		0.65%	3.2	Gage/4.4.5
205	Width of cell cavity (2 places)		0.65%	3.2	Gage/4.4.5

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:50Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-70675(AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.1	Power Supply Molding				9287159
					NEXT HIGHER ASSEMBLY 9342580
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
206	Depth of shorting bar hole (Sect. B-B)		0.65%	3.2	Gage/4.4.5
207	Distance from center line to edge of shorting bar hole		0.65%	3.2	Gage/4.4.5
208	Poor workmanship		0.65%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:50Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-70675(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9292197
4.4.2.2	Support Foam				NEXT HIGHER ASSEMBLY 9342580
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor 201	Adhesive missing		0.65%	3.2	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:50Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-70675(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.3	Shorting Bar, Ceramic				9292157
					NEXT HIGHER ASSEMBLY 9287158
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Thickness		0.40%	3.2	Gage
102	Solderability	15	2/	3.2	1/
Minor					
201	Total height		0.65%	3.2	Gage
202	Total length		0.65%	3.2	Gage
203	Dielectric glaze missing or incomplete		0.65%	3.2	Visual
204	Solder coating outside area "A" incorrect		0.65%	3.2	Visual
205	Poor workmanship		0.65%	3.8	Visual

NOTES:
1/ Per MIL-S-45743.
2/ Reject for one (1) or more defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:50Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-70675(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Shorting Bar and Connector Assembly	1 OF 1	9292158
			NEXT HIGHER ASSEMBLY 9342580

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Solder workmanship incorrect		0.40%	3.6.1	4.5.5
102	Evidence of cracks or chips		0.40%	3.2	Visual
Minor					
201	Poor workmanship		0.65%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:50Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-70675(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5	Spacer	1 OF 1	9342581
			NEXT HIGHER ASSEMBLY: 9342580

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Thickness		0.40%	3.2	Gage
102	Diameter		0.40%	3.2	Gage
Minor					
201	Poor workmanship		0.65%	3.8	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:50Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-70675(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Battery Insulator	1 OF 1	9342582
			NEXT HIGHER ASSEMBLY 9342580

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Thickness		0.40%	3.2	Gage
102	Diameter		0.40%	3.2	Gage
Minor					
201	Adhesive missing		0.65%	3.2	Visual
202	Poor workmanship		0.65%	3.8	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 — Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:50Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-70675(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.7	Power Supply Assembly				9342580
					NEXT HIGHER ASSEMBLY 9342551/9342552
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Pull test		100%	3.4	4.5.3
Major					
101	Non-activated voltage (each cell)		2/	3.3.1	1/, 4.5.1
102	Weld integrity		2/	3.2	Visual/4.5.4
103	Battery cell(s) not bonded to mold		0.40%	3.2	Visual
104	Shorting bar(s) support foam missing		0.40%	3.2	Visual
105	Shorting bar assemblies not properly seated in cavity		0.40%	3.2	Visual
106	Air gap present between support foam and cavity		0.40%	3.2	Visual
107	Length of lead(s) extending below mold (min)		0.40%	3.2	Gage
108	Resistance of shorting bar		0.40%	3.3.2	4.5.2
109	Solderability, 4 cell leads	15	15-0-1	3.6.2	4.5.6
110	Polyester film tape missing		0.65%	3.2	Visual
111	Spacer missing		100%	3.2	Visual
112	Battery insulator missing		100%	3.2	Visual
Minor					
201	Poor workmanship		0.65%	3.8	Visual

NOTES:
1/ Use 10^7 ohm input impedance voltmeter.
2/ Sample per MIL-STD-105D, Level II. Reject for one (1) or more failures.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:50Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-70675(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.8	Connector, Edge Clip				9292156
					NEXT HIGHER ASSEMBLY 9292158
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Solderability	20	0-1	3.2	MIL-STD-202, Method 208
Minor	None defined				

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-10-23T03:50Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection Tables and below.

4.4.4 Inspection equipment. The inspection equipment required to perform the examination and tests prescribed herein is identified in the tables beginning with paragraph 4.4.2.1. The Contractor shall submit inspection equipment designs for approval in accordance with the terms of the Contract. See section 6 of MIL-A-48078 and section 6.3 herein.

4.4.5 Dimensional control of molded parts. In place of normal sampling and inspections associated with the Classification of Defects, and after a curing time for the parts has been approved (See Note 1). The Contractor may, with the approval of the Government, select a sample of three (3) parts (as molded) from each cavity to be fully inspected dimensionally (all dimensions on drawing) to qualify a new or reworked cavity for use in production. The molded parts shall carry the individual cavity identification. As a control of each cavity during production, the above quantity of parts from each cavity shall be inspected for at least the defects listed in 4.4.2.1 after continuous production of each 5,000 parts or at the end of each week, whichever occurs first. of the three (3) samples, one (1) sample shall be the last part produced. If any defective parts are found during qualification of the cavity, the cavity producing the defective part will not be used in production. If any defective parts are found when inspection is performed for the control of the cavity, the cavity producing the defective part shall be removed from production. Further, that portion of production since the last control check shall be returned to the contractor for inspection for each separate type of defect according to MIL-STD-105, using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. All cavities removed from production because of some fault, may after reworking, be returned to production providing they pass the qualification test above. Tune contractor may request a change of inspection frequency providing he presents objective evidence to the contracting officer to substantiate the request. Contractor design of gages and test equipment required to perform the inspections listed herein shall be forwarded to Commander, AMCCOM, Picatinny Arsenal, New Jersey 07806-5000, ATTN: AMSMC-QAT-I (D) for approval prior to manufacture of equipment. The noted subparagraphs identify those items and minimum inspections subject to the requirements of this paragraph.

NOTE 1: In establishing a curing time, dimensionally check ten (10) parts from each cavity at periodic intervals (e.g. every 30, 60 etc. mins.) until dimensional stability is attained. The curing time will be from the time the part comes out of the mold until dimensional stability is attained. The inspection data used in determining the curing time shall be sent to AMCCOM, Picatinny Arsenal, New Jersey 07806-5000, ATTN: AMSMC-QAT-M (D). When a new cavity is substituted, an old cavity reworked, or the material or cycle time changed, a new curing time shall be established and approved.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:50Z
Check the source to verify that this is the current version before use.

4.5 Methods of inspection.

4.5.1 Non-activated voltage. Each battery cell of the power supply assembly shall be checked for conformance with the requirements of 3.3.1 when measured by a 10 megohm input impedance voltmeter. (Non-destructive test)

4.5.2 Shorting bar resistance. The continuity-resistance of each shorting bar circuit shall be measured, using an approved ohmmeter . Observation shall be made for compliance with requirements of 3.3.2. (Non-destructive test)

4.5.3 Battery lead pull test. A five (5) pound plus two (2) pound force shall be applied to each lead in.a direction parallel to the lead using approved test equipment. Observation shall be made for compliance with requirements of 3.4.

4.5.4 Battery lead weld integrity. Visual examination of the lead welds shall be performed at a minimum of 10x magnification. Observation shall be made for compliance with the requirement of 3.5.

4.5.5 Shorting bar and connector assembly solder workmanship. Soldering and inspection shall conform to MIL-S-45743. Visual examination shall be performed at a minimum of 10x magnification. Observation shall be made for compliance with requirements of 3.6.1. (Non-destructive test)

4.5.6 Solderability. The power supply assembly leads shall be subjected to solderability procedure of MIL-S-45743. Observation shall be made for compliance with requirements of 3.6.2. (Destructive test)

5. PACKAGING

5.1 Preservation and packaging. The Power Supply Assembly shall be preserved and packaged in accordance with MIL-STD-1169, level C.

5.2 Packing. Packing of the assemblies shall be in accordance with MIL-STD-1169 level C.

5.3 Marking. Marking shall be in accordance with MIL-STD-1169. Lotting shall comply with MIL-STD-1168.

5.4 Shipping. When shipments from more than one lot are shipped as a carload, each lot shall be kept separate than the division between lots clearly indicated to prevent mixing of lots in transit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:50Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The component(s) covered by this specification is intended for use in the M718A1/M741A1 Electronic Assemblies.

6.2 Ordering data. See Section 6.1 of MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. See MIL-A-48078. Submit equipment designs as required, to Commander, ARDEC, ATTN: AMSMC-QAT-I (D), Picatinny Arsenal, New Jersey 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract. Unless otherwise specified, data item DI-R-1714 will apply.

6.4 Submission of results of contractor-conducted examinations and tests. Unless otherwise specified by the Contracting officer, the contractor shall forward requested records of examinations of tests to Commander, ARDEC, ATTN: AMSMC-QAT-M (D), Picatinny Arsenal, New Jersey 07806-5000.

6.5 Distribution of ammunition data cards. Distribution of data cards shall include the following: Commander, ARDEC, ATTN: AMSMC-QAT-M (D), Picatinny Arsenal, New Jersey 07806-5000.

6.6 Drawings. Drawings listed in Section 2 of this specification under the heading U.S. Armament Research, Development and Engineering Center (ARDEC), may include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal (ARRADCOM) or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.7 Subject term (key word) listings.

Mines, AT
Power Supply Assembly
Pull Test, Battery Lead Weld

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1345-A390)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:50Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-P-70675 (AR)	Power Supply Assembly, For Mines M718A1/M741A1, System

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(FOLD ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:50Z
Check the source to verify that this is the current version before use.