MIL-R-55241A(EL)
AMENDMENT 2
14 February 1967

SUPERSEDING
AMENDMENT 1
3 May 1965

MILITARY SPECIFICATION

RADIO SET AN/ARC-73( ) (UNITS OF)

(This amendment forms a part of MIL-R-55241A(EL), 11 September 1964)

Paragraph 2.1 — Delete the following under Specifications:

UU-T-111	Tape, Paper, Gummed (Sealing and Securing).
PPP-B-601	Boxes, Wood. Cleated-Plywood.
PPP-B-621	Boxes, Wood. Nailed and Lock-Corner.
PPP-B-640	Boxes, Folding, Fiberboard, Corrugated, Triple Wall.
MIL-A-101	Adhesive, Water Resistant, for Sealing Fiberboard Boxes.
MIL-B-117	Bags, Interior Packaging.
MIL-D-3464	Dessicants, Activated (In Bags) for Static Dehumidification.

Paragraph 2.1 — Add the following under Specifications:

PPP-T-45	Tape, Gummed, Paper, Reinforced and Plain, for Sealing and Securing.
PPP-T-97	Tape; Pressure-Sensitive Adhesive, Filament Reinforced.
MIL-B-131	Barrier Material, Water Vaporproof, Flexible, Heat-Sealable
MIL-I-8835	Indicator, Humidity, Card, Chemically Impregnated.

Paragraph 2.1 — Delete the following under Military Standards

MS-20003	Indicator, Humidity Cord, Three Spot Impregnated Areas (Cobaltous Chloride).

Paragraph 2.1 — Add the following under Military Standards.

MIL-STD-147	Palletized Unit Loads: 40in. x 48 in. 4-Way Partial and 4-Way Pallets.

FSC 5821

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:40Z
Check the source to verify that this is the current version before use.

Amendment 2
MIL-R-55241A(EL)

Paragraph 2.1	Under DRAWINGS replace "Signal Corps" with "Electronics Command"
Paragraph 2.1	Delete the following under drawings.
SC-GL-323019	Drawing and Gage List for Receiver R-1123( )/ ARC-73.
SC-GL-323020	Drawing and Gage List for Receiver R-1123 ( )/ ARC-73.
SC-GL-323021	Drawing and Gage List for Transmitter T-879( )/ ARC-73.
SC-GL-323022	Drawing and Gage List for Transmitter T-879( )/ ARC-73.
SM-D-452262	Power Supply Module A4 (Transmitter).
SM-D-453349	Power Supply Module A3 (Receiver).
Paragraph 2.1	Add the following under Drawings
SC-GL-323117	Drawing and Gage List for Receiver R-1123 ( )/ ARC-73.
SC-GL-323120	Drawing and Gage List for Receiver R-1123( )/ ARC-73.
SC-GL-323118	Drawing and Gage List for Transmitter T-879( )/ ARC-73.
SC-GL-323119	Drawing and Gage List for Transmitter T-879( )/ ARC-73.
SM-GL-323234	Power Supply Module A3 (Receiver).
SM-GL-323235	Power Supply Module A4 (Transmitter).
Paragraph 3.12.1.5	Shock, sub-paragraph (b), replace "30" with "15".
Paragraph 3.13.2	Response Audio . - Change "+1 or -5db" to "+2 or -4db".
Paragraph 3.13.9	Selectivity, Overall . First sentence, replace "4OKC" with "± 4OKC".
Paragraph 3.13.13,	AGC Operation , Replace "3" with "4".
Paragraph 4.4	Preproduction Inspection Table I. . Delete reference to "Altitude" and "Humidity".
Paragraph 4.5.1	Table II, Group A inspection , under Visual and Mechanical, add: "T-879( )/ARC-73 (Assembly) major 1.0% and minor 4.0%".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:40Z
Check the source to verify that this is the current version before use.

Paragraph 4.5.4 Group C Inspection. Table IV. Under subgroup I AN/ARC-73( ) insert the following:

Inspection	Req Para	Insp Para
Altitude	3.12.1.2 3.12.1.3	4.10.1
Humidity	3.12.1.3 3.12.2.3	4.10.2

Paragraph 4.5.4.1.4 Noncompliance . Replace with:

"4.5.4.1.4 Noncompliance. The contractor shall immediately report in writing each group C failure occurrence, including details of the failure and characteristics affected. The contractor shall immediately investigate the cause of failure and further report the results of investigation and details of the proposed corrective action on (i) the process and materials, as applicable, and, (ii) all units of product which were manufactured under the same conditions and which the Government considers subject to the same failure. Reports shall be forwarded to the responsible technical activity designated in the contract through the Quality Assurance Representative. After corrective action has been taken, additional sample units shall be subjected to group C inspection (all inspections, or the inspections which the sample failed, at the option of the Government) and Groups A and B inspection may be reinstituted; however, final acceptance and shipment will be withheld until the group C reinspection results have shown that the corrective action was effective".

Paragraph 4.8.16 Squelch control, third sentence, replace "increase" with "decrease".

Paragraph 4.10.4 Shock, replace, second sentence with "Sensitivity (using a signal modulated 30 per cent, 1000 cps) and power output shall be checked".

Paragraph 4.18.2 Electrical Performance . (Modules) Delete all reference to drawings under (a), (b), (c), (d), (e) and (f) and replace with the following:

(a) SC-GL-323117
(b) SC-GL-323120
(c) SC-GL-323118
(d) SC-GL-323119
(e) SC-GL-323235
(f) SC-GL-323234

Section 5, Preparation for Delivery. - Replace with the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:40Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging . Preservation and packaging shall be Level A or C, as specified (see 6.2(c)).

5.1.1 Level A.

5.1.1.1 Cleaning . Radio Set AN/ARC-73 ( ) shall be cleaned in accordance with process C-1 of MIL-P-116.

5.1.1.2 Drying . Radio Set AN/ARC-73 ( ) shall be dried in accordance with the applicable procedure of MIL-P-116.

5.1.1.3 Unit packaging . Unit packaging shall be in accordance with methods prescribed in MIL-P-116 as specified herein.

5.1.1.3.1 Technical literature. Each technical literature shall be packaged method 1C-1.

5.1.1.3.2 Transmitter Radio, T-879 ( )/ARC-73. Each transmitter shall be packaged method 11b. Cushion the transmitter on all surfaces with cells or pads or both, fabricated of fiberboard conforming to PPP-F-320, type CF, class domestic, designed to protect all projections and to absorb the shock of impact in handling and transit. Place the dessicant, as required by MIL-P-116, together with the cushioned transmitter, within a close-fitting fiberboard box conforming to PPP-B-636, type CF, class domestic, variety SW, grade 125. Secure a humidity indicator card conforming to MIL-I-8835 to the underside of one of the top inner flaps with tape conforming to PPP-T-45, type 111. Blunt all corners of the box and cover any stapled or stitched joints with tape conforming to PPP-T-45, type 111. Place the sealed box within a barrier bag fabricated of material conforming to MIL-B-131, class 1. Heat seal the closure leaving a small opening to exhaust the air. Exhaust the excess air and complete the seal. Place the bagged container within a close-fitting fiberboard box conforming to PPP-B-636, W5c. Cover any stapling on the inside of the exterior box with tape conforming to PPP-T-76. Close the box in accordance with the appendix of the box specification. In addition, seal all seams and joints with tape, not less than two inches wide, conforming to PPP-T-76.

5.1.1.3.3 Receiver Radio, R-1123 ( )/ARC-73. Each receiver shall be packaged method 11b in accordance with the procedure specified in 5.1.1.3.2

5.1.1.3.4 Control Radio, C-4074 ( )/ARC-73 . Each control shall be packaged method 11b in accordance with the procedure specified in 5.1.1.3.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:40Z
Check the source to verify that this is the current version before use.

5.1.1.3.5 Mounting, MT-2699 ( )/ARC-73. Each mounting, including hardware and plug, shall be packaged method 111. Stow the hardware and plug in the cotton bag conforming to PPP-B-20. Close the bag with the drawstrings provided and secure to the mounting with tape conforming to PPP-T-76. Cushion the mounting on all surfaces with cells or pads or both, fabricated of fiberboard conforming to PPP-F-320, W6c. The cushioning shall be designed to support the interior surfaces of the unit container in such a manner as to provide adequate bearing strength for stacking purposes. Place the cushioned mounting within a close-fitting fiberboard box conforming to PPP-B-636, W6c. Close the box in accordance with the appendix of the box specification. In addition, seal all seams and joints with tape, not less than two inches wide, conforming to PPP-T-76.

5.1.1.3.6 Radio Set AN/ARC-73 ( ) . Each radio set shall be unit packaged in accordance with the procedures specified in 5.1.1.3.2 thru 5.1.1.3.5.

5.1.2 Level C . Each Radio Set AN/ARC-73 ( ), or individual units, shall be preserved and packaged in a manner that will afford adequate protection against corrosion, deterioration and damage during shipment from the supply source to the first receiving activity.

5.2 Packing . Packing shall be Level A, B or C as specified (see 6.2(c))

5.2.1 Level A .

5.2.1.1 Transmitter Radio, T-879 ( )/ARC-73. A quantity of transmitters, packaged as specified in 5.1, shall be packed within a close-fitting fiberboard box conforming to PPP-B-636, type CF, class weather-resistanct, special requirements use. Close the box in accordance with the appendix of the box specification. To facilitate palletization, fiberboard boxes shall be uniform in size and contain equal quantities of the packaged items to the greatest extent possible.

5.2.1.2 Receiver Radio, R-1123 ( )/ARC-73. A quantity of receivers, packaged as specified in 5.1, shall be packed in accordance with the procedure specified in 5.2.1.1.

5.2.1.3 Control Radio, C-4074 ( )/ARC-73. A quanitity of controls, packaged as specified in 5.1, shall be packed in accordance with the procedure specified in 5.2.1.1.

5.2.1.4 Mounting MT-2699 ( )/ARC-73. A quantity of mountings, packaged as specified in 5.1, shall be packed in accordance with the procedure specified in 5.2.1.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:40Z
Check the source to verify that this is the current version before use.

5.2.1.5 Radio Set AN/ARC-73 ( ). Each radio set, unit packaged as specified in 5.1, shall be consolidated with a close-fitting box conforming to PPP-B-636, type CF, class weather-resistant, special requirements use. Place the technical literature, packaged as specified in 5.1.1.3.1, on top of the contents, directly under the lid of the box. Close the box in accordance with the appendix of the box specification.

5.2.1.6 Palletized load . A quantity of Radio Set AN/ARC-73 ( ), or individual units, packed as specified in 5.2.1.1 thru 5.2.1.5, shall be placed on a pallet, load type 1, conforming to MIL-STD-147. A fiberboard cap shall be employed over the load having two sides extending down the stacked load at least 12 inches to accommodate marking requirements. The cap shall be fabricated of fiberboard conforming to PPP-F-320, class weather resistant, W5s. The load shall be banded to the pallet by strapping.

5.2.1.7 Less than palletized load . When quantities per destination are less than a pallet load, containers specified in 5.2.1.1 thru 5.2.1.5 shall be reinforced by pressure-sensitive filament tape conforming to PPP-T-97, type IV as specified in the appendix of the box specification. No further packing shall be required.

5.2.2 Level B. A quantity of Radio Set AN/ARC-73 ( ), or individual units, packaged as specified in 5.1, shall be packed as specified in 5.2.1 except that the fiberboard boxes and fiberboard caps shall be class domestic.

5.2.3 Level C. A quantity of Radio Set AN/ARC-73 ( ), or individual units, packaged as specified in 5.1, shall be packed as specified in 5.2.1 except that the pallets, fiberboard boxes and fiberboard caps shall be of the type, size and kind commonly used for the purpose and shall comply with the rules and regulations of the common carrier as applicable to the mode of transportation. Packing shall be accomplished in a manner that will afford adequate protection to the package and its contents during shipment from the supply source to the first receiving activity.

5.3 Marking . In addition to any special marking required by the contract or order, interior packages and exterior shipping containers shall be marked in accordance with MIL-STD-129.

CUSTODIAN
Army-EL

PREPARING ACTIVITY
Army-EL

Project Number 5821-A027

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:40Z
Check the source to verify that this is the current version before use.