MIL-W-83970B(USAF)
25 JAN 88
SUPERSEDING
MIL-W-83970A(USAF)
16 JANUARY 1981

MILITARY SPECIFICATION
WING AND ROLLERON ASSEMBLY, AIM-9

This specification is approved for use within the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the wing, fairing and rolleron assembly, referred to herein as the assembly. The rolleron assembly is referred to as the rolleron. The bearing assembly is part of the rolleron and is referred to as the bearing.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

Federal

QQ-W-423	Wire, Steel, Corrosion-Resisting
QQ-S-763	Steel Bar Wire, Shape and Forging - Corrosion Resisting
QQ-S-766	Steel Plates, Sheets, and Strip, Corrosion Resisting

Military

MIL-B-197	Bearings, Antifriction; Associated Parts and Subassemblies; Preparation and Delivery of

Beneficial comments (recommendation, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: WR-ALC/MMEDTB, Robins AFB, GA 31098-5906 by using the self addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1420
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:55Z
Check the source to verify that this is the current version before use.

MIL-H-6875	Heat Treatment of Steel, Process for
MIL-A-8421	Air Transportability Requirements, General Specification for
MIL-P-9024	Packaging, Materials Handling and Transportability System, and System Segments, General Specification for
MIL-I-45208	Inspection System Requirements
MIL-G-81322	Grease, Aircraft, General Purpose, Wide Temperature Range

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	Marking for Shipment and Storage
MIL-STD-45662	Calibration System Requirements

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

AIR FORCE

69E33005	Wing and Rolleron Assembly
69C33157	Rolleron Assembly, Wing
7031263	Bearing, Rolleron

TECHNICAL PACKING ORDER

TPO 1420-410-0996AB	Wing and Rolleron Assembly

AIR FORCE TECHNICAL ORDER

T.O. 00-25-203	Standard Functional Criteria for Design and Operation of Clean Rooms

2.2 Other Publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the non-government documents which is current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM-D1457 Materials, PTFE Molding and Extrusion
(Applications for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103).

ANIT-FRICTION BEARING MANUFACTURERS ASSOCIATION

AFBMA 10	Metal Balls
ABEC-7	Standards of the Annular Bearing Engineers Committee (ABEC) of the AFBMA.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:55Z
Check the source to verify that this is the current version before use.

(Applications for copies should be addressed to the Anti-Friction Bearing Manufacturers Association, Inc., 2341 Jefferson Davis Highway, Arlington VA 22202).

NON-GOVERNMENT

DRAWINGS

FORD AEROSPACE AND COMMUNICATION CORPORATION (CAGEC 09205)

143520	Rolleron Assembly
143526	Bearing, Rolleron

(Applications for copies should be requested from the contracting activity or as directed by the contracting activity).

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Design and construction. The assembly shall meet the requirements of Drawing 69E33005 and shall contain the following items of major equipment.

a. Wing and fairing assembly

b. Rolleron assembly

c. Hinge

d. Bearings

The wing assembly consists of a fixed aerodynamic surface (the wing) to which is attached, by means of a canted damped hinge, a movable aerodynamic surface (the rolleron). The rolleron is actuated by a gyroscope wheel which is driven by the missile slipstream. The action of the rolleron minimizes missile roll.

The damper assembly provides a damping and stabilizing action on the rolleron and basically is a hydraulically damped hinge.

The cager is a longitudinal slot in the base of the rolleron assembly which seats on the wing plate. Its function is to hold the rolleron in a neutral position until missile launch. During missile launch, inertia forces, resulting from missile acceleration, cause the rolleron to move up the damper shaft until the slot clears the wing plate releasing the rolleron and allowing the rolleron to pivot about the damper axis.

The bearings shall be nonseparable ball bearing assemblies with an outer ring land-riding retainer, having straight through ball pockets (no ledge). Open side ball pockets for snap type assembly shall not be allowed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:55Z
Check the source to verify that this is the current version before use.

3.2 Preproduction sample. Unless otherwise specified in the contract or purchase order, a preproduction sample of 12 assemblies shall be used for preproduction testing. The preproduction sample shall be manufactured using the same procedures that will be used for production. Any production prior to approval of the preproduction sample shall be at the contractor's risk. Upon completion of testing, all sample assemblies shall be delivered with a certified final report to the procuring activity. The rolleron bearings used in the preproduction sample shall be of the same quality as the bearings used in the production lots and shall be procured from the same manufacturer. Should it be deemed desirable to use bearings supplied by an alternate manufacturer, it shall be mandatory to test a separate preproduction sample which contains these alternate bearings.

3.3. Bearing characteristics.

3.3.1 Bearing physical characteristics.

3.3.1.1 Dimensions. The bearing dimensions and tolerances shall be in accordance with ABEC 7 of the Annular Bearings Engineers Committee (ABEC) of the Anti-Friction Bearing Manufacturers Association (AFBMA), except as specified herein and except as shown on Drawing 143526 (-30 Assembly) or Drawing 7031263 (-10 Assembly).

3.3.1.1.1 Pitch circle diameter. Each bearing shall contain eight 0.1406 diameter balls on a 0.435 $\pm$ 0.005 inch diameter pitch circle.

3.3.1.1.2 Radial clearance. The radial clearance between the inner ring outside diameter (OD) and the shield shall be between 0.001 and 0.005 inch.

3.3.1.1.3 Internal radial play. Internal radial play shall be from 0.0008 to 0.0011 inch.

3.4 Design and construction. The bearings shall be fabricated and assembled in accordance with Drawing 143526 (-30 Assembly) or Drawing 7031263 (-10 Assembly) and as specified herein.

3.4.1 Bearing materials, processes and parts.

3.4.1.1 Rings. Inner and outer rings shall be made from stainless steel, QQ-S-763, Class 440C, Condition A, and shall be heat treated to a Rockwell Hardness of 58C minimum in accordance with MIL-H-6875.

3.4.1.2 Balls, bearing. Balls shall be made from vacuum melted corrosion resistant (stainless) steel, QQ-S-763, Class 440C, Condition A, and shall be heat treated to a Rockwell Hardness of 60C minimum in accordance with AFBMA Standards for Balls, (AFBMA 10), Grade 5.

3.4.1.3 Retainers. Retainers shall be made from polyimide (DuPont SP Vespell or equivalent).

3.4.1.4 Shields. Shields shall be made from stainless steel, QQ-S-766, Class 3402, Condition A, or QQ-S-763, Class 301.

3.4.1.5 Retaining rings. Retaining rings shall be made from spring-tempered stainless steel, QQ-W-423, Class 302, Condition B.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:55Z
Check the source to verify that this is the current version before use.

3.4.1.6 Gaskets. Gaskets shall be made from polytetrafluroathylene resin in accordance with ASTM-D1457.

3.4.1.7 Salvaged material. Recycled and recovered raw materials shall be used to the maximum extent possible in lieu of virgin raw material as long as these materials do not jeopardize the intended use and fully comply with all contract requirements.

3.4.1.8 Lubrication.

3.4.1.8.1 Retainers. After the bearings have been thoroughly cleaned and dried, the retainers shall be vacuum-impregnated with the base oil used in the grease specified in MIL-G-81322.

3.4.1.8.2 Bearings. The bearings shall be lubricated with 225 plus or minus 25 milligrams of MIL-G-81322 grease.

3.5 Assembly performance.

3.5.1 Operating speed. The rolleron, when assembled into the wing assembly, shall be capable of rotation at speeds up to 45,000 revolutions per minute (rpm) without shifting of parts or damage to the rolleron.

3.5.2 Life. The rolleron wheel shall be capable of continuous operation for not less than 60 hours at a speed of 45,000 rpm at the environmental temperatures specified in 4.2.2.

3.5.3 High load. The assembly shall be capable of operating for a minimum of five (5) minutes without damage with the rolleron wheel rotating at 40,000 $\pm$ 5,000 rpm while the assembly is being oscillated at 7.5 $\pm$ 1 Hz at a temperature of 200°F $\pm$ 10°F.

3.5.4 Vibration. The assembly shall perform as specified herein while being vibrated with a sinusoidal force over the frequency spectrum from 200 to 2,000 Hz in the direction of each of the three mutually perpendicular axis, while the rolleron wheel is operating at a speed of 42,500 $\pm$ 2,5000 revolutions per minute.

The vibration forces shall be 10 gravity units (gs) per acceleration of frequencies betweem 200 and 1,000 Hz and five (5) gs between 1,000 and 2,000 Hz. There shall be no shifting of parts or damage to the rolleron as a result of this vibration.

3.5.5 Transportability. The assembly shall be fully transportable to permit employment, deployment and logistics support. The assembly in its package configuration shall be capable of transportation by air and surface carriers in accordance with MIL-A-8421 and MIL-P-9024.

3.6 Standards of manufacture.

3.6.1 Assembly conditions. The bearings shall be assembled under clean room conditions conforming to Air Force Technical Manual T.O. 00-25-203, Class I or better.

3.6.2 Workmanship. The bearings shall be manufactured using workmanship in which extreme care shall be exercised in handling of the bearings so that no

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:55Z
Check the source to verify that this is the current version before use.

physical damage occurs due to untrue press equipment, dropping of bearings, improper press fits, improper installation, distortion of bearing rings due to excessive gaging pressures or damage to shields. There shall be no evidence of contamination resulting from dirty work areas, improper opening of bearing packages, poor washing techniques and methods or use of dirty lubricants. In addition, there shall be no evidence of corrosion caused by contact of the bearings with bare fingers or through exposure of bearings to corrosive fumes and moisture.

3.6.3 Overall. Workmanship shall be in accordance with released engineering drawings and specifications. Workmanship includes the use of proper materials, processess and finishes. The assembly, including all components subassemblies shall be constructed, assembled, lubricated, sealed and finished in a manner to assure compliance with all the requirements contained herein and the applicable drawings and specifications.

4. QUALITY ASSURANCE PROVISIONS

4.1. Responsibilitiy for inspection. Unless otherwise specified in the Contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections, set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Unless otherwise specified, the contractor shall establish a quality assurance program complying with MIL-T-45208.

4.1.1 Responsibility for compliance. All items must meet all requirement of Sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Instruments and test equipment. All instruments are test equipment used for inspection and testing shall be in conformity with MIL-STD-45662.

4.1.3 Test procedures. The procedures and methods for performing all tests specified herein shall be prepared by the contractor and approved by the procuring activity prior to submission of the equipment to these tests. The procuring activity reserves the right to require additional tests as deemed necessary to determine compliance to the requirements of the detailed specification.

4.1.4 Lot sampling plan and procedures. Unless specified otherwise, the sampling plans and procedures shall be in accordance with MIL-STD-105, Inspection Level S-4, except that if any one sample fails any acceptance test, the entire lot shall be subjected to that test. All failures shall be rejected and removed from the lot.

4.2 Preproduction tests. A total of 12 assemblies shall be subjected to pre-

Source: https://assist.dla.mil - Downloaded: 2026-10-23T09:55Z
Check the source to verify that this is the current version before use.

production testing. Failure of any assembly to meet the preproduction tests listed shall be cause for rejection of the preproduction sample. The preproduction tests shall consist of those tests specified in 4.2.1 through 4.2.4. In addition, if at any time during production a lot is rejected, the procuring activity may require that the preproduction tests be reconducted on a new sample. In this event, a sample may be selected randomly from the rejected lot, from the subsequent lot, or from both and delivered to the designated activity for testing.

4.2.1 Operation speed. The assembly shall be mounted in a test fixture which rigidly retains the rolleron axis in a horizontal plane. The rolleron shall be driven by compressed air or gas at a speed from 40,000 to 45,000 rpm for 5.0 plus or minus 0.5 minutes. Allow the rolleron wheel to coast to a stop with no braking action. The rolleron shall meet the requirements of 3.5.1.

4.2.2 Life. A quantity of eight rolleron assemblies shall be operated for a minimum of 60 hours with the wheel rotating between 40,000 and 45,000 rpm. The temperature of the air or gas driving the rolleron wheel shall be within plus or minus 10°F of the actual test temperature for each phase of the test. Operating periods shall be at least 15 minutes in duration. During these periods the rolleron assembly shall be subjected to oscillations of an approximate angular sinusoidal motion about the rolleron hinge line. Test conditions shall be as follows:

a. Twenty hours minimum at minus 40 plus or minus 5 degrees F.

b. Twenty hours minimum at plus 200 plus or minus 10 degrees F.

c. Twenty hours minimum at plus 70 plus or minus 5 degrees F.

An oscillation of 0.5 Hz minimum through a peak to peak amplitude of 60 ± 5 degrees will be induced on the assembly durning the above test. The assembly shall meet the requirements of 3.5.2.

4.2.3 High load. The eight rolleron assemblies tested under 4.2.2 shall be operated for a minimum of five minutes with the rolleron wheel rotating at 40,000 plus or minus 5,000 rpm while the test assembly is being oscillated at 7.5 plus or minus 1 Hz at a temperature of plus 200 plus or minus 10°F. The oscillation shall be approximately sinusoidal at an amplitude of 60° ± 5° about the rolleron hinge line.

4.2.4 Vibration. A quantity of four assemblies shall be supported at the wing root in a test fixture that provides nonflexible support and adaptability to direct the vibration excitation along each of the three perpendicular axis. With the rolleron wheel spinning continuously at the speeds specified in 3.5.1 vibrate the assembly with a sinusodal force over the frequency spectrum from 200 to 2,000 Hertz (Hz). The vibration forces shall provide ten gravity units (gs) peak acceleration, at the rolleron hinge line, between 1,000 and 2,000 Hz. A complete cycle shall include sweeping the frequency spectrum at a logarithmic rate, from 200 to 2,000 Hz and returning to 200 Hz within 15 plus or minus 5 minutes. Three complete cycles shall be made in each of the three mutually perpendicular axis. The assembly shall meet the requirements of 3.5.4.

4.3 Quality conformance inspections. The contractor shall verify conformance

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:55Z
Check the source to verify that this is the current version before use.

with the requirements of Section 3 in accordance with the inspections and tests specified in the following subparagraphs. The lot acceptance plan of 4.1.4 shall apply unless otherwise specified.

4.3.1 Physical inspection. Each unit shall be inspected for quality conformance to the following physical characteristics as defined in the applicable drawings:

a. Dimensional verification.

b. Finish.

c. Workmanship.

4.3.2 Rolleron bearing quality.

4.3.2.1 Quality conformance inspections. Quality conformances tests and examinations shall be performed on lot samples (see 4.3.3.1) from all production lots (see 4.3.3) submitted for acceptance under this specification subsequent to the lot(s) from which the preproduction sample was selected. Quality conformance inspection shall consist of performing all of the tests and examinations listed in Table I.

TABLE I. REQUIREMENTS/TEST METHOD CORRELATION

	Requirement Para	Test Method Para
Dimensions	3.3.1.1	4.3.4.1
Pitch circle diameter	3.3.1.1.1	4.3.4.2
Radial clearance	3.3.1.1.2	4.3.4.3
Internal radial play	3.3.1.1.3	4.3.4.4
Design and construction	3.4	4.3.5
Rings	3.4.1.1	4.3.6
Balls, bearing	3.4.1.2	4.3.7
Retainers	3.4.1.3	4.3.8
Shields	3.4.1.4	4.3.8
Retaining rings	3.4.1.5	4.3.8
Gaskets	3.4.1.6	4.3.8
Retainers	3.4.1.8.1	4.3.9.1
Bearings	3.4.1.8.2	4.3.9.2
Assembly conditions	3.6.1	4.3.10.1
Workmanship	3.6.2	4.3.10.2

4.3.3 Lot. Unless otherwise specified in the contract or purchase order (see 6.2) a lot shall consist of not less than 200 bearings which have been manufactured using the same materials, processes or procedures and which are submitted for acceptance at the same time and place.

4.3.3.1 Lot sample. Unless otherwise specified in the contract or purchase order (see 6.2) lot sampling shall be done in accordance with MIL-STD-105, Inspection Level S-4. If any bearing of the lot sample fails any of the quality conformance tests listed in Table I, the entire lot shall be subjected to that test and all bearings that fail the test shall be rejected and removed from the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:55Z
Check the source to verify that this is the current version before use.

4.3.3.2 Calibration of test equipment. Test and measurement equipment shall be calibrated to perform in accordance with MIL-STD-45662.

4.3.4 Test methods.

4.3.4.1 Dimensions. Bearings shall be inspected to verify conformance to 3.3.1.1.

4.3.4.2 Pitch circle diameter. Before lubrication, each bearing shall be measured under a minimum contact load by measuring with an optical comparator (with a surface illumination attachment). The bearing shall meet the requirements of 3.3.1.1.1.

4.3.4.3 Radial clearance. Radial clearance between the inner ring and the shield shall be measured with a standard measuring instrument. The clearance shall meet the requirements of 3.3.1.1.2.

4.3.4.4 Internal radial play. The internal radial play shall be measured as specified in AFBMA Standards, Section 4. The bearings shall meet the requirements of 3.3.1.1.3.

4.3.5 Design and construction. Bearing shall be inspected to verify compliance with 3.4.

4.3.6 Rings. The rings shall be tested in accordance with MIL-H-6875. The rings shall meet the requirements of 3.4.1.1.

4.3.7 Ball, bearing. The balls shall be tested in accordance with AFBMA Standards (AFBMA 10) for Grade 5. The balls shall meet the requirements of 3.4.1.2.

4.3.8 Retainers, shields, retaining rings and gaskets. Certification shall be furnished to ensure that all retainers, shields, retaining rings and gaskets meet the requirements of 3.4.1.3, 3.4.1.4, 3.4.1.5 and 3.4.1.6.

4.3.9 Lubrication.

4.3.9.1 Retainers. Certification shall be furnished to ensure that all retainers meet the requirements of 3.4.1.8.1.

4.3.9.2 Bearings. Certification shall be furnished to ensure that all bearings meet the requirements of 3.4.1.8.2.

4.3.10 Standards of manufacture.

4.3.10.1 Assembly conditions. Certification shall be furnished to verify compliance with 3.6.1.

4.3.10.2 Workmanship. The bearings shall be visually inspected to ensure that all parts are present and finished as specified and meet the requirements of 3.6.2.

4.3.11 Functional tests. The assembly shall be 100 percent tested to the following requirements:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:55Z
Check the source to verify that this is the current version before use.

a. Drawing 69C33157, Note 10 of Drawing 143520, Note 6: Checking of the wheel rundown time after specified operation.

b. Drawing 69E33005, Note 5: Checking is the uncage and recage force of the rolleron assembly.

c. Drawing 69E33005, Note 8: Checking of the uncage and recage force of the rolleron assembly.

4.3.12 Rejection and retest. Equipment which has been rejected during test or inspection may be reworked or have parts replaced to correct defects. Before subjecting to retest, all rework must be accepted and shall not be retested until specific approval is obtained.

5. PACKAGING

5.1 Preservation and packaging. The assembly shall be preserved and packaged in accordance with TPO 1420-410-0996AB.

5.2 Marking. The packaging and packing shall be marked in accordance with MIL-STD-129.

5.3 Protection of bearings. Unless otherwise specified, preservation, packaging and packing and marking shall be in accordance with MIL-B-197, method IA-8, IA-13, IA-18 or IA-19.

6. NOTES

6.1 Intended use. The Wing and Rolleron Assemblies covered by this specification are to be used on the AIM-9B, E, J, N and P series Air-to-Air Missiles.

6.2 Ordering data. Procurement document should specify the following:

a. Title, number and date of this specification.

b. Contract number to be stamped on each wing.

c. First articles to be delivered as specified.

NOTICE: When Government drawings, specifications or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished or in any way supplied the said drawings, specifications or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

6.3 Subject term (Key word) listing.

a. Missile Components

b. Wing Assembly

Source: https://assist.dla.mil -- Downloaded: 202640-23T09:55Z
Check the source to verify that this is the currentversion before use.

c. Rolleron Assembly

d. Specification, Military

Custodian
Air Force - 99

Preparing Activity
Air Force - 84
Agent: Air Force - 99
Project 1420-F284

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:55Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 4966 Alexandria, VA.

POSTAGE WILL BE PAID BY

WR-ALC/MMEDTB
Robins AFB GA 31098-5906

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:55Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:55Z
Check the source to verify that this is the current version before use.