

MS9386

FED. SUP CLASS 5330





SECTION A-A

PART NUMBER	ID IN.		ID (mm)		T IN.		T (mm)		APPROX MASS	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	LB/100	kg/100
MS9386-001	0.025	0.033	0.635	0.838	0.037	0.043	0.940	1.092	.0015	.0007
MS9386-002	0.038	0.046	0.965	1.168	0.047	0.053	1.194	1.346	.003	.0014
MS9386-003	0.052	0.060	1.321	1.524	0.057	0.063	1.448	1.600	005	.0018
MS9386-004	0.065	0.075	1.65	1.90	0.067	0.073	1.702	1.854	.008	.0036
MS9386-005	0.096	0.106	2.44	2.69	0.067	0.073	1.702	1.854	.010	.0045
MS9386-006	0.109	0.119	2.77	3.02	0.067	0.073	1.702	1.854	.011	.0054
MS9386-007	0.140	0.150	3.56	3.81	0.067	0.073	1.702	1.854	.013	.0059
MS9386-008	0.171	0.181	4.34	4.60	0.067	0.073	1.702	1.854	.015	.0068
MS9386-009	0.203	0.213	5.16	5.41	0.067	0.073	1.702	1.854	.017	.0077
MS9386-010	0.234	0.244	5.94	6.20	0.067	0.073	1.702	1.854	.018	.0082
MS9386-011	0.296	0.306	7.52	7.77	0.067	0.073	1.702	1.854	.022	.010
MS9386-012	0.359	0.369	9.12	9.37	0.067	0.073	1.702	1.854	025	.011
MS9386-013	0.421	0.431	10.69	10.95	0.067	0.073	1.702	1.854	029	.013
MS9386-014	0.484	0.494	12.29	12.55	0.067	0.073	1.702	1.854	033	.015
MS9386-015	0.546	0.556	13.87	14.12	0.067	0.073	1.702	1.854	037	.017
MS9386-016	0.609	0.619	15.47	15.72	0.067	0.073	1.702	1.854	.040	.018
MS9386-017	0.671	0.681	17.04	17.30	0.067	0.073	1.702	1.854	.044	.020
MS9386-018	0.734	0.744	18.64	18.90	0.067	0.073	1.702	1.854	.048	022
MS9386-019	0.795	0.807	20.19	20.50	0.067	0.073	1.702	1.854	.051	.023
MS9386-020	0.858	0.870	21.79	22.10	0.067	0.073	1.702	1.854	.055	.025
MS9386-021	0.920	0.932	23.37	23.67	0.067	0.073	1.702	1.854	.059	.027
MS9386-022	0.983	0.995	24.97	25.27	0.067	0.073	1.702	1.854	.062	.028
MS9386-023	1.045	1.057	26.54	26.85	0.067	0.073	1.702	1.854	.066	.030
MS9386-024	1.108	1.120	28.14	28.45	0.067	0.073	1.702	1.854	070	.032
MS9386-025	1.170	1.182	29.72	30.02	0.067	0.073	1.702	1.854	074	034
MS9386-026	1.233	1.245	31.32	31.62	0.067	0.073	1.702	1.854	077	035
MS9386-027	1.295	1.307	32.89	33.20	0.067	0.073	1.702	1.854	.083	.038
MS9386-028	1.358	1.370	34.49	34.80	0.067	0.073	1.702	1.854	.085	.039
MS9386-029	1.479	1.499	37.57	38.07	0.067	0.073	1.702	1.854	.092	042
MS9386-030	1.604	1.624	40.74	41.25	0.067	0.073	1.702	1.854	.100	045
MS9386-031	1.729	1.749	43.92	44.42	0.067	0.073	1.702	1.854	107	049
MS9386-032	1.854	1.874	47.09	47.60	0.067	0.073	1.702	1.854	115	.052
MS9386-033	1.979	1.999	50.27	50.77	0.067	0.073	1.702	1.854	122	055
MS9386-034	2.104	2.124	53.44	53.95	0.067	0.073	1.702	1.854	.129	.059
MS9386-035	2.229	2.249	56.62	57.12	0.067	0.073	1.702	1.854	137	.062
MS9386-036	2.354	2.374	59.79	60.30	0.067	0.073	1.702	1.854	.144	065
MS9386-037	2.479	2.499	62.97	63.47	0.067	0.073	1.702	1.854	.151	.068
MS9386-038	2.604	2.624	66.14	66.65	0.067	0.073	1.702	1.854	159	072
MS9386-039	2.724	2.754	69.19	69.95	0.067	0.073	1.702	1.854	166	.076
MS9386-040	2.849	2.879	72.36	73.13	0.067	0.073	1.702	1.854	.174	.079
MS9386-041	2.974	3.004	75.54	76.30	0.067	0.073	1.702	1.854	.181	.082
MS9386-042	3.224	3.254	81.89	82.65	0.067	0.073	1.702	1.854	196	.089
MS9386-043	3.474	3.504	88.24	89.00	0.067	0.073	1.702	1.854	.210	095
MS9386-044	3.724	3.754	94.59	95.35	0.067	0.073	1.702	1.854	.225	.102
MS9386-045	3.974	4.004	100.94	101.70	0.067	0.073	1.702	1.854	.240	.109
MS9386-046	4.224	4.254	107.29	108.05	0.067	0.073	1.702	1.854	.255	.116
MS9386-047	4.474	4.504	113.64	114.40	0.067	0.073	1.702	1.854	.270	.122
MS9386-048	4.724	4.754	119.99	120.75	0.067	0.073	1.702	1.854	.285	.129
MS9386-049	4.966	5.012	126.14	127.30	0.067	0.073	1.702	1.854	.300	.136
MS9386-050	5.216	5.262	132.49	133.65	0.067	0.073	1.702	1.854	.314	.142
MS9386-102	0.044	0.054	1.12	1.37	0.100	0.106	2.540	2.692	.020	.009
MS9386-103	0.076	0.086	1.93	2.18	0.100	0.106	2.540	2.692	.024	.011
MS9386-104	0.107	0.117	2.72	2.97	0.100	0.106	2.540	2.692	.027	.012
MS9386-105	0.138	0.148	3.51	3.76	0.100	0.106	2.540	2.692	.031	014

(B) ENTIRE STANDARD REVISED & REDRAWN.

APPROVED 20 Dec 66 REVISED (A) 1 May 69 (B) 17 Jun 75

This military standard is approved for use by all departments and agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

User activities
Army - SM, MC
Navy
Air Force
DSA

Review activities
Army - OS
Navy
Air Force
DSA - IS

P.A. Air Force - 11
Other Cust
Army - AV
Navy - AS

TITLE: PACKING, PREFORMED, AMS 7267, O-RING

MILITARY STANDARD
MS 9386

PROCUREMENT SPECIFICATION: NONE

SUPERSEDES:

SHEET 1 OF 7

DD FORM 672-1

Proj. No. 5330-0464

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:16Z
Check the source to verify that this is the current version before use.

MS9386

FED. SUP CLASS
5330

PART NUMBER	ID IN.		ID (mm)		T IN.		T (mm)		APPROX MASS	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	LB/100	kg/100
MS9386-106	0.169	0.179	4.29	4.55	0.100	0.106	2.540	2.692	.036	016
MS9386-107	0.201	0.211	5.11	5.36	0.100	0.106	2.540	2.692	040	.018
MS9386-108	0.232	0.242	5.89	6.15	0.100	0.106	2.540	2.692	044	020
MS9386-109	0.294	0.304	7.47	7.72	0.100	0.106	2.540	2.692	051	023
MS9386-110	0.357	0.367	9.07	9.32	0.100	0.106	2.540	2.692	060	027
MS9386-111	0.419	0.429	10.64	10.90	0.100	0.106	2.540	2.692	.068	031
MS9386-112	0.482	0.492	12.24	12.50	0.100	0.106	2.540	2.692	.075	034
MS9386-113	0.544	0.554	13.82	14.07	0.100	0.106	2.540	2.692	084	.038
MS9386-114	0.607	0.617	15.42	15.67	0.100	0.106	2.540	2.692	.092	042
MS9386-115	0.669	0.679	16.99	17.25	0.100	0.106	2.540	2.692	.099	.045
MS9386-116	0.732	0.742	18.59	18.85	0.100	0.106	2.540	2.692	108	.049
MS9386-117	0.793	0.805	20.14	20.45	0.100	0.106	2.540	2.692	.116	.053
MS9386-118	0.856	0.868	21.74	22.05	0.100	0.106	2.540	2.692	.124	056
MS9386-119	0.918	0.930	23.32	23.62	0.100	0.106	2.540	2.692	.132	.060
MS9386-120	0.981	0.993	24.92	25.22	0.100	0.106	2.540	2.692	.140	.064
MS9386-121	1.043	1.055	26.49	26.80	0.100	0.106	2.540	2.692	148	.067
MS9386-122	1.106	1.118	28.09	28.40	0.100	0.106	2.540	2.692	156	.071
MS9386-123	1.168	1.180	29.67	29.97	0.100	0.106	2.540	2.692	.164	.074
MS9386-124	1.231	1.243	31.27	31.57	0.100	0.106	2.540	2.692	.172	.078
MS9386-125	1.293	1.305	32.84	33.15	0.100	0.106	2.540	2.692	.180	.082
MS9386-126	1.356	1.368	34.44	34.75	0.100	0.106	2.540	2.692	.188	085
MS9386-127	1.418	1.430	36.02	36.32	0.100	0.106	2.540	2.692	.196	.089
MS9386-128	1.481	1.493	37.62	37.92	0.100	0.106	2.540	2.692	204	093
MS9386-129	1.539	1.559	39.09	39.60	0.100	0.106	2.540	2.692	.212	.096
MS9386-130	1.602	1.622	40.69	41.20	0.100	0.106	2.540	2.692	220	.100
MS9386-131	1.664	1.684	42.27	42.77	0.100	0.106	2.540	2.692	.228	.103
MS9386-132	1.727	1.747	43.87	44.37	0.100	0.106	2.540	2.692	.236	.108
MS9386-133	1.789	1.809	45.44	45.95	0.100	0.106	2.540	2.692	.244	111
MS9386-134	1.852	1.872	47.04	47.55	0.100	0.106	2.540	2.692	.252	.114
MS9386-135	1.914	1.935	48.64	49.15	0.100	0.106	2.540	2.692	260	.118
MS9386-136	1.977	1.997	50.22	50.72	0.100	0.106	2.540	2.692	.268	.122
MS9386-137	2.040	2.060	51.82	52.32	0.100	0.106	2.540	2.692	.276	.125
MS9386-138	2.102	2.122	53.39	53.90	0.100	0.106	2.540	2.692	.284	129
MS9386-139	2.165	2.185	54.99	55.50	0.100	0.106	2.540	2.692	.292	.132
MS9386-140	2.227	2.247	56.57	57.07	0.100	0.106	2.540	2.692	.300	.136
MS9386-141	2.290	2.310	58.17	58.67	0.100	0.106	2.540	2.692	308	140
MS9386-142	2.352	2.372	59.74	60.25	0.100	0.106	2.540	2.692	.316	.143
MS9386-143	2.415	2.435	61.34	61.85	0.100	0.106	2.540	2.692	324	.147
MS9386-144	2.477	2.497	62.92	63.42	0.100	0.106	2.540	2.692	.332	151
MS9386-145	2.540	2.560	64.52	65.02	0.100	0.106	2.540	2.692	.340	.154
MS9386-146	2.602	2.622	66.09	66.60	0.100	0.106	2.540	2.692	.348	.158
MS9386-147	2.660	2.690	67.56	68.33	0.100	0.106	2.540	2.692	.356	.161
MS9386-148	2.722	2.752	69.14	69.90	0.100	0.106	2.540	2.692	.364	.165
MS9386-149	2.785	2.815	70.74	71.50	0.100	0.106	2.540	2.692	.372	.169
MS9386-150	2.847	2.877	72.31	73.08	0.100	0.106	2.540	2.692	.381	.173
MS9386-151	2.972	3.002	75.49	76.25	0.100	0.106	2.540	2.692	.396	.180
MS9386-152	3.222	3.252	81.84	82.60	0.100	0.106	2.540	2.692	.428	.194
MS9386-153	3.472	3.502	88.19	88.95	0.100	0.106	2.540	2.692	461	.209
MS9386-154	3.722	3.752	94.54	95.30	0.100	0.106	2.540	2.692	.492	.223
MS9386-155	3.972	4.002	100.89	101.65	0.100	0.106	2.540	2.692	.525	.238
MS9386-156	4.222	4.252	107.24	108.00	0.100	0.106	2.540	2.692	.556	252
MS9386-157	4.472	4.502	113.59	114.35	0.100	0.106	2.540	2.692	.590	.268
MS9386-158	4.722	4.752	119.94	120.70	0.100	0.106	2.540	2.692	621	.282
MS9386-159	4.972	5.002	126.29	127.05	0.100	0.106	2.540	2.692	.654	297
MS9386-160	5.214	5.260	132.44	133.60	0.100	0.106	2.540	2.692	.685	311

User activities: Army – SH, MC; Navy – SH; Air Force; DSA

Review activities: Army; Navy – OS; Air Force; DSA – IS

This military standard is approved for use by all departments and agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

APPROVED 20 Dec 66 REVISED (A) 1 May 69 (B) FOR CHANGES SEE SHEETS 1, 2, 3, 4, 5, 6 AND 7

P.A. Air Force – 11
Other Cust
Army – AV
Navy – AS

TITLE
PACKING, PREFORMED, AMS 7267, O-RING

MILITARY STANDARD
MS 9386

PROCUREMENT SPECIFICATION
NONE

SUPERSEDES

SHEET 2 OF

DD FORM 672-1

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:16Z
Check the source to verify that this is the current version before use.

MS9386

FED SUP CLASS
5330

PART NUMBER	ID IN.		ID (mm)		T IN.		T (mm)		APPROX MASS	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	LB/100	kg/100
MS9386-161	5.464	5.510	138.79	139.95	0.100	0.106	2.540	2.692	.718	326
MS9386-162	5.714	5.760	145.14	146.30	0.100	0.106	2.540	2.692	.749	.340
MS9386-163	5.964	6.010	151.49	152.65	0.100	0.106	2.540	2.692	782	.355
MS9386-164	6.214	6.260	157.84	159.00	0.100	0.106	2.540	2.692	812	.368
MS9386-165	6.464	6.510	164.19	165.35	0.100	0.106	2.540	2.692	.845	383
MS9386-166	6.714	6.760	170.54	171.70	0.100	0.106	2.540	2.692	876	397
MS9386-167	6.964	7.010	176.89	178.05	0.100	0.106	2.540	2.692	.910	.413
MS9386-168	7.207	7.267	183.06	184.58	0.100	0.106	2.540	2.692	941	.427
MS9386-169	7.457	7.517	189.41	190.93	0.100	0.106	2.540	2.692	974	.442
MS9386-170	7.707	7.767	195.76	197.28	0.100	0.106	2.540	2.692	1 015	.460
MS9386-171	7.957	8.017	202.11	203.63	0.100	0.106	2.540	2.692	1 035	.470
MS9386-172	8.207	8.267	208.46	209.98	0.100	0.106	2.540	2.692	1.070	.485
MS9386-173	8.457	8.517	214.81	216.33	0.100	0.106	2.540	2.692	1.101	.499
MS9386-174	8.707	8.767	221.16	222.68	0.100	0.106	2.540	2.692	1.132	.514
MS9386-175	8.957	9.017	227.51	229.03	0.100	0.106	2.540	2.692	1.163	.528
MS9386-176	9.207	9.267	233.86	235.38	0.100	0.106	2.540	2.692	1.199	544
MS9386-177	9.457	9.517	240.21	241.73	0.100	0.106	2.540	2.692	1.230	.558
MS9386-178	9.707	9.767	246.56	248.08	0.100	0.106	2.540	2.692	1.260	.572
MS9386-201	0.166	0.176	4.22	4.47	0.135	0.143	3.429	3.632	072	.033
MS9386-202	0.229	0.239	5.82	6.07	0.135	0.143	3.429	3.632	.087	.039
MS9386-203	0.291	0.301	7.39	7.65	0.135	0.143	3.429	3.632	.101	.046
MS9386-204	0.354	0.364	8.99	9.25	0.135	0.143	3.429	3.632	.116	053
MS9386-205	0.416	0.426	10.57	10.82	0.135	0.143	3.429	3.632	.131	.059
MS9386-206	0.479	0.489	12.17	12.42	0.135	0.143	3.429	3.632	.146	.066
MS9386-207	0.541	0.551	13.74	14.00	0.135	0.143	3.429	3.632	.160	073
MS9386-208	0.604	0.614	15.34	15.60	0.135	0.143	3.429	3.632	.175	.079
MS9386-209	0.666	0.676	16.92	17.17	0.135	0.143	3.429	3.632	189	.086
MS9386-210	0.728	0.740	18.49	18.80	0.135	0.143	3.429	3.632	.204	.093
MS9386-211	0.790	0.802	20.07	20.37	0.135	0.143	3.429	3.632	.219	.099
MS9386-212	0.853	0.865	21.67	21.97	0.135	0.143	3.429	3.632	.233	.106
MS9386-213	0.915	0.927	23.24	23.55	0.135	0.143	3.429	3.632	.248	.112
MS9386-214	0.978	0.990	24.84	25.15	0.135	0.143	3.429	3.632	.262	.119
MS9386-215	1.040	1.052	26.42	26.72	0.135	0.143	3.429	3.632	.277	126
MS9386-216	1.103	1.115	28.02	28.32	0.135	0.143	3.429	3.632	.292	.132
MS9386-217	1.165	1.177	29.59	29.90	0.135	0.143	3.429	3.632	.306	.139
MS9386-218	1.228	1.240	31.19	31.50	0.135	0.143	3.429	3.632	.322	.146
MS9386-219	1.290	1.302	32.77	33.07	0.135	0.143	3.429	3.632	335	.152
MS9386-220	1.353	1.365	34.37	34.67	0.135	0.143	3.429	3.632	350	.159
MS9386-221	1.415	1.427	35.94	36.25	0.135	0.143	3.429	3.632	364	.165
MS9386-222	1.478	1.490	37.54	37.85	0.135	0.143	3.429	3.632	.379	.172
MS9386-223	1.599	1.619	40.61	41.12	0.135	0.143	3.429	3.632	.408	.185
MS9386-224	1.724	1.744	43.79	44.30	0.135	0.143	3.429	3.632	.437	.198
MS9386-225	1.849	1.869	46.96	47.47	0.135	0.143	3.429	3.632	.466	.211
MS9386-226	1.974	1.994	50.14	50.65	0.135	0.143	3.429	3.632	.496	.225
MS9386-227	2.099	2.119	53.31	53.82	0.135	0.143	3.429	3.632	.526	.239
MS9386-228	2.224	2.244	56.49	57.00	0.135	0.143	3.429	3.632	.555	.252
MS9386-229	2.349	2.369	59.66	60.17	0.135	0.143	3.429	3.632	.585	.265
MS9386-230	2.474	2.494	62.84	63.35	0.135	0.143	3.429	3.632	.612	.278
MS9386-231	2.599	2.619	66.01	66.52	0.135	0.143	3.429	3.632	.642	.291
MS9386-232	2.719	2.749	69.06	69.82	0.135	0.143	3.429	3.632	.671	.304
MS9386-233	2.844	2.874	72.24	73.00	0.135	0.143	3.429	3.632	.700	.318
MS9386-234	2.969	2.999	75.41	76.17	0.135	0.143	3.429	3.632	.730	.331
MS9386-235	3.094	3.124	78.59	79.35	0.135	0.143	3.429	3.632	.758	.344

APPROVED 20 Dec 66 REVISED (A) 1 May69 (B) FOR CHANGES SEE SHEETS 1, 2, 3, 4, 5, 6 AND 7

User: Army – SH, MC; Navy – SH; Air Force; DSA

Preparing activities: Army – MI; Navy – OS; Air Force; DSA – IS

This military standard is approved for use by all departments and agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A. Air Force – 11

Other Cust
Army – AV
Navy – AS

TITLE: PACKING, PREFORMED, AMS 7267, O-RING

MILITARY STANDARD
MS 9386

PROCUREMENT SPECIFICATION
NONE

SUPERSEDES:

SHEET 3 OF

DD FORM 672-1 (Edited coordination)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:16Z
Check the source to verify that this is the current version before use.

MS9386

FED. SUP CLASS 5330

PART NUMBER	ID IN.		ID (mm)		T IN.		T (mm)		APPROX MASS	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	LB/100	kg/100
MS9386-236	3.219	3.249	81.76	82.52	0.135	0.143	3.429	3.632	.788	.357
MS9386-237	3.344	3.374	84.94	85.70	0.135	0.143	3.429	3.632	.816	.370
MS9386-238	3.469	3.499	88.11	88.87	0.135	0.143	3.429	3.632	.845	.383
MS9386-239	3.599	3.624	91.29	92.05	0.135	0.143	3.429	3.632	.876	.397
MS9386-240	3.719	3.749	94.46	95.22	0.135	0.143	3.429	3.632	.905	.410
MS9386-241	3.844	3.874	97.64	98.40	0.135	0.143	3.429	3.632	.935	.424
MS9386-242	3.969	3.999	100.81	101.57	0.135	0.143	3.429	3.632	.964	.437
MS9386-243	4.094	4.124	103.99	104.75	0.135	0.143	3.429	3.632	.994	.451
MS9386-244	4.219	4.249	107.16	107.92	0.135	0.143	3.429	3.632	1.021	.463
MS9386-245	4.344	4.374	110.34	111.10	0.135	0.143	3.429	3.632	1.050	.476
MS9386-246	4.469	4.499	113.51	114.27	0.135	0.143	3.429	3.632	1.080	.490
MS9386-247	4.594	4.624	116.69	117.45	0.135	0.143	3.429	3.632	1.110	.504
MS9386-248	4.719	4.749	119.86	120.62	0.135	0.143	3.429	3.632	1.138	.516
MS9386-249	4.844	4.874	123.04	123.80	0.135	0.143	3.429	3.632	1.170	.531
MS9386-250	4.969	4.999	126.21	126.97	0.135	0.143	3.429	3.632	1.200	.544
MS9386-251	5.086	5.132	129.18	130.35	0.135	0.143	3.429	3.632	1.228	.558
MS9386-252	5.211	5.257	132.36	133.53	0.135	0.143	3.429	3.632	1.257	.570
MS9386-253	5.336	5.382	135.53	136.70	0.135	0.143	3.429	3.632	1.286	.583
MS9386-254	5.461	5.507	138.71	139.88	0.135	0.143	3.429	3.632	1.315	.596
MS9386-255	5.586	5.632	141.88	143.05	0.135	0.143	3.429	3.632	1.342	.609
MS9386-256	5.711	5.757	145.06	146.23	0.135	0.143	3.429	3.632	1.372	.622
MS9386-257	5.836	5.882	148.23	149.40	0.135	0.143	3.429	3.632	1.400	.635
MS9386-258	5.961	6.007	151.41	152.58	0.135	0.143	3.429	3.632	1.430	.649
MS9386-259	6.211	6.257	157.76	158.93	0.135	0.143	3.429	3.632	1.488	.675
MS9386-260	6.461	6.507	164.11	165.28	0.135	0.143	3.429	3.632	1.547	.702
MS9386-261	6.711	6.757	170.46	171.63	0.135	0.143	3.429	3.632	1.605	.728
MS9386-262	6.961	7.007	176.81	177.98	0.135	0.143	3.429	3.632	1.662	.754
MS9386-263	7.206	7.264	182.98	184.51	0.135	0.143	3.429	3.632	1.720	.780
MS9386-264	7.456	7.514	189.33	190.86	0.135	0.143	3.429	3.632	1.780	.807
MS9386-265	7.704	7.764	195.68	197.21	0.135	0.143	3.429	3.632	1.839	.834
MS9386-266	7.954	8.014	202.03	203.56	0.135	0.143	3.429	3.632	1.900	.862
MS9386-267	8.204	8.264	208.38	209.91	0.135	0.143	3.429	3.632	1.957	.888
MS9386-268	8.454	8.514	214.73	216.26	0.135	0.143	3.429	3.632	2.015	.914
MS9386-269	8.704	8.764	221.08	222.61	0.135	0.143	3.429	3.632	2.075	.941
MS9386-270	8.954	9.014	227.43	228.96	0.135	0.143	3.429	3.632	3.121	.962
MS9386-271	9.204	9.264	233.78	235.31	0.135	0.143	3.429	3.632	2.194	.995
MS9386-272	9.454	9.514	240.13	241.66	0.135	0.143	3.429	3.632	2.245	1.018
MS9386-273	9.704	9.764	246.48	248.01	0.135	0.143	3.429	3.632	2.306	1.046
MS9386-274	9.954	10.014	252.83	254.36	0.135	0.143	3.429	3.632	2.365	1.073
MS9386-275	10.454	10.514	265.53	267.06	0.135	0.143	3.429	3.632	2.473	1.122
MS9386-276	10.954	11.014	278.23	279.76	0.135	0.143	3.429	3.632	2.600	1.179
MS9386-277	11.454	11.514	290.93	292.46	0.135	0.143	3.429	3.632	2.715	1.232
MS9386-278	11.954	12.014	303.63	305.16	0.135	0.143	3.429	3.632	2.832	1.285
MS9386-279	12.954	13.014	329.03	330.56	0.135	0.143	3.429	3.632	3.065	1.390
MS9386-280	13.954	14.014	354.43	355.96	0.135	0.143	3.429	3.632	3.300	1.497
MS9386-281	14.954	15.014	379.83	381.36	0.135	0.143	3.429	3.632	3.535	1.604
MS9386-282	15.910	16.000	404.11	406.40	0.135	0.143	3.429	3.632	3.759	1.705
MS9386-283	16.910	17.000	429.51	431.80	0.135	0.143	3.429	3.632	3.993	1.811
MS9386-284	17.910	18.000	454.91	457.20	0.135	0.143	3.429	3.632	4.227	1.917
MS9386-309	0.407	0.417	10.34	10.59	0.205	0.215	5.21	5.46	.332	.151
MS9386-310	0.470	0.480	11.94	12.19	0.205	0.215	5.21	5.46	.365	.166
MS9386-311	0.532	0.542	13.51	13.77	0.205	0.215	5.21	5.46	.399	.181
MS9386-312	0.595	0.605	15.11	15.37	0.205	0.215	5.21	5.46	.432	.196
MS9386-313	0.657	0.667	16.69	16.94	0.205	0.215	5.21	5.46	.465	.211

APPROVED 20 Dec 66 REVISED (A) 1 May 69 (B) FOR CHANGE SHEETS 1, 2, 3, 4, 5, 6 AND 7

User: Army, Navy - SH, MC, Air Force, DSA

Review activities: Army, Navy - OS, Air Force, DSA - ES

This military standard is approved for use by all departments and agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A. Air Force - 11

Other Cust: Army - AV, Navy - AS

TITLE: PACKING, PREFORMED, AMS 7267, O-RING

MILITARY STANDARD

MS 9386

PROCUREMENT SPECIFICATION: NONE

SUPERSEDES:

SHEET 4 OF

DD FORM 672-1

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:16Z
Check the source to verify that this is the current version before use.

MS9386

FED. SUP CLASS

PART NUMBER	ID IN.		ID (mm)		T IN.		T (mm)		APPROX MASS	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	LB/100	kg/100
MS9386-314	0.719	0.731	18.26	18.57	0.205	0.215	5.21	5.46	.498	.226
MS9386-315	0.781	0.793	19.84	20.14	0.205	0.215	5.21	5.46	532	.241
MS9386-316	0.844	0.856	21.44	21.74	0.205	0.215	5.21	5.46	.565	.256
MS9386-317	0.906	0.918	23.01	23.32	0.205	0.215	5.21	5.46	.598	.271
MS9386-318	0.969	0.981	24.61	24.92	0.205	0.215	5.21	5.46	.632	.287
MS9386-319	1.031	1.043	26.19	26.49	0.205	0.215	5.21	5.46	.665	.302
MS9386-320	1.094	1.106	27.79	28.09	0.205	0.215	5.21	5.46	.698	.317
MS9386-321	1.156	1.168	29.36	29.67	0.205	0.215	5.21	5.46	.732	.332
MS9386-322	1.219	1.231	30.96	31.27	0.205	0.215	5.21	5.46	.765	347
MS9386-323	1.281	1.293	32.54	32.84	0.205	0.215	5.21	5.46	.798	.362
MS9386-324	1.344	1.356	34.14	34.44	0.205	0.215	5.21	5.46	.832	.377
MS9386-325	1.465	1.485	37.21	37.72	0.205	0.215	5.21	5.46	.897	.407
MS9386-326	1.590	1.610	40.39	40.89	0.205	0.215	5.21	5.46	.965	.438
MS9386-327	1.715	1.735	43.56	44.07	0.205	0.215	5.21	5.46	1.031	.468
MS9386-328	1.840	1.860	46.74	47.24	0.205	0.215	5.21	5.46	1.100	.499
MS9386-329	1.965	1.985	49.91	50.42	0.205	0.215	5.21	5.46	1.163	528
MS9386-330	2.090	2.110	53.09	53.59	0.205	0.215	5.21	5.46	1.231	558
MS9386-331	2.215	2.235	56.26	56.77	0.205	0.215	5.21	5.46	1.300	.590
MS9386-332	2.340	2.360	59.44	59.94	0.205	0.215	5.21	5.46	1.368	.620
MS9386-333	2.465	2.485	62.61	63.12	0.205	0.215	5.21	5.46	1 433	.650
MS9386-334	2.590	2.610	65.79	66.29	0.205	0.215	5.21	5.46	1.498	.680
MS9386-335	2.710	2.740	68.83	69.60	0.205	0.215	5.21	5.46	1.565	.710
MS9386-336	2.835	2.865	72.01	72.77	0.205	0.215	5.21	5.46	1.632	.740
MS9386-337	2.960	2.990	75.18	75.95	0.205	0.215	5.21	5.46	1.700	.771
MS9386-338	3.085	3.115	78.36	79.12	0.205	0.215	5.21	5.46	1.765	800
MS9386-339	3.210	3.240	81.53	82.30	0.205	0.215	5.21	5.46	1.830	.830
MS9386-340	3.335	3.365	84.71	85.47	0.205	0.215	5.21	5.46	1.900	.862
MS9386-341	3.460	3.490	87.88	88.65	0.205	0.215	5.21	5.46	1.965	.891
MS9386-342	3.585	3.615	91.06	91.82	0.205	0.215	5.21	5.46	2.030	921
MS9386-343	3.710	3.740	94.23	95.00	0.205	0.215	5.21	5.46	2.100	953
MS9386-344	3.835	3.865	97.41	98.17	0.205	0.215	5.21	5.46	2.166	982
MS9386-345	3.960	3.990	100.58	101.35	0.205	0.215	5.21	5.46	2.233	1.013
MS9386-346	4.085	4.115	103.76	104.52	0.205	0.215	5.21	5.46	2.300	1.043
MS9386-347	4.210	4.240	106.93	107.70	0.205	0.215	5.21	5.46	2.366	1.074
MS9386-348	4.335	4.365	110.11	110.87	0.205	0.215	5.21	5.46	2.432	1.103
MS9386-349	4.460	4.490	113.28	114.05	0.205	0.215	5.21	5.46	2.495	1.132
MS9386-350	4.585	4.615	116.46	117.22	0.205	0.215	5.21	5.46	2.565	1.164
MS9386-351	4.710	4.740	119.63	120.40	0.205	0.215	5.21	5.46	2.631	1.193
MS9386-352	4.835	4.865	122.81	123.57	0.205	0.215	5.21	5.46	2.698	1.224
MS9386-353	4.960	4.990	125.98	126.75	0.205	0.215	5.21	5.46	2.765	1.254
MS9386-354	5.077	5.123	128.96	130.12	0.205	0.215	5.21	5.46	2.831	1.284
MS9386-355	5.202	5.248	132.13	133.30	0.205	0.215	5.21	5.46	2.898	1.314
MS9386-356	5.327	5.373	135.31	136.47	0.205	0.215	5.21	5.46	2.964	1.344
MS9386-357	5.452	5.498	138.48	139.65	0.205	0.215	5.21	5.46	3.031	1.375
MS9386-358	5.577	5.623	141.66	142.82	0.205	0.215	5.21	5.46	3.098	1.405
MS9386-359	5.702	5.748	144.83	146.00	0.205	0.215	5.21	5.46	3.164	1.435
MS9386-360	5.827	5.873	148.01	149.17	0.205	0.215	5.21	5.46	3.231	1.466
MS9386-361	5.952	5.998	151.18	152.35	0.205	0.215	5.21	5.46	3.298	1.496
MS9386-362	6.202	6.248	157.53	158.70	0.205	0.215	5.21	5.46	3.431	1.556
MS9386-363	6.452	6.498	163.88	165.05	0.205	0.215	5.21	5.46	3.564	1.617
MS9386-364	6.702	6.748	170.23	171.40	0.205	0.215	5.21	5.46	3.698	1.677
MS9386-365	6.952	6.998	176.58	177.75	0.205	0.215	5.21	5.46	3.831	1 738
MS9386-366	7.195	7.255	182.75	184.28	0.205	0.215	5.21	5.46	3.964	1.798
MS9386-367	7.445	7.505	189.10	190.63	0.205	0.215	5.21	5.46	4 097	1.858
MS9386-368	7.695	7.755	195.45	196.98	0.205	0.215	5.21	5.46	4.231	1.919

APPROVED 20 Dec 66 REVISED (A) 1 May 69 (B) FOR CHANGES SEE SHEETS 1, 2, 3, 4, 5, 6 AND 7

User
Army
Navy - SH, MC
Air Force
DSA

Review activity
Army
Navy - OS
Air Force
DSA - IS

This military standard is approved for use by all departments and agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A. Air Force - 11
Other Cust
Army - AV
Navy - AS

TITLE
PACKING, PREFORMED, AMS 7267, O-RING

MILITARY STANDARD
MS 9386

PROCUREMENT SPECIFICATION
NONE

SUPERSEDES:

SHEET 5 OF

DD FORM 672-1 (Reverse coordinated form)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:16Z
Check the source to verify that this is the current version before use.

MS 9386

FED. SUP CLASS
5330

PART NUMBER	ID IN.		ID (mm)		T IN.		T (mm)		APPROX MASS	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	LB/100	kg/100
MS9386-369	7.945	8.005	201.80	203.33	0.205	0.215	5.21	5.46	4.364	1.980
MS9386-370	8.195	8.255	208.15	209.68	0.205	0.215	5.21	5.46	4.497	2.040
MS9386-371	8.445	8.505	214.50	216.03	0.205	0.215	5.21	5.46	4.630	2.100
MS9386-372	8.695	8.755	220.85	222.38	0.205	0.215	5.21	5.46	4.764	2.161
MS9386-373	8.945	9.005	227.20	228.73	0.205	0.215	5.21	5.46	4.897	2.221
MS9386-374	9.195	9.255	233.55	235.08	0.205	0.215	5.21	5.46	5.030	2.282
MS9386-375	9.445	9.505	239.90	241.43	0.205	0.215	5.21	5.46	5.164	2.342
MS9386-376	9.695	9.755	246.25	247.78	0.205	0.215	5.21	5.46	5.297	2.403
MS9386-377	9.945	10.005	252.60	254.13	0.205	0.215	5.21	5.46	5.431	2.464
MS9386-378	10.445	10.505	265.30	266.83	0.205	0.215	5.21	5.46	5.697	2.584
MS9386-379	10.945	11.005	278.00	279.53	0.205	0.215	5.21	5.46	5.964	2.705
MS9386-380	11.445	11.505	290.70	292.23	0.205	0.215	5.21	5.46	6.230	2.826
MS9386-381	11.945	12.005	303.40	304.93	0.205	0.215	5.21	5.46	6.497	2.947
MS9386-382	12.945	13.005	328.80	330.33	0.205	0.215	5.21	5.46	7.030	3.189
MS9386-383	13.945	14.005	354.20	355.73	0.205	0.215	5.21	5.46	7.563	3.431
MS9386-384	14.945	15.005	379.60	381.13	0.205	0.215	5.21	5.46	8.096	3.672
MS9386-385	15.910	16.000	404.11	406.40	0.205	0.215	5.21	5.46	8.619	3.910
MS9386-386	16.910	17.000	429.51	431.80	0.205	0.215	5.21	5.46	9.152	4.151
MS9386-387	17.910	18.000	454.91	457.20	0.205	0.215	5.21	5.46	9.685	4.393
MS9386-388	18.910	19.000	480.31	482.60	0.205	0.215	5.21	5.46	10.218	4.635
MS9386-389	19.910	20.000	505.71	508.00	0.205	0.215	5.21	5.46	10 752	4.877
MS9386-390	20.910	21.000	531.11	533.40	0.205	0.215	5.21	5.46	11.285	5.119
MS9386-391	21.910	22.000	556.51	558.80	0.205	0.215	5.21	5.46	11.818	5 360
MS9386-392	22.880	23.000	581.2	584.2	0.205	0.215	5.21	5.46	12.343	5.599
MS9386-393	23.880	24.000	606.4	609.6	0.205	0.215	5.21	5.46	12.876	5.840
MS9386-394	24.880	25.000	632.0	635.0	0.205	0.215	5.21	5.46	13.409	6.082
MS9386-395	25.880	26.000	657.4	660.4	0.205	0.215	5.21	5.46	13 942	6.324
MS9386-425	4.460	4.490	113.28	114.05	0.269	0.281	6.83	7.14	4.340	1.969
MS9386-426	4.585	4.615	116.44	117.22	0.269	0.281	6.83	7.14	4.457	2.022
MS9386-427	4.710	4.740	119.63	120.40	0.269	0.281	6.83	7.14	4.610	2.091
MS9386-428	4.835	4.865	122.81	123.57	0.269	0.281	6.83	7.14	4.686	2.126
MS9386-429	4.960	4.990	125.98	126.75	0.269	0.281	6.83	7.14	4.800	2.177
MS9386-430	5.077	5.123	128.96	130.12	0.269	0.281	6.83	7.14	4.915	2.229
MS9386-431	5.202	5.248	132.13	133.30	0.269	0.281	6.83	7.14	5.029	2.281
MS9386-432	5.327	5.373	135.31	136.47	0.269	0.281	6.83	7.14	5.143	2.333
MS9386-433	5.452	5.498	138.48	139.65	0.269	0.281	6.83	7.14	5.257	2.385
MS9386-434	5.577	5.623	141.66	142.82	0.269	0.281	6.83	7.14	5.371	2.436
MS9386-435	5.702	5.748	144.83	146.00	0.269	0.281	6.83	7.14	5.486	2.488
MS9386-436	5.827	5.873	148.01	149.17	0.269	0.281	6.83	7.14	5.600	2.540
MS9386-437	5.952	5.998	151.18	152.35	0.269	0.281	6.83	7.14	5.714	2.592
MS9386-438	6.202	6.248	157.53	158.70	0.269	0.281	6.83	7.14	5.943	2.696
MS9386-439	6.452	6.498	163.88	165.05	0.269	0.281	6.83	7.14	6.172	2.800
MS9386-440	6.702	6.748	170.23	171.40	0.269	0.281	6.83	7.14	6.400	2.903
MS9386-441	6.952	6.998	176.58	177.75	0.269	0.281	6.83	7.14	6.629	3.007
MS9386-442	7.195	7.255	182.75	184.26	0.269	0.281	6.83	7.14	6.858	3.111
MS9386-443	7.445	7.505	189.10	190.63	0.269	0.281	6.83	7.14	7.066	3.205
MS9386-444	7.695	7.755	195.45	196.98	0.269	0.281	6.83	7.14	7.315	3.318
MS9386-445	7.945	8.005	201.80	203.33	0.269	0.281	6.83	7.14	7.543	3.422
MS9386-446	8.445	8.505	214.50	216.03	0.269	0.281	6.83	7.14	8.000	3.629
MS9386-447	8.945	9.005	227.20	228.73	0.269	0.281	6.83	7.14	8.457	3.836
MS9386-448	9.445	9.505	239.90	241.43	0.269	0.281	6.83	7.14	8.914	4.043

User: Army, Navy – SH, MC, Air Force, DSA

Review activities: Army, Navy – OS, Air Force, DSA – IS

This military standard is approved for use by all departments and agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

AMSC N/A 1, 2, 3, 4, 5, 6 AND 7

P.A. Air Force – 11
Other Cust
Army – AV
Navy – AS

TITLE
PACKING, PREFORMED, AMS 7267, O-RING

MILITARY STANDARD
MS 9386

PROCUREMENT SPECIFICATION
NONE

SUPERSEDES:

SHEET 6 OF

DD FORM 672-1

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:16Z
Check the source to verify that this is the current version before use.

MS9386

FED. SUP CLASS
5330

PART NUMBER	ID IN.		ID (mm)		T IN.		T (mm)		APPROX MASS	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	LB/100	kg/100
MS9386-449	9.945	10.005	252.60	254.13	0.269	0.281	6.83	7.14	9.372	4.251
MS9386-450	10.445	10.505	265.30	266.83	0.269	0.281	6.83	7.14	9.829	4.458
MS9386-451	10.945	11.005	278.00	279.53	0.269	0.281	6.83	7.14	10.287	4.666
MS9386-452	11.445	11.505	290.70	292.23	0.269	0.281	6.83	7.14	10.734	4.873
MS9386-453	11.945	12.005	303.40	304.93	0.269	0.281	6.83	7.14	11.200	5.080
MS9386-454	12.445	12.505	316.10	317.63	0.269	0.281	6.83	7.14	11.668	5.292
MS9386-455	12.945	13.005	328.80	330.33	0.269	0.281	6.83	7.14	12.115	5.495
MS9386-456	13.445	13.505	341.50	343.03	0.269	0.281	6.83	7.14	12.572	5.703
MS9386-457	13.945	14.005	354.20	355.73	0.269	0.281	6.83	7.14	13.029	5.910
MS9386-458	14.445	14.505	366.90	368.43	0.269	0.281	6.83	7.14	13.486	6.117
MS9386-459	14.945	15.005	379.60	381.13	0.269	0.281	6.83	7.14	13.943	6.324
MS9386-460	15.445	15.505	392.30	393.83	0.269	0.281	6.83	7.14	14.401	6.532
MS9386-461	15.910	16.000	404.11	406.40	0.269	0.281	6.83	7.14	14.840	6.731
MS9386-462	16.410	16.500	416.81	419.10	0.269	0.281	6.83	7.14	15.297	6.939
MS9386-463	16.910	17.000	429.51	431.80	0.269	0.281	6.83	7.14	15.754	7.146
MS9386-464	17.410	17.500	442.21	444.50	0.269	0.281	6.83	7.14	16.211	7.353
MS9386-465	17.910	18.000	454.91	457.20	0.269	0.281	6.83	7.14	16.668	7.560
MS9386-466	18.410	18.500	467.61	469.90	0.269	0.281	6.83	7.14	17.126	7.768
MS9386-467	18.910	19.000	480.31	482.60	0.269	0.281	6.83	7.14	17.583	7.976
MS9386-468	19.410	19.500	493.01	495.30	0.269	0.281	6.83	7.14	18.040	8.183
MS9386-469	19.910	20.000	505.71	508.00	0.269	0.281	6.83	7.14	18.497	8.390
MS9386-470	20.910	21.000	531.11	533.40	0.269	0.281	6.83	7.14	19.411	8.805
MS9386-471	2..910	22.000	556.51	558.80	0.269	0.281	6.83	7.14	20.326	9.220
MS9386-472	22.880	23.000	581.2	584.2	0.269	0.281	6.83	7.14	21.226	9.628
MS9386-473	23.880	24.000	606.6	609.6	0.269	0.281	6.83	7.14	22.140	10.042
MS9386-474	24.880	25.000	632.0	635.0	0.269	0.281	6.83	7.14	23.050	10.455
MS9386-475	25.880	26.000	657.4	660.4	0.269	0.281	6.83	7.14	23.969	10.872

1. MATERIAL: SILICONE RUBBER AMS 7267.
2. DIMENSIONS IN INCHES. METRIC CONVERSIONS ARE IN PARENTHESES. INTERNATIONAL SYSTEM UNITS (SI) SHOWN ARE FOR REFERENCE ONLY.
3. IDENTIFICATION AND PACKAGING PER AMS 2817.
4. MANUFACTURING AND INSPECTION PER AS871.
5. DO NOT USE UNASSIGNED PART NUMBERS.

AS AND AMS ARE SOCIETY OF AUTOMOTIVE ENGINEERS, INC. PUBLICATIONS.
THIS STANDARD WAS DEVELOPED COOPERATIVELY WITH THE MILITARY SERVICES BY THE SAE AEROSPACE PART STANDARDS DIVISION.

User: Army, Navy – SH, MC, Air Force, DSA

Review activities: Army, Navy – OS, Air Force, DSA – IS

This military standard is approved for use by all departments and agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document

APPROVED 20 Dec 66 REVISED (A) 1 May 69 (B) FOR CHANGES SEE SHEETS 1, 2, 3, 4, 5, 6 AND 7

P.A. Air Force - 11
Other Cust
Army – AV
Navy – AS

TITLE
PACKING, PREFORMED, AMS 7267, O-RING

MILITARY STANDARD
MS 9386

PROCUREMENT SPECIFICATION
NONE

SUPERSEDES:

SHEET 7 OF

DD FORM 672-1

☆ U S GOVERNMENT PRINTING OFFICE 1975-603-766/5008

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:16Z
Check the source to verify that this is the current version before use.