WW-D-1909A
January 12, 1978
SUPERSEDING
WW-D-001909 (GSA-FSS)
September 24, 1975 and
Fed. Spec. WW-P-541/8
(In Part) October 12, 1971

# FEDERAL SPECIFICATION

# DISPENSER, PAPER TOWEL

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

## 1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers the requirements for paper towel dispenser cabinets.

1.2 Classification.

1.2.1 Types. Paper towel dispenser cabinets furnished under this specification shall be of the following types (see 6.2):

Type I - Single-fold towel dispenser.
II - Quarter-fold towel dispenser.
III - C-fold towel dispenser.
IV - Double-fold, open top, towel dispenser.

## 2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

UU-T-591 - Towels, Paper.
UU-T-595 - Towel, Wiping, Paper; Industrial and Institutional.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Philadelphia, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Houston, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:24Z
Check the source to verify that this is the current version before use.

Military Standard:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

3. REQUIREMENTS

3.1 Standard commercial product. Paper towel dispensers covered by this specification shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's current standard commercial product.

3.2 General.

3.2.1 Material. Paper towel dispensers shall be made of carbon steel. The thickness of the steel shall be as specified hereinafter. The steel shall be of the quality used in normal practice for the intended purpose.

3.2.2 Door panel and hinge. Doors shall be front opening and hinged. Doors shall be stiffened by embossing at all four edges or by any other suitable forming method.

3.2.3 Door panel lock. Each dispenser with a door shall be equipped with a key lock. The lock shall lock automatically when the door is closed.

3.2.4 Dispensing slot panels. Cabinets shall have a bottom dispensing slot. The dispensing slot panel shall be designed to prevent tearing of towels (see 4.4).

3.2.5 Fill indicator. Except for open top dispensers, an indicator or slot shall be provided to clearly show the supply of towels in the cabinet.

3.2.6 Fastening holes. Each dispenser shall have a minimum of four mounting holes or slots in the rear panel except that open top dispensers shall have three holes or slots. The width of the slots and the diameter of the holes shall be 3/16 inch minimum.

3.3 Dispenser construction.

3.3.1 Type I. Type I dispenser shall be suitable for dispensing type I single-folded towels in accordance with UU-T-591. The minimum thickness of the uncoated metal shall be 0.033 inch. The color of the dispenser shall be white.

3.3.2 Type II. Type II dispensers shall be suitable for dispensing type V, quarter-fold towels in accordance with UU-T-595. The minimum thickness of the uncoated metal shall be 0.033 inch. The finish coat shall be green enamel.

3.3.3 Type III. Type III dispensers shall be suitable for dispensing type III C-folded towels in accordance with UU-T-591. The minimum thickness of the uncoated metal shall be 0.033 inch. The color of the dispenser shall be white.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:24Z
Check the source to verify that this is the current version before use.

3.3.4 Type IV. Type IV dispensers shall be open top design. The dispenser shall be for dispensing double-fold paper towels. The minimum inside dimensions of the dispenser shall be 8 inches high, 11 inches long, and 6-1/2 inches in depth. The minimum thickness of the uncoated metal shall be 0.027 inch. Body members shall be joined by spot welding to form a rigid structure having square corners, free from twist or warpage, and of uniform sides. All unprotected metal edges shall be rolled. The edges around the top of the dispenser shall be rolled to the inside of the dispenser. The color of the dispenser shall be white.

3.4 Finish. Prior to painting, all metal surfaces shall be given a rust preventive chemical conversion coating in accordance with the manufacturer's standard practice. The exterior and interior finish shall be a smooth baked, gloss enamel which shall be hard, durable, continuous, and free from blisters, pinholes, or other surface blemishes.

3.5 Furnished items.

3.5.1 Lock key. Types I, II, and III dispensers shall be furnished with a minimum of one lock key. The key(s) shall be taped to the exterior of the dispenser.

3.5.2 Wood screws. All dispensers shall be furnished with the appropriate number of No. 8- by 3/4-inch round-head or pan-head wood screws. Except for stainless steel, screws shall be plated to resist corrosion. The screws shall be placed in an envelope and packaged with the dispenser.

3.6 Mounting. All dispensers shall be for surface mounting.

3.7 Marking. Each dispenser shall be clearly marked with the manufacturer's name or registered trademark. The method of marking shall be by embossing, stamping, or decalcomania.

3.8 Workmanship. All surfaces shall be free from sharp edges. Exposed enameled surfaces shall be smooth and uniform in application and color and free of chips, cracks, or other defects affecting appearance. All surfaces shall be free of blisters.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government.

4.2 Sampling for examination and tests. Samples for examination shall be selected in accordance with level S-4 in MIL-STD-105. Sample for tests shall be selected in accordance with level S-2 in MIL-STD-105.

4.3 Examination and tests.

4.3.1 Examination. Examine dispensers selected in accordance with 4.2 for defects listed in table I. The acceptable quality levels (AQL's) for defects shall be 2.5 percent defective for major defects and 6.5 percent defective for total defects.

TABLE I. Classification of defects

| Defects | Major | Minor |
|---|---|---|
| Type not as specified | X | |
| Material not as specified. | X | |
| Door panel not stiffened | X | |
| Lock not as specified. | X | |
| Finish not as specified | X | |
| Furnished items missing | X | |
| Dimensions not as specified | X | |
| Markings not as specified | | X |
| Damage or defects affecting function or serviceability | X | |
| Damage or defects not affecting function or serviceability | | X |

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:24Z
Check the source to verify that this is the current version before use.

4.3.2 Test. Test dispensers selected in accordance with 4.2 as specified in 4.4. The AQL for the test shall be 4.0 percent defective.

4.4 Test method. Using paper towels intended for use with the dispenser, fill the dispenser to the maximum capacity recommended by the manufacturer. Remove 10 towels, one at a time, at intervals of not greater than 1 second. Upon completion of removal of 10 towels, examine towels for conformance to 3.2.4.

4.5 Inspection of preparation for delivery. An inspection shall be made to determine whether the packaging, packing and marking comply with the requirements in section 5 of this specification. Defects shall be scored in accordance with table II. For examination of interior packaging, the sample unit shall be one shipping container fully prepared for delivery, selected at random just prior to the closing operations. Sampling shall be in accordance with MIL-STD-105. Defects of closure listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 with an AQL of 4.0 defects per hundred units.

TABLE II. Classification of preparation for delivery defects

| Examine | Defects |
|---|---|
| Markings | Omitted; incorrect; illegible; improper size, location, sequence or method of application. |
| Material | Any component missing, damaged or not conforming to the applicable specification or requirements stated herein. |
| Workmanship | Inadequate application of components such as incomplete closure of container flaps, loose strapping or distortion of container. |
| Contents | Quantity per container is more or less than required. Gross weight exceeds requirements of the box specification. |

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A. Each dispenser shall be packaged in a paperboard or fiberboard box. The box shall be secured to prevent accidental opening.

5.1.2 Commercial. Each dispenser shall be packaged in accordance with normal commercial practice. The complete package shall be designed to protect the item against damage during shipment, handling, and storage.

5.2 Packing. Packing shall be level A or commercial as specified (see 6.2).

5.2.1 Level A. Dispensers, packaged as specified in 5.1.1, shall be packed in boxes made from weather-resistant fiberboard having a bursting strength of not less than 275 pounds per square inch. The box flaps shall be secured with water-resistant adhesive applied to not less than 75 percent of the surface area of contact between the flaps, or with 3 inch wide water resistant tape applied to the full length of the center seams and extending over the ends not less than 3 inches. Alternatively, cleated plywood, wirebound, or nailed wood boxes shall be acceptable shipping containers when lined with a waterproof barrier material. The edges of the barrier material shall be sealed with waterproof tape or adhesive.

5.2.2 Commercial. The dispensers, packaged as specified in 5.1.2, shall be packed in fiberboard boxes to insure safe delivery at destination, to provide for safe redistribution by the initial receiving activity and shall be acceptable by common carrier under National Motor Freight Classification or Uniform Freight Classification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:24Z
Check the source to verify that this is the current version before use.

5.3 Unitization. When shipments to Government depots are full car or truckload, the shipping containers shall be unitized for shipment and handling in accordance with normal commercial practice. The unitized load shall not exceed 2,500 pounds in weight, 63 inches in height, 56 inches in length and 45 inches in width.

6. NOTES

6.1 Intended use.

6.1.1 Type II. Type II dispensers are intended for dispensing disposable paper towels used for cleaning, polishing, and wiping operations.

6.1.2 Types I, III, and IV. These dispensers are intended for dispensing disposable paper towels for drying the hands.

6.2 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type (see 1.2.1).
(c) Selection of applicable packaging and packing levels (see 5.1 and 5.2).

6.3 Specification cross reference.

| WW-P-541b | WW-P-541/8 | | | WW-D-001909 | WW-D-1909A |
|---|---|---|---|---|---|
| Type | Type | Class | Style | Type | Type |
| 445 | I | 3 | N | 445 | I |
| --- | I | 3 | N | 443 | II |
| 449 | I | 3 | N | 449 | III |
| --- | I | 3 | N | 444 | IV |

MILITARY INTERESTS:

Custodians:

Army - ME
Navy - YD
Air Force - 99

Review Interest:

Navy - CG
DSA - CS

User Interest:

Navy - MC
Army - CE

Military Coordinating Activity:

Navy - YD

Preparing Activity:

GSA-FSS

Civil Agency Coordinating Activity:

GSA-PCS-PBO

5

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See Section 2 of this specification to obtain extra copies and other documents referenced herein. Price 60 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:24Z
Check the source to verify that this is the current version before use.