AMENDMENT

TO

INTERIM FEDERAL SPECIFICATION

TRAP, DRAIN, PLUMBING FIXTURE (P-TRAP) (LAND USE)

This amendment was developed by the General Services Administration, Federal Supply Service, Washington, DC 20406, based upon currently available technical information. The General Services Administration has authorized this amendment as a part of Interim Federal Specification WW-F-001914 (GSA-FSS), dated November 17, 1975.

PAGE 1

Paragraph 2.1, delete reference to Federal Specifications and all Federal Specifications listed thereunder.

PAGE 2

Paragraph 2.1, under Military Standards, delete MIL-STD-105.

Paragraph 2.2, delete all reference to ASTMs B456, B504, and B571 and in their place substitute the following:

"B287 - Acetic Acid-Salt Spray (Fog) Testing."

PAGE 3

Paragraph 3.7.2, delete in its entirety and substitute the following:

"3.7.2 Exterior surfaces. Exposed surfaces of traps, plugs, and other hardware shall have a bright or satin chromium plated finish at the manufacturer's option. The plated surface shall show no evidence of corrosion when tested for 8 hours in accordance with 4.5.1".

PAGE 5

Paragraph 4.5.1, delete in its entirety and substitute the following:

"4.5.1 Chromium plating. Test chromium plating in accordance with ASTM B287. At end of test examine specimen for conformance to 3.7.2".

Paragraph 4.5.2, delete in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:24Z
Check the source to verify that this is the current version before use.

PAGE 6

Section 5 "PREPARATION FOR DELIVERY". Delete entire section and substitute the following:

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or commercial as specified (see 6.2).

5.1.1 Level A. Each drain trap shall be packaged in a paperboard or fiberboard box. The box shall be secured to prevent accidental opening.

5.1.2 Commercial.

5.1.2 Commercial. Each drain trap shall be packaged in accordance with normal commercial practice. The complete package shall be designed to protect the item against damage during shipment, handling and storage.

5.2 Packing. Packing shall be level A or commercial as specified (see 6.2).

5.2.1 Level A. Twenty-five (25) drain traps packaged as specified in 5.1.1 shall be packed in boxes made from weather resistant fiberboard having a bursting strength of not less than 275 pounds per square inch. The box flaps shall be secured with water resistant adhesive applied to not less than 75 percent of surface area of contact between the flaps or with 3-inch wide water resistant tape applied to the full length of the center seams and extending over the ends not less than 3 inches. Alternatively, cleated plywood, wirebound, or nailed wood boxes shall be acceptable shipping containers when lined with a water proof barrier material. The edges of the barrier material shall be sealed with waterproof tape or adhesive to protect the contents.

5.2.2 Commercial. Drain traps, packaged as specified in 5.1.2, shall be packed in fiberboard boxes to insure safe delivery at destination, to provide for safe redistribution by the initial receiving activity, and shall be acceptable by common carrier under National Motor Freight Classification or Uniform Freight Classification.

5.3 Unitization. When shipments to Government depots are full car or truckloads, the shipping containers shall be unitized for shipment and handling in accordance with normal commercial practice. The unitized load shall not exceed 2,500 pounds in weight, 63 inches in height, 56 inches in length, and 45 inches in width.

5.4 Marking. Packages, shipping containers, and unitized loads (when applicable) shall be marked in accordance with Fed. Std. No. 123.

Paragraph 6.2, delete subparagraph (d) in its entirety.

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:24Z
Check the source to verify that this is the current version before use.