WW-T-1765A
October 29, 1976
SUPERSEDING
Fed. Spec. WW-T-1765
March 8, 1974

FEDERAL SPECIFICATION

TOILET, PORTABLE, SELF-CONTAINED

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers self-contained, portable toilets intended for use in campgrounds, recreational areas, construction sites, and other such locations where use of a conventional toilet may not be practical.

1.2 Classification.

1.2.1 Types, styles, classes, models, and sizes. Portable toilets shall be of the following types, styles, classes, models, and sizes, as specified (see 6.2):

Type I - Recirculating.

Style A - Indoor.

Size 1 - Minimum 150 usages = (based on 70 percent of 15 gallon tank).
Size 2 - Minimum 400 usages = (based on 70 percent of 40 gallon tank).

Style B - Outdoor (with cabana).

Size 2 - Minimum 400 usages = (based on 70 percent of 40 gallon tank).
Size 3 - Minimum 800 usages = (based on 70 percent of 80 gallon tank).
Size 4 - Minimum 1000 usages = (based on 70 percent of 100 gallon tank).

Class 1 - With urinal.
Class 2 - Without urinal.

Model 1 - Open front seat.
Model 2 - Pop-up seat.
Model 3 - Molded seat on removable tank cover.

Type II - Nonrecirculating.

Style B - Outdoor (with cabana).

Size 2 - Minimum 400 usages = (based on 70 percent of 40 gallon tank).
Size 3 - Minimum 800 usages = (based on 70 percent of 80 gallon tank).
Size 4 - Minimum 1000 usages = (based on 70 percent of 100 gallon tank).

Class 1 - With urinal.
Class 2 - Without urinal.

Model 1 - Open front seat.
Model 3 - Molded seat on removable tank cover.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:24Z
Check the source to verify that this is the current version before use.

Federal Specification:

TT-E-489 - Enamel, Alkyd, Gloss (For Exterior and Interior Surface).

Federal Standard:

Fed. Std. No. 123 - Marking for Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Preproduction sample. Unless otherwise specified (see 6.2), the contractor shall furnish within the time limit specified in the contract, one toilet of each type and style specified in the contract as preproduction samples for examination and testing. Examination and tests shall be as specified in section 4 and shall be subject to surveillance and approval by the government. Approval of the preproduction samples on the basis of the specified examination and tests shall not relieve the contractor of his obligation to meet the requirements of this specification for the remaining units furnished under the contract.

3.2 Types I and II toilets shall be the manufacturer's standard commercial products, except as herein and herewith modified.

3.3 Materials.

3.3.1 Types I and II. All materials, piping, and fittings shall be corrosion resisting.

3.3.2 Tank assembly.

3.3.2.1 Type I. Materials used for the tank assembly shall be plastic, layered polyester fiberglass, stainless steel, ceramic material, or exterior grade plywood coated with a plastic resin.

3.3.2.2 Type II. In addition to the acceptable materials listed in 3.3.2.1, the tank assembly shall be fabricated from galvanized steel, 18 gauge or thicker, provided the steel has been protectively covered with a minimum of two coats of enamel.

3.3.3 Tank, interior finish. The interior of all toilet tanks shall have an impervious, smooth surface to facilitate cleaning. The surface shall be resistive to chemical and waste corrosion and impervious to the absorption of waste and chemical derivatives.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:24Z
Check the source to verify that this is the current version before use.

3.3.4 Toilet bowl. The toilet bowl shall be constructed, formed, or fabricated from corrosion resisting steels ceramic or ceramic coated metal, plastic, layered polyester fiberglass, or gel coat materials. The bowl shall have a smooth surface and shall resist burning.

3.3.5 Styles A and B.

3.3.5.1 Exterior finish. The exterior of indoor units shall have a smooth surface. The surface shall be impervious to the absorption of chemical and waste derivatives.

3.3.6 Style B.

3.3.6.1 Cabana.

3.3.6.1.1 Type I. Materials utilized in the construction of cabanas shall be anodized aluminum, corrosion resisting steel, plastic, layered polyester fiberglass, or exterior grade plywood coated with a plastic resin. Materials utilized shall resist cracking at a temperature range of -25°F to +120°F.

3.3.6.1.2 Type II. In addition to the acceptable materials listed in 3.3.6.1.1, the cabana shall be fabricated from galvanized steel, 18 gauge or thicker, provided the steel has been protectively covered with a minimum of two coats of enamel, conforming to class A, composition G of TT-E-489.

3.3.6.1.3 Cabana, interior finish. The interior finish of the cabana shall have a smooth surface to facilitate cleaning. The surface shall also be impervious to the absorption of chemical and waste derivatives.

3.3.6.1.4 Color. The exterior of the cabana shall be in the color specified (see 6.2), but selection of color shall be limited to brown, blue, green, or white.

3.3.6.2 Skids and tank underguard. Skids and tank underguard shall be fabricated from noncorrosive metal or constructed from construction grade woods.

3.3.6.2.1 Treatment. With the exception of redwood, wooden skids shall be pressure or dip treated to resist mold, rot, and insect damage.

3.3.6.3 Hardware. All hardware, including latches, chains, locks, and hinges shall be made from corrosion resisting steel, brass, or carbon steel. If made from carbon steel, it shall be zinc, cadmium or chrome plated. Metals shall be selected for similarity to reduce or inhibit electrolytic corrosion.

3.3.7 Urinal.

3.3.7.1 Type I, class 1. The urinal shall be made of plastic, layered polyester fiberglass, corrosion resisting steel, ceramic material, or exterior grade plywood coated with a plastic resin.

3.3.7.2 Type II, class 1. In addition to the acceptable materials listed in 3.3.7.1, the urinal shall be fabricated from galvanized steel. The steel shall be 20 gauge or thicker and protectively covered with a minimum of two coats of enamel.

3.4 Construction.

3.4.1 Toilet seat.

3.4.1.1 Model 1. An open front seat design shall be provided.

3.4.1.2 Model 2. A pop-up seat design, shall be provided.

3.4.1.3 Model 3. Molded impression of toilet seat shall be integral to removable tank cover.

3.4.2 Seat cover (lid). A toilet seat cover shall be provided.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:24Z
Check the source to verify that this is the current version before use.

3.4.3 Toilet tank. The interior of the toilet tank shall be designed to provide a recess or sloping surface to facilitate pump-out. The tank interior shall be free of any obstructions that might hang up waste material.

3.4.4 Toilet bowl.

3.4.4.1 Type I. All recirculating toilets shall utilize a bowl design that provides sight restriction so the contents of the bowl cannot be viewed when facing the bowl from a normal angle. The sight restrictor shall be noncorrosive and shall be spring loaded or welded or bonded to the bowl. If welded or bonded, a through bowl cleanout plug shall be provided.

3.4.5 Style A.

3.4.5.1 Mounting fixtures. Indoor units shall be furnished with a sufficient number of mounting fixtures to assure a rigid attachment when properly mounted.

3.4.5.2 Ventilation. Units shall be provided with a method for venting to the outside.

3.4.6 Style B.

3.4.6.1 Interior surfaces. There shall be no open spaces, crevices, or any other hard to clean features within the cabana.

3.4.6.2 Floor. The floor shall be provided with suitable antiskid protection. If the antiskid device is removable, it shall be easily replaceable.

3.4.6.3 Urinal. Two methods are acceptable for attachment of the urinal to the tank assembly.

3.4.6.3.1 Method 1. The urinal shall be located in a position relative to the tank so the urinal spout goes directly into the tank. The spout diameter shall be a minimum of 3/4 inch.

3.4.6.3.2 Method 2. The urinal shall be connected to the tank by a smooth hose. A minimum hose diameter of 3/4 inch is required. Without creating a trap, there shall be a curved passageway between the urinal and the tank.

3.4.6.4 Paper holder. A two roll toilet tissue dispenser shall be provided. The dispenser shall be constructed to prevent "free reeling" of the toilet tissue.

3.4.6.5 Tank underguard. A tank underguard shall be provided. The underguard shall completely protect the tank bottom from damage during pickup.

3.4.6.6 Skids. Outdoor units shall be securely mounted on removable skids.

3.4.6.7 Ventilation.

3.4.6.7.1 Tank ventilation. A minimum vent area to the outside from the tank of 12.5 square inches (a circle approximately 4 inches in diameter) shall be provided, but in no case shall the tank vent area be less than the area of the bowl opening.

3.4.6.7.2 Cabana ventilation. There shall be a minimum of two screened ventilation areas venting the cabana, each having a minimum of 50 square inches of vent area. The vents shall be provided with 16-mesh screening.

3.4.6.8 Hardware. Each unit shall be fitted with a securely attached inside hook and eye or a slide bolt. The door shall be provided with a spring of sufficient strength to close the door automatically. Hardware shall be tamper resistant.

3.4.6.8.1 Hasp assembly. An outside hasp assembly shall be provided. The hasp assembly shall be removable.

3.4.6.8.2 Hinges. Door hinges shall be piano, butt design, heavy duty spring loaded, screen door hinges, or heavy duty 6 inch straps. Hinges shall be rigidly attached and shall be tamper resistant.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:24Z
Check the source to verify that this is the current version before use.

3.5 Operation.

3.5.1 Type I.

3.5.1.1 Flush cycle. Actuation of the flushing control shall cause the flushing fluid to be drawn from the tank, through a filter, and into the bowl to clean and flush waste material back into the tank.

3.5.1.1.1 Flushing fluid. The flushing fluid shall contain a bacteria and odor control chemical. When the toilet is of a waterless design, the flushing fluid shall be a mineral oil base solution. The chemical or oil shall be non-toxic and shall be compatable with all materials used in the construction of the waste storage tank and the recirculating system.

3.5.1.2 Method of flushing. Recirculating toilets shall be electrically, air, hand or foot pedal operated. Batteries if used, shall be located in a lockable compartment.

3.5.1.3 Flushing control. Flushing shall be accomplished with a single control which is easy to find and operate. A permanent label shall be fixed to the unit with the operating instructions clearly printed.

3.5.1.4 Filter. The filter shall be a self-cleaning or replaceable cartridge type design. It shall be easily accessible for repair and replacement.

3.5.1.5 Pump. The flush pump shall provide the flushing fluid with sufficient velocity to wash deposits from the bowl.

3.5.2 Type II. Type II units shall be of a nonrecirculating design, not utilizing a mechanical flush system.

3.6 Usages.

3.6.1 Types I and II. Minimum number of usages shall be based on 70 percent capacity. The following minimun number of usages shall be accomodated before the tank exceeds 70 percent capacity.

TABLE I.

Size	No. of usages * (min)
1	150
2	400
3	800
4	1000

* Usage - One usage = 0.071 gallon.

3.7 Provision of pump out.

3.7.1 Types I and II. Pumping out of the toilet tank shall be provided for by any one of the three following methods.

3.7.1.1 Method 1. A side drain or bottom drain valve for type I and II shall be provided with a 3 inch minimum diameter opening. The valve shall have a lockable, securely fitting protective cover, hinged to the unit or, for a type I, a rear or side pumpout port approximately 6 inches by 12 inches to provide access to the interior of the tank at the angle to reach all four corners.

3.7.1.2 Method 2. The unit shall be designed to permit pumping through the seat with a 2 inch minimum diameter suction hose.

3.7.1.3 Method 3. The unit shall be designed with a liftable seat to allow access for pumping.

3.8 Functional requirements.

3.8.1 Types I and II.

3.8.1.1 Static load. When tested in accordance with 4.4.2.1.1, the unit shall show no visible distortion or deformation, no leaking, and no evidence of cracking or chipping.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:24Z
Check the source to verify that this is the current version before use.

3.8.2 Type I.

3.8.2.1 Flush control. When tested in accordance with 4.4.2.2.1, the flush control shall show no signs of failure.

3.8.2.2 Pump. When tested in accordance with 4.4.2.2.2, the cumulative degradation in pump volume shall not exceed 10 percent.

3.8.2.3 Filter. When tested in accordance with 4.4.2.2.3, the filter shall remain in operable condition.

3.9 Instruction manual. The manufacturer shall furnish with each order supplied, three copies of a manual of installation, operating, and servicing procedures.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling.

4.2.1 Visual examination. Sampling for these characteristics shall be in accordance with general inspection level II in MIL-STD-105.

4.3 Examination.

4.3.1 End item examination. Toilets shall be examined for defects listed in table II. The Acceptable Quality Level (AQL) for defects shall be 2.5 defects per hundred units for major defects and 6.5 defects per hundred units for total defects.

TABLE II. Dlassification of defects, end item

Defects	Major	Minor
Type, style, class, model, or size not as specified	X	
Materials unacceptable	X	
Tank interior finish not smooth or impervious	X	
Toilet bowl not smooth surface		X
Cabana interior finish not smooth or impervious	X	
Style A exterior finish not smooth or impervious	X	
Seat cover missing	X	
Tank interior not designed with recess or sloping surface, not free of obstructions		X
Sight restrictor missing	X	
Color not as specified	X	
Style B unit has hard to clean features		X
Antiskid device missing	X	
Urinal connection other than methods 1 or 2		X
Paper holder missing		X
Tank underguard missing	X	
Ventilation less than required	X	
Hardware missing or not tamper resistant		X
Style A mounting fixtures missing	X	
No method for venting style A	X	
Battery compartment not lockable	X	
Operating instructions missing		X
Pump out provision not acceptable	X	
Filter not easily accessible		X
Damage or defects affecting function or serviceability	X	
Damage or defects not effecting function or serviceability		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:24Z
Check the source to verify that this is the current version before use.

4.4 Tests.

4.4.1 Frequency of tests. Unless otherwise specified (see 6.2), tests shall be performed on the preproduction samples and thereafter only when changes in material or designs are made.

4.4.2 Functional tests.

4.4.2.1 Types I and II.

4.4.2.1.1 Static load. The test procedure for compliance with 3.8.1.1 shall be as follows. The assembled unit shall be preconditioned to 73°F for 2 hours before the test. The unit shall then be filled with water to the fluid level which would occur after full usage. The seat cover shall be removed. With the unit mounted as recommended by the manufacturer, a gradual increasing static load starting with 45 pounds shall be applied until a uniform static load of 600 pounds is placed vertically on the unit then removed.

4.4.2.2 Type I.

4.4.2.2.1 Flush control reliability. Type I units shall be cycled in the following manner to test the reliability of the flush control system. The unit shall first be charged to the level recommended by the manufacturer. The unit shall then be cycled through 5,000 flush cycles. Cycling shall be accomplished automatically, but at a controlled rate to prevent overheating (if electric operation). To simulate actual operating conditions, 750 grams of toilet paper per 10 gallons of toilet volume shall be added at regular intervals during the cycling test.

4.4.2.2.2 Pump reliability. At the end of the following flush cycles the volume of the pump shall be measured. The degradation in pump volume at the end of each of the 10 measurement periods shall be noted, and after the tenth measurement period the degradations shall be added together to compute the cumulative degradation:

Cycle	Cycle
1	2500
100	3500
500	4000
1000	4500
1500	5000

4.4.2.2.3 Filter. The condition of the filter at the end of the cycling test outlined in 4.4.2.2.1 shall be observed for conformance to 3.8.2.3.

5. PREPARATION FOR DELIVERY

5.1 Packaging and packing. Unless otherwise specified (see 6.2), each complete toilet shall be packaged and packed for domestic or export shipment in accordance with the manufacturer's recommendations, which will insure carrier acceptance and safe delivery at the lowest rates to the ultimate destination.

5.2 Marking. In addition to any special markings required by the contractor or order, all markings shall be in accordance with Fed. Std. No. 123 or MIL-STD-129, as applicable.

6. NOTES

6.1 Intended use. Style A units are intended to be installed in an existing structure, whereas style B units are intended to provide self-enclosed toilet facilities where there is no such existing structure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:24Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type, style, class, model, size (see 1.2.1).
(c) When preproduction samples are not required (see 3.1).
(d) Color of cabana, brown, blue, green, or white (see 3.3.6.1.4).
(e) Frequency of tests, if different (see 4.3.2.2).
(f) Packaging and packing, if different (see 5.1).

6.3 Preproduction model. Any changes or deviations of production toilets from the approved preproduction model during production will be subject to the approval of the contracting officer. Approval of the preproduction model will not relieve the supplier of his obligation to furnish toilets conforming to this specification.

CIVIL AGENCY COORDINATING ACTIVITIES:

GSA - PBO
OSH - OSH
USDA - AFS

PREPARING ACTIVITY: GSA - FSS

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See Section 2 of this specification to obtain extra copies and other documents referenced herein.
Price cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:24Z
Check the source to verify that this is the current version before use.