THIS IS A REPRINT ARRANGED TO FIT THE LARGER SPECIFICATION BINDERS

ZZ-B-71b

JUNE 16, 1944

SUPERSEDING
Fed. Spec. ZZ-B-71a
May 2, 1933

FEDERAL SPECIFICATION

BAGS; POLITZER*

This specification was approved on the above date by the Director of Procurement, for the use of all departments and establishments of the Government, and shall become effective not later than August 15, 1944. It may be put into effect, however, at any earlier date after promulgation.

A. APPLICABLE SPECIFICATION.

A–1. The following Federal Specification, of the issue in effect on date of invitation for bids, shall form a part of this specification:

ZZ–R–601—Rubber Goods; General Specifications (Methods of Physical Tests and Chemical Analyses).

B. TYPES AND CLASSES.

B–1. Politzer bags shall be of the following types and classes, as specified in the invitation for bids:

Type I. Valveless.
Type II. Valve.

B–1a. *Classes.*—

Class A. Rubber or synthetic rubber bag and tubing.
Class B. Chloroprene polymer type bag and tubing.

C. MATERIAL AND WORKMANSHIP.

C–1. The surface shall be smooth and free from pits or other imperfections. An embossed surface will not be acceptable. Rubber, synthetic rubber, and mixtures thereof shall be of good quality and suitable for the purpose.

*Certain provisions of this specification are intended to conserve critical or strategic materials. When the present emergency is over, this specification will be considered for revision.

D. GENERAL REQUIREMENTS.

D–1. *Design.*—Bags shall be pear-shaped and shall be fitted with throat plug having threaded hole to receive a straight tapered connection piece. Each bag shall be furnished complete with one straight tapered hard connection piece about 2 inches long, one round, olive point, hard nasal tip about ⅝-inch diameter at its widest point, and one piece of tubing not less than 6 inches in length. The connection piece and the nasal tip shall make tight fit with the tubing. Politzer bags shall be of 8-ounce capacity. (See pars. E–1 and E–2.)

D–2. *Dimensions.*—The wall of the bag shall be 0.125 inch thick with a tolerance of plus or minus 0.025 inch. The tubing shall be 3/16-inch inside diameter with 1/16-inch wall.

E. DETAIL REQUIREMENTS.

E–1. *Class A bags, rubber or synthetic rubber, bags and tubing.*—

E–1a. Bags and tubing shall be made of a rubber compound, a synthetic rubber compound or a suitable mixture thereof.

E–1b. Hard connection pieces and nasal tips shall be made of hard rubber, hard synthetic rubber or a suitable mixture thereof.

E–1c. Synthetic rubber shall be the types known as

GR-I (Butyl);
GR-M (Chloroprene polymer); and
GR-S (Buna S).

E–2. *Class B bags, chloroprene polymer type.*—

E–2a. Bags and tubing shall be made of synthetic rubber compound of the chloroprene polymer type.

E–2b. Hard connection pieces and nasal tips shall be made of hard Buna S (GR-S) synthetic rubber.

E–3. *Tensile strength.*—The tensile strength of bags and of tubing shall be at least 1,200 and 1,800 pounds per square inch, respectively.

E–4. *Ultimate elongation.*—The ultimate elongation of bags shall be not less than 300 percent (2 inches to 8 inches) and of tubing not less than 700 percent (1 inch to 8 inches).

E–5. *Resistance to hot air.*—The bag and tubing, after being subjected to a temperature of 158° F. plus or minus 2° F. in air for 7 days, shall show a decrease in tensile strength of not more than 25 percent.

E–6. *Branding.*—Each bag shall be marked with the manufacturer's name and trade name and date of manufacture.

E–7. *Valve.*—The type II bag (valve type) shall automatically prevent the contained air from passing the valve when pressure is applied to the bulb but permit air to flow through the valve when the pressure is released.

F. METHOD OF SAMPLING, INSPECTION, AND TESTS.

F–1. *Sampling.*—One bag shall be taken at random from each 100 or less delivered, for test and analysis.

F–2. *Inspection and tests.*—See paragraphs A–1, E–3, E–4, and E–5.

Source: https://assist.dla.mil -- Downloaded: 2026/10-26T12:25Z
Check the source to verify that this is the current version before use.

G. PACKAGING, PACKING, AND MARKING FOR SHIPMENT.

G–1. *Packaging.*—Unless otherwise specified, commercial packages are acceptable under this specification.

G–2. *Packing.*—Unless otherwise specified, the subject commodity shall be packed in substantial commercial containers of the type, size, and kind commonly used for the purpose, so constructed as to insure acceptance and safe delivery by common or other carriers, at the lowest rate, to the point of delivery called for in the contract or purchase order.

G–3. *Marking.*—Unless otherwise specified, shipping containers shall be marked with the name of the material, and the quantity contained therein, as defined by the contract or order under which the shipment is made, the name of the contractor, and the number of the contract or order.

H. REQUIREMENTS APPLICABLE TO INDIVIDUAL DEPARTMENTS.

H–1. The following departmental specifications of the issue in effect on date of invitation for bids, and special requirements, shall form a part of this specification and shall be applicable to purchases made under this specification by the respective departments:

H–2. *Army:* United States Army Specification No. 100–2, Standard Specification for Marking Shipments.

H–3. *Navy:*

H–3a. *Navy Department Specifications.*—

General Specifications for Inspection of Material
39P16—General Specification for Packaging and Packing for Overseas Shipment.

Copies of these specifications and of the Navy Shipment Marking Handbook may be obtained without cost upon application to the Bureau of Supplies and Accounts, Navy Department, Washington 25, D. C.

H–3b. *Packaging.*—

H–3b (1). Unless otherwise specified, pollitzer bags shall be packaged individually in substantial folding or set-up boxes as follows:

H–3b (2). Full telescope style folding cartons of not less than 0.026 inch caliper.

H–3b (3). Telescope set-up boxes, with minimum lid depth of one (1) inch. Caliper of board shall be not less than 0.022 inch, No. 2 finish. The boxes shall be plain stayed with not less than 60-pound basis weight kraft stays and either full tight wrapped or strip wrapped.

H–3c. *Packing.*—

H–3c (1). *For domestic shipment.*—Unless otherwise specified, pollitzer bags, packaged as described in paragraph H–3b, shall be packed in units of 100 in either R. S. C. style 275-pound Mullen test corrugated or solid fiberboard cartons. Carton flaps shall be sealed by means of a suitable adhesive, metal stitched, or taped. If taped, kraft gummed tape of not less than 2½-inch width, 60-pound basis weight, shall be used.

H–3c (2). *For overseas shipment.*—Unless otherwise specified, pollitzer bags packed as described in paragraph H–3c (1) shall be overpacked in units of one (1) or two (2) in nailed wood boxes, wire-bound boxes, or cleated plywood boxes, conforming to the requirements of the applicable section of Navy Department Specification 39P16, except that if plywood boxes are used cleat drainage ducts will not be required. Shipping containers shall be lined with a sealed waterproof bag, or its equivalent, made in conformance with the construction and tests of Section XXV of Navy Department Specification 39P16. The material used shall have a minimum water resistance of 24 hours. The seams and closures shall have strength and water resistance equal to that of the body material. Shipping containers shall be strapped in accordance with the strapping requirements of the applicable sections of Navy Department Specification 39P16.

H–3c (3). *For domestic and overseas shipment.*—When practicable, shipping containers shall be of uniform size and shall contain the same number of items of one type and class. Containers shall be designed to fit the contents in a compact manner.

H–3d. *Marking.*—

H–3d (1). *Packages.*—Unless otherwise specified, each package shall be plainly marked with the following:

Name of article.
Stock No. ——.
Type.
Class.
Quantity contained (as defined by the contract or order).
Name of manufacturer.

H–3d (2). *Shipping containers.*—Unless otherwise specified, each shipping container shall be plainly marked in black on two adjacent sides with the following:

Name of article.
Stock No. ——.
Type.
Class.
Quantity contained (as defined by the contract or order).
Name of contractor or manufacturer.
Contract No. ——.
Gross weight.
Requisition No. ——.

H–3d (3). *For domestic and overseas shipment.*—In addition to the foregoing, marking shall conform to the specific requirements of the latest issue of the Navy Shipment Marking Handbook.

I. NOTES:

I–1. Purchasers should exercise any desired options offered herein and specify the type and class required.

I–2. It is believed that this specification adequately describes the characteristics necessary to secure the desired material and that nor-

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T12:25Z
Check the source to verify that this is the current version before use.

mally no samples will be necessary prior to award to determine compliance with this specification. If, for any particular purpose, samples with bids are necessary, they should be specifically asked for in the invitation for bids, and the particular purpose to be served by the bid sample should be definitely stated, the specification to apply in all other respects.

I–3. Federal Specifications do not include all types, classes, grades, sizes, etc., of the commodities indicated by the titles of the specifications, or which are commercially available, but are intended to cover the types, etc., which are suitable for Federal Government requirements.

Notice.—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

(Activities outside the Federal Government may obtain copies of Federal Specifications and Standards as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington 25, D. C.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, Seattle, and Washington, D. C.

(Federal Government activities may obtain copies of Federal Specifications and Standards and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Copies of this specification may be purchased for cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:25Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:25Z
Check the source to verify that this is the current version before use.