INTERIM AMENDMENT

TO

FEDERAL SPECIFICATION

MAT, FLOOR (LINK-TYPE)

This interim amendment was developed by the Standardization Division, Federal Supply Service, General Services Administration, Washington, D. C. 20406, based on currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized Federal agencies to use this amendment as a valid exception to Federal Specification ZZ-M-46C, dated July 8, 1966.

PAGE 1

Paragraph beginning "(Single copies of this specification, etc.," line 4, following the word "charge' insert "from Business Service Centers,'.

PAGE 2

Paragraph 2.2, delete in its entirety and substitute.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

Delete the reference to "Official Classification Committee" and address and "American Trucking Association, Inc.' and address and substitute the following:

National Classification Board

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Association, Inc., Attention. Tariff Order Section, 1616 P Street, N. W., Washington, D. C., 20036.)

Uniform Classification Committee

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, 202 Union Station, Chicago, Illinois 60606.)

Paragraph 3.1.1.2, delete in its entirety and substitute:

3.1.1.2 Class 2. The links of class 2 mats shall be made of super-imposed layers of rubberized fabric and shall contain not less than three plies of fabric. As an alternate construction, white sidewall strips measuring approximately 3/8 inch in thickness and black sidewall strips measuring approximately 1/4 inch in thickness and 3/4 inches wide, with spacers, cut from 2 and 4-ply passenger tires may be used for the rubberized fabric links. The average weight for the strip mat shall not exceed 3-1/3 pounds per square foot. The links or strips shall be free of objectionable odor and shall contain no material that may stain, injure, or mar the appearance of the floor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:24Z
Check the source to verify that this is the current version before use.