MIL-C-22672B(AS)
Amendment-2
15 August 1966
Superseding
Amendment-1
15 April 1965

MILITARY SPECIFICATION

CODER-RECEIVER-TRANSMITTER KY-533A(*)/ASQ

This amendment forms a part of Military Specification MIL-C-22672B(WP) dated 21 October 1964 and has been approved by the Naval Air Systems Command, Department of the Navy.

By this amendment basic MIL-C-22672B(WP) is changed to MIL-C-22672B(AS) and throughout the specification Bureau of Naval Weapons shall be changed to Naval Air Systems Command

*Page 1, Specification Title: Delete "KY-533(*)/ASQ" and substitute "KY-533A/ASQ." Make this same change throughout the specification.

*Page 2, paragraph 2.1, under SPECIFICATIONS Military: Delete "MIL-E-4682" and "MIL-R-23094" and titles.

*Page 3, paragraph 2.1, under STANDARDS Military: Add

"MIL-STD-781 Reliability Tests, Exponential Distribution"

*Page 4, paragraph 3.1.2: Delete

*Page 4, paragraph 3.2.2.3: Delete "325 hours" and substitute "450 hours"

Page 9, paragraph 3.3.3.7.4(3): Delete

*Page 10, paragraph 3.3.3.9.1, last sentence: Delete and substitute

"Recovery time shall be measured from the leading edge of the last pulse of the first reply to the leading edge of the first pulse of the second reply at the 50% amplitude points of the pulses concerned."

*Page 10, paragraph 3.3.3.9.2: Delete "Modes 1, 2, 3/A, and C" and substitute

"Modes 1, 2, 3/A, C and Mode 4 sync patterns"

*Page 13, paragraph 3.3.4.8, last sentence: Delete "and 4 are" and substitute

"is"

FSC 5841

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:18Z
Check the source to verify that this is the current version before use.

*Page 19, paragraph 3.3.7.10.1(2)b: Delete "1500" and substitute

"3000"

*Page 22, paragraph 3.3.11.1, after "Amplitude": Delete "2 to 20 volts" and substitute

"±1.5 to 5.0 volts"

After "Undesired Signal Plus Quiescent d-c voltage": Delete "From +0.7 volt maximum to -0.7 volt minimum" and substitute "±0.5 volt maximum"

*Page 23, paragraph 3.3.11.2, after "Undesired Signal Plus Quiescent d-c Voltage" Delete "From +0.7 volt maximum to -0.7 volt minimum" and substitute

"±0.5 volt maximum"

*Page 24, paragraph 3.3.11.3, after "Amplitude": Delete "3 to 6.5V" and substitute

"3 to 5 volts"

After "Pulse Position of the first reply pulse": Delete "Between 200 and 260 usec" and substitute

"199 ±2 usec"

*Page 24, paragraph 3.3.11.4, last sentence: Delete and substitute

"If the Mode 4 trigger is followed within 10 usec by a disparity pulse (3.3.12.4), the interrogation shall not be counted for Mode 4 duty limiting purposes."

Pages 24 and 25, paragraphs 3.3.11.5, 3.3.11.5.1 and 3.3.11.5.2: Delete

*Page 25, paragraph 3.3.12.1: Delete "within 200 microseconds"

*Page 26, paragraph 3.3.12.3(2), second sentence: Delete "Condition No. 1 or No. 2"

Delete the third sentence

*Page 26, paragraph 3.3.12.4, after "Timing from fourth sync pulse": Delete and substitute

"2 to 200 usec"

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:18Z
Check the source to verify that this is the current version before use.

*Page 26, paragraph 3.3.13: Delete and substitute

"3.3.13 Reply Indication Signal Characteristics - A reply indication signal is used to indicate Mode 4 reply activity. When the equipment is supplying a 100 ma reply indication signal to an external load, the voltage drop measured from the +28 volt equipment power line to the reply indication output shall not exceed 4 volts under any combination of service conditions. The signal shall continue 2 to 5 seconds after the Mode 4 reply ceases."

*Page 28, paragraph 3.4.1.4.1(2): Delete and substitute

"(2) In the NORMAL position of the control, all voltages shall be applied, the modulator shall be enabled and the unit shall be capable of normal operation immediately, provided the time delay (3.3.6.4) has elapsed."

*Page 33, paragraphs 4.4.3 through 4.4.3.4: Delete and substitute

"4.4.3 Reliability Assurance Tests - Reliability Assurance Tests shall be conducted using MIL-STD-781. Tests as required by both the Qualification Phase and the Sampling Phase shall be conducted.

4.4.3.1 Qualification Phase - Prior to the acceptance of equipments under the contract or order, minimum of three (3) equipments shall be tested as outlined in MIL-STD-781, under the section entitled "Qualification Phase of Production Reliability Tests." The maximum number of equipments to be used shall be those listed in Table 5 of MIL-STD-781. For the Qualification Phase, Test Level E shall be used. The Accept-Reject Criteria for Test Plan IV shall be used.

4.4.3.2 Reliability Sampling Phase Tests - Samples of the equipment shall be tested as outlined in MIL-STD-781, under the section entitled "Sampling Phase of Product on Reliability Tests." For the Sampling Phase, Test Level E shall be used. The Accept-Reject Criteria for Test Plan IV shall be used to determine the length of the tests (until an accept or reject decision is reached).

4.4.3.2.1 Lot Size for Sampling Phase - The entire contract quantity (with the exception of those equipments used in the Qualification Phase) shall be evaluated as one lot. The test program shall start the first month after the Qualification Phase has been completed. Samples of each month's production shall be selected and placed on test in the same manner as though one month's production was a lot. The samples shall be tested until an accept or reject decision is reached. In the meantime, other equipments constructed shall be shipped. The test results shall be summarized monthly for the procuring activity. The procuring activity reserves the right to stop the acceptance of equipment at any time after one or more reject decisions have been reached, pending a review of the contractor's efforts to improve the equipment, the equipment parts, the equipment quality control etc., so that the entire contract quantity will show an accept decision.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:18Z
Check the source to verify that this is the current version before use.

Page 35, paragraph 4.4.3.6: Delete and substitute

"4.4.3.6 Determination of Compliance - Compliance shall be determined in accordance with Test Plan IV of MIL-STD-781."

An asterisk preceding a page number denotes a change to be made to the specification which did not appear in Amendment-1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:18Z
Check the source to verify that this is the current version before use.