INCH-POUND
MIL-R-22684/1B
w/Amendment 3
4 July 2020
SUPERSEDING
MIL-R-22684/1B
w/Amendment 2
27 May 2016

MILITARY SPECIFICATION

# RESISTOR, FIXED, FILM, INSULATED, STYLE RL07

This specification is inactive for design after 21 November 1968. Use MIL-PRF-39017/1.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-22684.

## 1. SCOPE

1.1 Scope. This specification covers the associated requirements for insulated, film, fixed resistors of 2-percent and 5-percent resistance tolerance. These resistors are capable of full-load operation at an ambient temperature of 70°C and have a resistance-temperature characteristic of ±200 parts per million per degree Celsius (ppm/°C). Designers are CAUTIONED on using these resistors in high power pulse applications (see 6.3).

1.2 Part or Identifying Number (PIN). Resistors covered by this specification are identified by a PIN which consists of the basic number of this specification and a coded dash number taken from table I. The PIN is in the following form:

| M22684/01 | - | 1001 |
|---|---|---|
| Performance specification number | | Coded dash number |

The coded dash number is derived in accordance with paragraph 6.2.2 of MIL-PRF-22684.

## 2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

Comments, suggestions, or questions on this document should be addressed to: DLA Land and Maritime, ATTN: VAT, Post Office Box 3990, Columbus, Ohio 43218-3990 or by email resistor@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil/

AMSC N/A FSC 5905

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:22Z
Check the source to verify that this is the current version before use.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATION

MIL-PRF-22684 - Resistor, Fixed, Film (Insulated), General Specification.


(Copies of these documents are available online at https://quicksearch.dla.mil).

2.3 Order of precedence. In the event of a conflict between the text of this document and the reference cited herein (except for related specification sheets), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General. The requirements for acquiring the product described herein shall consist of this document and MIL-PRF-22684.

3.2 Interface and physical dimensions. Resistors shall meet the interface and physical dimensions specified on figure 1, as applicable.




| Ltr | DIMENSIONS | | | |
|---|---|---|---|---|
| | INCHES | | MILLIMETERS | |
| | MIN | MAX | MIN | MAX |
| A | .205 | .281 | 5.56 | 7.14 |
| B | 1.375 | 1.625 | 34.92 | 41.28 |
| C | .019 | .027 | 0.48 | 0.68 |
| D | .082 | .098 | 2.08 | 2.49 |

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. The end of the body shall be that point at which the diameter equals the nearest drill size larger than 250 percent of the nominal lead diameter. The leads shall be solderable to within .125 inch (3.18 mm) of the resistor body.

FIGURE 1. Configuration and dimensions.



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:22Z
Check the source to verify that this is the current version before use.

3.3 Power rating. The power rating shall be 1/4 watt based on full load operation at an ambient temperature of 70°C.

3.4 Voltage rating. The maximum continuous working voltage shall not exceed 250 volts.

3.5 Resistance values and resistance tolerances. The minimum and maximum standard resistance values and associated resistance tolerances shall be as listed in table I.

Table I. PIN designation. (M22684/01-)

| Dash No. | Type designation | Resistance tolerance (percent) | Nominal total resistance value (in Ohms) |
|---|---|---|---|
| 0001 | RL07S510G | 2 | 51 |
| 0002 | RL07S510J | 5 | |
| 0003 | RL07S560G | 2 | 56 |
| 0004 | RL07S560J | 5 | |
| 0005 | RL07S620G | 2 | 62 |
| 0006 | RL07S620J | 5 | |
| 0007 | RL07S680G | 2 | 68 |
| 0008 | RL07S680J | 5 | |
| 0009 | RL07S750G | 2 | 75 |
| 0010 | RL07S750J | 5 | |
| 0011 | RL07S820G | 2 | 82 |
| 0012 | RL07S820J | 5 | |
| 0013 | RL07S910G | 2 | 91 |
| 0014 | RL07S910J | 5 | |
| 0015 | RL07S101G | 2 | 100 |
| 0016 | RL07S101J | 5 | |
| 0017 | RL07S111G | 2 | 110 |
| 0018 | RL07S111J | 5 | |
| 0019 | RL07S121G | 2 | 120 |
| 0020 | RL07S121J | 5 | |
| 0021 | RL07S131G | 2 | 130 |
| 0022 | RL07S131J | 5 | |
| 0023 | RL07S151G | 2 | 150 |
| 0024 | RL07S151J | 5 | |
| 0025 | RL07S161G | 2 | 160 |
| 0026 | RL07S161J | 5 | |
| 0027 | RL07S181G | 2 | 180 |
| 0028 | RL07S181J | 5 | |
| 0029 | RL07S201G | 2 | 200 |
| 0030 | RL07S201J | 5 | |
| 0031 | RL07S221G | 2 | 220 |
| 0032 | RL07S221J | 5 | |
| 0033 | RL07S241G | 2 | 240 |
| 0034 | RL07S241J | 5 | |
| 0035 | RL07S271G | 2 | 270 |
| 0036 | RL07S271J | 5 | |
| 0037 | RL07S301G | 2 | 300 |
| 0038 | RL07S301J | 5 | |
| 0039 | RL07S331G | 2 | 330 |
| 0040 | RL07S331J | 5 | |
| 0041 | RL07S361G | 2 | 360 |
| 0042 | RL07S361J | 5 | |
| 0043 | RL07S391G | 2 | 390 |
| 0044 | RL07S391J | 5 | |
| 0045 | RL07S431G | 2 | 430 |
| 0046 | RL07S431J | 5 | |
| 0047 | RL07S471G | 2 | 470 |
| 0048 | RL07S471J | 5 | |
| 0049 | RL07S511G | 2 | 510 |
| 0050 | RL07S511J | 5 | |
| 0051 | RL07S561G | 2 | 560 |
| 0052 | RL07S561J | 5 | |
| 0053 | RL07S621G | 2 | 620 |
| 0054 | RL07S621J | 5 | |
| 0055 | RL07S681G | 2 | 680 |
| 0056 | RL07S681J | 5 | |
| 0057 | RL07S751G | 2 | 750 |
| 0058 | RL07S751J | 5 | |
| 0059 | RL07S821G | 2 | 820 |
| 0060 | RL07S821J | 5 | |
| 0061 | RL07S911G | 2 | 910 |
| 0062 | RL07S911J | 5 | |
| 0063 | RL07S102G | 2 | 1,000 |
| 0064 | RL07S102J | 5 | |
| 0065 | RL07S112G | 2 | 1,100 |
| 0066 | RL07S112J | 5 | |
| 0067 | RL07S122G | 2 | 1,200 |
| 0068 | RL07S122J | 5 | |
| 0069 | RL07S132G | 2 | 1,300 |
| 0070 | RL07S132J | 5 | |
| 0071 | RL07S152G | 2 | 1,500 |
| 0072 | RL07S152J | 5 | |
| 0073 | RL07S162G | 2 | 1,600 |
| 0074 | RL07S162J | 5 | |
| 0075 | RL07S182G | 2 | 1,800 |
| 0076 | RL07S182J | 5 | |
| 0077 | RL07S202G | 2 | 2,000 |
| 0078 | RL07S202J | 5 | |
| 0079 | RL07S222G | 2 | 2,200 |
| 0080 | RL07S222J | 5 | |
| 0081 | RL07S242G | 2 | 2,400 |
| 0082 | RL07S242J | 5 | |
| 0083 | RL07S272G | 2 | 2,700 |
| 0084 | RL07S272J | 5 | |
| 0085 | RL07S302G | 2 | 3,000 |
| 0086 | RL07S302J | 5 | |
| 0087 | RL07S332G | 2 | 3,300 |
| 0088 | RL07S332J | 5 | |

Table I. PIN designation (M22684/01-) - continued.



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:22Z
Check the source to verify that this is the current version before use.

| Dash No. | Type designation | Resistance tolerance (percent) | Nominal total resistance value (in Ohms) |
|---|---|---|---|
| 0089 | RL07S362G | 2 | 3,600 |
| 0090 | RL07S362J | 5 | |
| 0091 | RL07S392G | 2 | 3,900 |
| 0092 | RL07S392J | 5 | |
| 0093 | RL07S432G | 2 | 4,300 |
| 0094 | RL07S432J | 5 | |
| 0095 | RL07S472G | 2 | 4,700 |
| 0096 | RL07S472J | 5 | |
| 0097 | RL07S512G | 2 | 5,100 |
| 0098 | RL07S512J | 5 | |
| 0099 | RL07S562G | 2 | 5,600 |
| 0100 | RL07S562J | 5 | |
| 0101 | RL07S622G | 2 | 6,200 |
| 0102 | RL07S622J | 5 | |
| 0103 | RL07S682G | 2 | 6,800 |
| 0104 | RL07S682J | 5 | |
| 0105 | RL07S752G | 2 | 7,500 |
| 0106 | RL07S752J | 5 | |
| 0107 | RL07S822G | 2 | 8,200 |
| 0108 | RL07S822J | 5 | |
| 0109 | RL07S912G | 2 | 9,100 |
| 0110 | RL07S912J | 5 | |
| 0111 | RL07S103G | 2 | 10,000 |
| 0112 | RL07S103J | 5 | |
| 0113 | RL07S113G | 2 | 11,000 |
| 0114 | RL07S113J | 5 | |
| 0115 | RL07S123G | 2 | 12,000 |
| 0116 | RL07S123J | 5 | |
| 0117 | RL07S133G | 2 | 13,000 |
| 0118 | RL07S133J | 5 | |
| 0119 | RL07S153G | 2 | 15,000 |
| 0120 | RL07S153J | 5 | |
| 0121 | RL07S163G | 2 | 16,000 |
| 0122 | RL07S163J | 5 | |
| 0123 | RL07S183G | 2 | 18,000 |
| 0124 | RL07S183J | 5 | |
| 0125 | RL07S203G | 2 | 20,000 |
| 0126 | RL07S203J | 5 | |
| 0127 | RL07S223G | 2 | 22,000 |
| 0128 | RL07S223J | 5 | |

| Dash No. | Type designation | Resistance tolerance (percent) | Nominal total resistance value (in Ohms) |
|---|---|---|---|
| 0129 | RL07S243G | 2 | 24,000 |
| 0130 | RL07S243J | 5 | |
| 0131 | RL07S273G | 2 | 27,000 |
| 0132 | RL07S273J | 5 | |
| 0133 | RL07S303G | 2 | 30,000 |
| 0134 | RL07S303J | 5 | |
| 0135 | RL07S333G | 2 | 33,000 |
| 0136 | RL07S333J | 5 | |
| 0137 | RL07S363G | 2 | 36,000 |
| 0138 | RL07S363J | 5 | |
| 0139 | RL07S393G | 2 | 39,000 |
| 0140 | RL07S393J | 5 | |
| 0141 | RL07S433G | 2 | 43,000 |
| 0142 | RL07S433J | 5 | |
| 0143 | RL07S473G | 2 | 47,000 |
| 0144 | RL07S473J | 5 | |
| 0145 | RL07S513G | 2 | 51,000 |
| 0146 | RL07S513J | 5 | |
| 0147 | RL07S563G | 2 | 56,000 |
| 0148 | RL07S563J | 5 | |
| 0149 | RL07S623G | 2 | 62,000 |
| 0150 | RL07S623J | 5 | |
| 0151 | RL07S683G | 2 | 68,000 |
| 0152 | RL07S683J | 5 | |
| 0153 | RL07S753G | 2 | 75,000 |
| 0154 | RL07S753J | 5 | |
| 0155 | RL07S823G | 2 | 82,000 |
| 0156 | RL07S823J | 5 | |
| 0157 | RL07S913G | 2 | 91,000 |
| 0158 | RL07S913J | 5 | |
| 0159 | RL07S104G | 2 | 100,000 |
| 0160 | RL07S104J | 5 | |
| 0161 | RL07S114G | 2 | 110,000 |
| 0162 | RL07S114J | 5 | |
| 0163 | RL07S124G | 2 | 120,000 |
| 0164 | RL07S124J | 5 | |
| 0165 | RL07S134G | 2 | 130,000 |
| 0166 | RL07S134J | 5 | |
| 0167 | RL07S154G | 2 | 150,000 |
| 0168 | RL07S154J | 5 | |

3.6 Terminal type. The terminal type available shall be solderable in accordance with MIL-PRF-22684.

3.7 Dielectric withstanding voltage. Resistors shall be tested as specified in MIL-PRF-22684. The magnitude of test voltage shall be as follows:

| | | |
|---|---|---|
| Atmospheric pressure | - | 500 volts rms |
| Barometric pressure | - | 325 volts rms |

3.8 Insulation resistance. Resistors shall be tested as specified in MIL-PRF-22684 except the insulation resistance shall be not less than 100 megohms.



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:22Z
Check the source to verify that this is the current version before use.

3.9 Moisture resistance. Resistors shall be tested as specified in MIL-PRF-22684 except the change in resistance shall not exceed 1.5 percent.

3.10 Life. Resistors shall be tested as specified in MIL-PRF-22684 except the change in resistance shall not exceed 2.0 percent.

4. VERIFICATION

4.1 Sampling and inspection. Sampling and inspection procedures shall be in accordance with Group A inspection and Group B inspection of MIL-PRF-22684 and as specified herein.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Service or Defense Agency, or within the military services system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Notes The notes specified in MIL-PRF-22684 are applicable to this specification.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, date of this specification, and complete PIN (see 1.2).
b. If not otherwise specified (see 2.1), the versions of the individual documents referenced will be those in effect on the date of release of the solicitation.
c. Packaging requirements.

6.3 Pulse applications. Designers are CAUTIONED on using these resistors in high power pulse applications. Since they have not been qualified nor tested for such applications, damage and premature failure are possible. These resistors only see a one-time pulse (Short-time overload) as part of the group B inspection of this specification. Designers MAY CONSIDER using DLA Land and Maritime drawings 03004 for high power pulse applications.

6.4 Amendment notification. The margins of this specification are marked with vertical lines to indicate modification generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship.



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:22Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Review activities:
Army - AR, MI
Air Force - 19

Preparing activity:
DLA - CC

(Project 5905-2020-018)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:22Z
Check the source to verify that this is the current version before use.