MIL-O-23560/4A(WP)
Amendment 1
30 December 1965

MILITARY SPECIFICATION

OSCILLOGRAPH, TYPE IV

(For Torpedo Mark 37 Mod 1)

This amendment forms a part of Military Specification MIL-O-23560/4A(Wep) of 25 August 1964 and has been approved by the Bureau of Naval Weapons, Department of the Navy .

Page 5: Replace Table II with new Table II, attached.

FSC 1355

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:13Z
Check the source to verify that this is the current version before use.

2

Channel Number	Pin Connections	Natural Freq (cps)	Voltage (rms) Millivolts	Frequency Range (cps)	FREQUENCY RESPONSE FLAT WITHIN * (Percent)		
					At 0°F	At 70-80°F	At 130°F
1	1 2	500	1500	10 - 300	+7.5, -15	+7.5, -10	+15, -7.5
2	3 4	100	16 **	10 - 60	" "	" "	" "
3	5 6	500	1500	10 - 300	" "	" "	" "
4	7 8	"	"	"	" "	" "	" "
5	9 10	"	"	"	" "	" "	" "
6	11 12	"	"	"	" "	" "	" "
7	13 14	"	"	"	" "	" "	" "
8	15 16	"	"	"	" "	" "	" "
9	17 18	100	18.5	10 - 60	" "	" "	" "
10	19 20	500	1500	10 - 300	" "	" "	" "
11	21 22	"	"	"	" "	" "	" "
12	23 24	"	"	"	" "	" "	" "
13	25 26	"	"	"	" "	" "	" "
14	-- --	--	Dummy	— —	-- --	-- --	-- --

*Relative to response at 10 cps
**Driving source impedance of 360 ohms per paragraph 3.2.4.

Table II

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T17:13Z
Check the source to verify that this is the current version before use.