**INCH-POUND**

**MIL-F-50253A(AR)**
**AMENDMENT 4**
**01 October 1996**
**SUPERSEDING**
**AMENDMENT 3**
**26 December 1992**

# MILITARY SPECIFICATION

## FUZES, ROCKET, M423, M427 and M433 LOADING, ASSEMBLING AND PACKING

**This amendment forms a part of Military Specification MIL-F-50253A(AR), dated 10 November 1978, and is approved for use by the US Army Armament Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.**

**PAGE 2**

**2.1: Delete**

**"9260701 - Fuze, Rocket, M433 with Booster and Booster Lead" and substitute**
**"9260701 - Fuze, Rocket, M433".**

**Add**
**"9329860-3 - M433/M439 Fuze Continuity Test Set".**

**PAGE 3**

**3.7: Add "Note: This electrical characteristic is an electrical interface characteristic and shall not be altered or changed without an approved Government DEV/ WAV or ECP.".**

**PAGE 4**

**4.3.1: Delete "Fuze, Rocket, M433 with Booster and Booster Lead" and substitute "Fuze, Rocket, M433".**

**PAGE 5**

**Table I: Delete "with Booster and Booster Lead".**


DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://assist.dla.mil - Downloaded: 2026-02-27T07:37
Check the source to verify that this is the current version before use.

PAGE 6

Table I, In 2 places: Delete “with Booster and Booster Lead”.

PAGE 7

4.4.1: Delete

a. One metal parts lot from one manufacturer” and substitute

“Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, each inspection lot of boostered fuzes shall contain:

a. Fuzes bearing the same metal parts lot interfix number from one metal parts manufacturer”.

PAGE 9

4.4.2.2, Major 105: Delete “.40%” and substitute “100%”.

PAGE 10

4.5.2: Delete in its entirety and substitute

“Umbilical continuity test. Each fuze umbilical shall be connected to an umbilical test set (9329860-3). Each umbilical must meet the acceptance requirements. Any umbilical that does not meet the acceptance requirements shall be classed defective and removed from the lot.”

PAGE 11

4.5.3.2, line 8: Delete “functional” and substitute “functioned”.

4.5.3.3, Delete in its entirety and substitute

“M433 Fuze. Live boosters will be assembled into a government approved simulated M433 fuze, an M423 fuze assembly, or an M427 fuze assembly. When a simulated M433 fuze is used, the test fixture must simulate an M433 explosive train in the armed condition. Functional (electrical) energy of not less than 750 ergs shall be applied to the detonator electrical contacts in the simulated test fixture. High order detonation shall be determined by a 0.25 inch minimum dent in a cylindrical witness block (1.5 inch minimum height by 2.0 inch minimum diameter of 2011-T3 aluminum). When M423/427 fuze assemblies are used, the test procedure of 4.5.3.2 applies.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:18Z
Check the source to verify that this is the current version before use.

**WARNING: This test is dangerous and must be performed behind a suitable barricade."**

**PAGE 12**

**4.5.4.2, Delete in its entirety and substitute**

**"Ballistic functional criteria. The complete fuze with warhead and rocket motor shall be fired from a 2.75 inch rocket launcher to impact the natural ground at approximately 5,500 meters from the launcher. The launcher shall be a standard inventory launcher conforming to all launcher requirements. The launcher assembly shall be so fabricated and mounted that the azimuth and quadrant elevation (QE) will remain fixed during firing. Rounds containing M433 fuzes shall be set to the superquick mode with a Government approved setter design that represents the helicopter setting system. The warhead shall function high order upon ground impact. The warhead shall not air burst (function in air during flight). One or more occurrences of air burst shall cause the fuze-warhead combination lot to be rejected unless air burst(s) can be proven to be caused by abnormal rocket motor behaviors."**

**PAGE 13**

**6.3: Delete "DRDAR-QAR-I" and substitute "AMSTA-AR-QAC-S".**

**The margins of this document are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous amendment.**

**Custodian:**
**Army-AR**

**Preparing activity:**
**Army-AR**

**(Project 1340-A985)**



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:18Z
Check the source to verify that this is the current version before use.