INCH POUND

MIL-DTL-83413/7E
w/AMENDMENT 1
17 June 2013
SUPERSEDING
MIL-DTL-83413/7E
12 December 2012

DETAIL SPECIFICATION SHEET

CONNECTORS AND ASSEMBLIES, ELECTRICAL, AIRCRAFT
GROUNDING: GROUNDING CLAMP CONNECTOR FOR TYPES I AND III
GROUNDING ASSEMBLIES, CLIP, ELECTRICAL

This specification is approved for used by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-83413.




FIGURE 1. Grounding clamp, for types I and III grounding assemblies.

AMSC N/A

FSC 5999

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:02Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm	Inches	mm
.003	0.08	.113	2.87	.75	19.1
.004	0.10	.125	3.18	.84	21.3
.010	0.25	.130	3.30	.88	22.4
.031	0.79	.130	3.30	1.25	31.4
.062	1.57	.203	5.16	1.50	38.1
.078	1.98	.205	6.35	2.80	76.1
.080	2.03	.380	9.70	3.20	81.3
.090	2.29	.500	12.70	4.13	104.9

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Surface toughness: If cast, smooth cast finish 125 or 250 all over, except machine surface 63.
4. Remove all burrs and sharp edges .010 (0.25 mm) to .020 (0.51 mm) radius.
5. Unless otherwise specified, tolerance is ±.03 (0.8 mm) on decimals and ± 1° on angles.

FIGURE 1. Grounding clamp, for types I and III grounding assemblies - Continued.




FIGURE 2. Grounding clamp, for types I and III grounding assemblies with integrated jaw.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:02Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm	Inches	mm
.003	0.08	.113	2.87	.75	19.1
.004	0.10	.125	3.18	.84	21.3
.010	0.25	.130	3.30	.88	22.4
.031	0.79	.130	3.30	1.25	31.4
.062	1.57	.203	5.16	1.50	38.1
.078	1.98	.205	6.35	2.80	76.1
.080	2.03	.380	9.70	3.20	81.3
.090	2.29	.500	12.70	4.13	104.9

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Surface toughness: If cast, smooth cast finish 125 or 250 all over, except machine surface 63.
4. Remove all burrs and sharp edges .010 (0.25 mm) to .020 (0.51 mm) radius.
5. Unless otherwise specified, tolerance is ±.03 (0.8 mm) on decimals and ± 1° on angles.

FIGURE 2. Grounding clamp, for types I and III grounding assemblies with integrated jaw - Continued.

REQUIREMENTS:

Material-handle: Stainless steel in accordance with SAE-AMS-5355, grade 17-4PH on figure 2 configuration only, without passivation or aluminum alloy in accordance with ASTM-A385, ASTM-B26/B26M, ASTM-B108/B108M and SAE-J452, SAE-J453, SAE-AMS-4290, SAE-AMS-4291, Alloy 360, A380 or 384.

Material-spring: .125 diameter music wire in accordance with ASTM-A228/A228M, or equal. Heat treatment shall be as required to meet requirements. The spring shall be stress relieved, zinc/clear plated in accordance with ASTM-B633, or Nickel plated in accordance with ASTM-B733.

Material set screw: AIA/NASM51021, passivated in accordance with SAE-AMS 2700

Clamp connector resistance: Shall not exceed 500 milliohms.

Salt spray: 500 hours in accordance with test procedure EIA/ECA-364-26.

Part or Identifying Number (PIN): M83413/7-1: standard option without integrated jaw
M83413/7-1A: option with integrated jaw, see figure 1.

PIN M83413/7-1A supersedes PIN M83413/7-1.

Alternate jaw material: MPIF FX - 1008-110HT in accordance with Metal Powder Industries Federation, 105 College Road East, Princeton, New Jersey 08540.

QUALIFICATION:

The activity responsible for qualification and the Qualification Products List (QPL) for this specification sheet is the DLA Land and Maritime, DSCC-VQ, 3990 East Broad Street, Columbus, Ohio 43218-3990.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:02Z
Check the source to verify that this is the current version before use.

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents. In addition to MIL-DTL-83413, this document references the following:

ASTM-A228/A228M	AIA/NASM171401
ASTM-A385	AIA/NASM51021
ASTM-B26/B26M	SAE-J452
ASTM-B108/B108M	SAE-J453
ASTM-B633	SAE-AMS 2700
ASTM-B733	SAE-AMS-4290
EIA/ECA-364-26	SAE-AMS-4291
MPIF FX-1008-110HT	SAE-AMS-5355

CONCLUDING MATERIAL

Custodians:
Army - AV
Navy - AS
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5999-2013-005)

Review activities:
Army - AR, CR, CR4, MI
Navy - MC
Air Force - 02, 13, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:02Z
Check the source to verify that this is the current version before use.