INCH POUND

MIL-DTL-83413/7E
w/AMENDMENT 3
05 February 2015
SUPERSEDING
MIL-DTL-83413/7E
w/AMENDMENT 2
18 April 2014

DETAIL SPECIFICATION SHEET

CONNECTORS AND ASSEMBLIES, ELECTRICAL, AIRCRAFT GROUNDING: GROUNDING CLAMP CONNECTOR FOR TYPES I AND III GROUNDING ASSEMBLIES, ALUMINUM CLIP, ELECTRICAL

This specification is approved for used by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-83413.




FIGURE 1. Grounding clamp, for types I and III grounding assemblies.

AMSC N/A

FSC 5999

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:01Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm	Inches	mm
.003	0.08	.113	2.87	.75	19.1
.004	0.10	.125	3.18	.84	21.3
.010	0.25	.130	3.30	.88	22.4
.031	0.79	.130	3.30	1.25	31.4
.062	1.57	.203	5.16	1.50	38.1
.078	1.98	.205	6.35	2.80	76.1
.080	2.03	.380	9.70	3.20	81.3
.090	2.29	.500	12.70	4.13	104.9

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Surface toughness: If cast, smooth cast finish 125 or 250 all over, except machine surface 63.
4. Remove all burrs and sharp edges .010 (0.25 mm) to .020 (0.51 mm) radius.
5. Unless otherwise specified, tolerance is ±.03 (0.8 mm) on decimals and ± 1° on angles.

FIGURE 1. Grounding clamp, for types I and III grounding assemblies - Continued.

REQUIREMENTS:

Material-handle: The handle material shall be of aluminum alloy.

Material-spring: .125 diameter music wire in accordance with ASTM-A228/A228M, or equal. Heat treatment shall be as required to meet requirements. The spring shall be stress relieved, zinc/clear plated in accordance with ASTM-B633, or Nickel plated in accordance with ASTM-B733.

Material set screw: AIA/NASM51021, passivated in accordance with SAE-AMS 2700.

Clamp connector resistance: Shall not exceed 500 milliohms.

Salt spray: 96 hours in accordance with test procedure EIA/ECA-364-26 test condition A.

Part or Identifying Number (PIN): M83413/7-1.

Alternate jaw material: MPIF FX - 1008-110HT in accordance with Metal Powder Industries Federation, 105 College Road East, Princeton, New Jersey 08540.

QUALIFICATION:

Qualification is not required. In addition to the stated requirements above, first article testing shall consist of dimensional verification and resistance testing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:01Z
Check the source to verify that this is the current version before use.

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents. In addition to MIL-DTL-83413, this document references the following:

AIA/NASNASM171401
AIA/NASM51021
ASTM-A228/A228M
ASTM-B633
ASTM-B733
EIA/ECA-364-26
MPIF FX-1008-110HT
SAE-AMS 2700

CONCLUDING MATERIAL

Custodians:
Army - AV
Navy - AS
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5999-2015-002)

Review activities:
Army - AR, CR, CR4, MI
Navy - MC
Air Force - 02, 13, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:01Z
Check the source to verify that this is the current version before use.