MILITARY SPECIFICATION SHEET

RELAYS, REED (MERCURY WETTED), ALL WELDED, 0 TO 7.5 VOLT AMPERES

This amendment forms a part of Military Specification Sheet MIL-R-83407/3B(USAF), dated 28 March 1983, and is approved for use by the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 5

Under Contact data, add: "Contact bounce: Contact bounce shall be measured on each contact set using an oscilloscope or other acceptable means approved by the qualifying activity. The trace shall show contact switching at operate and release and appropriate timing markers. Rated voltage shall be applied to the coil. Contact bounce shall be measured at a contact load of 100 mA at 6 V dc. A contact bounce shall be considered any occurrence equal to or greater than 90 percent of the open circuit voltage with a pulse width of 10 microseconds or greater. The circuit shown on figure 1 of military specification MIL-R-83407(USAF), or equivalent, shall be used. Contact bounce shall not exceed 2.5 milliseconds (operate time not included)."

PAGE 7

Physical data, add new entry:

"Marking: Applicable except for -001, -002, -003, -004, -011, -012, -013, and -014. These parts shall be marked as follows:

Top of relay: Schematic (circuit) diagram, position arrow, and dash number.

Side of relay: Complete military part number, vendor FSCM, date code, and rated coil voltage."

Custodians:
Air Force - 85

Review activities:
Air Force - 99
DLA - ES

Agent:
DLA - ES

Preparing activity:
Air Force - 85

(Project 5945-F600)

FSC 5945

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:00Z
Check the source to verify that this is the current version before use.