JAN-P-106A

AMENDMENT—2
5 JUNE 1953

SUPERSEDING
Amendment—1
26 January 1953

JOINT ARMY-NAVY SPECIFICATION

PACKAGING AND PACKING FOR OVERSEAS SHIPMENT—BOXES; WOOD, NAILED

(For weight of contents not in excess of 1,000 pounds)

This amendment forms a part of Joint Army-Navy Specification JAN-P-106A, 1 August 1946, and has been approved by the Departments of the Army, the Navy, and the Air Force.

Page 1, title: Delete "Packaging and Packing for Overseas Shipment—Boxes; Wood, Nailed" and substitute:

"BOXES; WOOD, NAILED (OVERSEAS TYPE)"

Page 1, section A: Delete and substitute:

"A. APPLICABLE SPECIFICATIONS, STANDARDS, DRAWINGS, AND PUBLICATIONS.

"A-1. The following specifications and standards, of the issue in effect on date of invitation for bids, form a part of this specification:

"SPECIFICATIONS:

"FEDERAL

"FF-N-101—Nails; Spikes; Staples; and Tacks.

"FF-S-111—Screws; Wood.

"STANDARDS:

"MILITARY

"MIL-STD-105—Sampling Procedures and Tables for Inspection by Attributes.

"MIL-STD-129—Marking of Shipments.

"(Copies of specifications, standards and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.)"

Page 2, paragraph B-1, last sentence: Delete and substitute: "Style 1 and 5 boxes shall be furnished only when specified (see par. 2 of app.)."

Page 2, paragraph C-1a (1)—Under group I, add the following species in proper alphabetical order: "Alder, red; Fir, California red; Fir, grand; Fir, silver." Under group III, change "ash, pumpkin" to "Ash, Cabinet texture." Add between "Blackgum" and "Elm, White" the word "Cherry." Change "Elm, White" to "Elm, soft." Under

Source: https://assist.dla.mil -- Downlo
Check the source to verify that this is th

group IV change "Ash white" to "Ash, white, tough textured." Insert "Locust" between "Hickory" and "Maple, hard."

Page 2, paragraph C–1a (2): Delete and substitute:

"Lumber shall be seasoned to a moisture content not to exceed 18 percent, nor less than 7 percent of its oven-dry weight at time of delivery. The surface which will form the outside face of the box shall be sufficiently smooth to permit legible marking, stenciling, or printing. Pieces shall be cut true to length. Box components shall be free from all defects that materially weaken them, expose the contents of the box to damage, or interfere with the prescribed fabrication or nailing."

Page 3, Add: "C–1a (2) a—No knot, knot cluster, or series of knots measured across the width of the piece, within a length equal to the width of the piece shall have a diameter or a sum of diameters greater than one-third the width of the piece. No knot or portion of knot shall exceed 4 inches, measured across the width of the piece. Assemblies or box parts made up of pieces as described in paragraphs D–2b (2), D–2b (3), D–2b (4) shall be regarded as single pieces or solid boards insofar as the knot size specification is concerned."

Page 3, paragraph C–1c, table I: Delete and substitute:

Table I.—Size of corrugated fasteners

Thickness of box part	Size of corrugated fasteners
Inches	*Inch*
13/32 to 27/64, incl	1/4 x 1
7/16 to 31/64, incl	5/16 x 1
1/2 to 39/64, incl	3/8 x 1
5/8 to 51/64, incl	1/2 x 1
13/16 to 55/64, incl	5/8 x 1
7/8 and up	3/4 x 1

Page 4, paragraph D–2: Delete and substitute:

"D–2—*Thickness and width of pieces making up box parts.*"

Page 4—Paragraphs D–2a, D–2b, D–2b (1) and D–2b (2): Delete and substitute:

"D–2a. *Thickness.*—The minimum thickness of the ends, sides, top, and bottom, and the minimum thickness and width of cleats, shall be determined from tables II, III, and IV. Occasional variations in thickness due to mismanufacture will be permitted in not more than ten percent of the pieces, but no portion of any piece shall be less than seven-eighths of the required thickness. If pieces three-eighths inch or more in thickness are surfaced on both sides (to protect the contents), the thickness may be one-

Source: https://assist.dla.mil -- Down
Check the source to verify that this is t

thirty-second inch less than the thickness as determined from tables II, III, and IV.

"D–2b. *Widths.*—The number of pieces in any side, top, bottom, or end shall be chosen so that no piece shall be less than 2½ inches in width. Single unjointed pieces 2½ inches or more in width, which are butt jointed are acceptable in side, top, bottom, and end construction of styles 2, 2½, 3, 4, and 5 boxes. One piece is considered to be either a single unjointed piece or two or more built-up pieces when fabricated and used as defined in paragraphs D–2b (2), D–2b (3), and D–2b (4). Each cleat or batten shall be a single unjointed piece.

"D–2b (1). The number of pieces in any part (i. e., side, top, bottom, or end) shall not exceed the number given in table 1–A.

Table I–A.—Number of pieces in any part

Width of box part		Maximum number of pieces
Exceeding	Not exceeding	
Inches	*Inches*	
	4	1
4	7	2
7	10	3
10		(See note)

Note.—One piece for each 3 inches of width. No piece shall be less than 2½ inches in width.

"D–2b (2)—Two or more pieces that are Linderman-jointed and glued shall be considered as one-piece. The glue used in Linderman-jointed pieces shall be synthetic resin or protein glues. No toxic treatment of glue shall be required for synthetic resin glues up to 100 pounds of filler for 100 pounds dry weight of resin glue base. If the extension of synthetic resin glues exceeds 100 pounds of filler for each 100 pounds dry weight of resin glue base, there shall be added in the preparation of the glue not less than 5 pounds of highly chlorinated phenols or their sodium salts for each 100 pounds dry weight of filler in the glue mixture. When protein glues are used, there shall be added in the preparation of the glue not less than 5 pounds of highly chlorinated phenols or their sodium salts for each 100 pounds dry weight of glue base.

"D–2b (3)—Two or more pieces three-eighths inch or more in thickness and not less than 1½ inches wide at either end, which

Source: https://assist.dla.m
Check the source to verify tha

are butt jointed and which are fastened with two or more corrugated fasteners in accordance with paragraph D–2b (5) shall be considered as one piece when used for the sides, tops and bottoms of styles 2, 2½, 3, 4, and 5 boxes.

"D–2b (4)—Two or more pieces three-eighths inch or more in thickness and not less than 1½ inches wide at either end, which are tongued and grooved and which are fastened with two or more corrugated fasteners in accordance with paragraph D–2b (5) shall be considered as one piece.

"D–2b (5) *Spacing of corrugated fasteners.*—Spacing between fasteners and adjacent fasteners or edge of assembly shall not exceed 8 inches. If three or more corrugated fasteners are required in a joint, they shall be driven alternately from opposite sides of the part, unless the joint is tongued and grooved and glued, in which case fasteners may be driven from one side. Sizes of fasteners required are shown in table I."

Page 6, table III, bottom of second column: Delete "(See table III)" and substitute "(See table IV)."

Page 12, paragraph F–1 *Sampling.*—Add the following: "Sampling shall be in accordance with Standard MIL–STD–105."

Page 13, paragraph G–2: Delete and substitute:

"G–2 *Marking.*—In addition to any special marking required by the contract or order, shipments shall be marked in accordance with Standard MIL–STD–129."

Page 16, paragraphs H–6, H–7 and H–8: Delete.

Custodian:
Army—Quartermaster Corps
Navy—Bureau of Supplies and Accounts
Air Force
Other interest:
Army—CEMOSigT
Navy—AMdOrShT.

Source: https://assist.dla.mil -- Do
Check the source to verify that this