MILITARY SPECIFICATION

RESISTORS, FIXED, FILM, PRECISION, ESTABLISHED RELIABILITY, STYLE RFP04

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the detail requirements for established reliability, precision, film, fixed resistors. Resistors are available within the full range of reactance, tolerance, and failure rates.

2. APPLICABLE DOCUMENTS

2.1 Government specifications and standards. Unless otherwise specified, the following specifications, standards, and handbooks, of the issue listed in that issue of the Department of Defense Index of Specifications and Standards specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATION

MILITARY

MIL-R-122 - Resistors, Fixed, Precision, Established Reliability, General Specification For.

(Copies of specifications, standards, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Requirements. Requirements shall be in accordance with MIL-R-122, and as specified herein.

3.2 Design and construction. Resistors shall be of the design, construction, and physical dimensions specified on figure 1.

3.2.1 Temperature characteristic. Resistors are available in characteristics D, E, and F.

3.3 Power rating. The power rating shall be .3 watt at 85°C (see 6.2). The applicable power rating curve is curve C.

3.4 Voltage rating. The continuous working voltage shall not exceed 300 volts.


3.5 Resistance. Minimum and maximum resistance values shall be as follows:

a. Minimum resistance - 10 ohms.
b. Maximum resistance - 0.2 megohm.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to Naval Electronic Systems Command, ATTN: ELEX 8111, Department of the Navy, Washington, D.C. 20363 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at end of this document or by letter.

FSC 5905

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T05:04Z
Check the source to verify that this is the current version before use.



INCHES	MM	INCHES	MM
.002	0.05	.105	2.67
.010	0.25	.125	3.18
.015	0.38	.150	3.81
.020	0.51	.302	7.67
.025	0.64	.325	8.26
.030	0.76	.500	12.70
.0625	1.588	1.375	34.93
.075	1.91		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. The lead measurements shall be made at the point of emergence from the body.
4. Style and placement of the standoffs are optional.
5. Centerline of terminal shall coincide with the centerline of the body within ±.010 inch.
6. Resistance measuring point shall be .5 ±.125 inch for resistance values of 10Ω or more and .0625 ±.025 inch for resistance values less than 10Ω.

FIGURE 1. Fixed resistors, precision.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T05:04Z
Check the source to verify that this is the current version before use.

3.6 Weight. The maximum weight shall not exceed .00221 pound (1 gram).

3.7 Overload. Apply 6.25 times rated power to the resistor for 5 seconds. When tested as specified, the applied voltage shall not exceed 450 volts.

3.8 Dielectric withstanding voltage. The applicable test voltages are as follows:

a. Atmospheric pressure - 300 volts.
b. Barometric pressure (reduced) - 200 volts.

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection procedures shall be in accordance with MIL-R-122.

5. PACKAGING

5.1 Packaging. Packaging requirements shall be in accordance with MIL-R-122.

6. NOTES

6.1 Notes. The notes specified in MIL-R-122 are applicable to this specification.

6.2 Power rating at 25°C. The power rating at 25°C for 2,000 hours of life test has been established at .6 watt, 300 volts, maximum voltage. It should be noted that the failure rate level is established at the single condition of 85°C, .3 watt and 10,000 hour life test duration.

6.3 Changes from previous issue. The margin of this specification is marked with an asterisk to indicate where a change from the previous issue was made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - ER
Navy - EC
Air Force - 11

Review activities:
Army - AR, MI
Navy - AS, OS
Air Force - 17, 85, 99
DLA - ES

User activities:
Army - AT, AV, ME
Navy - CG, MC
Air Force - 19

Agent:
DLA - ES

Preparing activity:
Navy - EC

(Project 5905-1047-4)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T05:04Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T05:04Z
Check the source to verify that this is the current version before use.