INCH-POUND

MIL-PRF-83726/13L
04 August 2016
SUPERSEDING
MIL-R-83726/13K
15 December 2015

PERFORMANCE SPECIFICATION

RELAYS, SOLID STATE, TIME DELAY, (ON OPERATE), TYPE I CLASS C, SPST-NO, 300 MILLIAMPERES, FIXED TIME, 0.05 TO 600 SECONDS, HERMETICALLY SEALED

Inactive for new design after 15 January 1999.
No superseding document.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-PRF-83726.



CIRCUIT DIAGRAM
TERMINAL VIEW

Inches	mm	Inches	mm
.018	0.46	.300	7.62
.060	1.5	.42	10.7
.100	2.54	.58	14.7
.28	7.1	.920	23.37

FIGURE 1. Outline dimensions and configuration of relay.

AMSC N/A

FSC 5945

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:27Z
Check the source to verify that this is the current version before use.



TIMING DIAGRAM

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Load is connected between B+ and terminal designated LOAD. Delay begins upon application of power to terminals (B+) and (B-). Upon completion of delay period, circuit from load terminal to ground is completed. (B+) and (B-) are shown for reference only; they do not appear on the relay.
4. Unless otherwise specified, tolerance is ±.010 (0.25 mm).
5. This is an active pin. Do not connect this pin to any portion of the circuit or ground.

FIGURE 1. Outline dimensions and configuration of relay - Continued.

REQUIREMENTS:

Operational data:

Timing action: Delay-on-operate.

Timing delay: Fixed time, 50 milliseconds to 600 seconds. See table I.

Timing accuracy: ±10 percent of the nominal timing under all conditions of input voltage and environmental extremes.

Recycle characteristics:

Before time out: A power interruption occurring after the start but before completion of the timing cycle shall be for a duration of 0.5 percent of the nominal time delay or 10 ms, whichever is greater, to ensure a loss in timing no greater than 10 percent.

After time out: A power interruption of 0.5 percent of nominal time delay or 10 ms, whichever is greater, will initiate a new timing cycle with a loss in timing no greater than 5 percent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:27Z
Check the source to verify that this is the current version before use.

TABLE I. Available time delay relays. 1/

Dash number	Time delay in seconds ±10%	Dash number	Time delay in seconds ±10%
-0500	.05	-1602	16
-1000	.10	-1802	18
-2000	.20	-2002	20
-3000	.30	-2202	22
-5000	.50	-2502	25
-7500	.75	-3002	30
-1001	1.0	-3502	35
-2001	2.0	-4002	40
-3001	3.0	-4502	45
-4001	4.0	-5002	50
-5001	5.0	-5502	55
-6001	6.0	-6002	60
-7001	7.0	-1003	100
-8001	8.0	-2003	200
-9001	9.0	-3003	300
-1002	10	-4003	400
-1202	12	-5003	500
-1402	14	-6003	600

1/ Additional time delay relays within the 0.05 to 600 second delay range are available. To establish Part or Identifying Numbers (PINs) not listed in table I (see “PIN” herein).

Input data:

Input voltage: 28 V dc nominal; range 18 V dc to 31 V dc.

Duty rating: Continuous.

Current drain: 10 milliamperes maximum, plus load current.

Reverse polarity protection: The timer will not be damaged or operate when input voltage polarity is reversed.

Output data:

Configuration: SPST-NO, solid state switch closure to ground.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:27Z
Check the source to verify that this is the current version before use.

Load ratings:

Resistive: 300 milliamperes at 25°C, derated to 100 milliamperes at +125°C. Minimum load current of 10 milliamperes is required.

Inductive: Three MIL-PRF-39016/6 relays or equivalent with 26.5 V dc coil voltage.

Lamp load: Two M6363/8-5 lamps in accordance with MIL-DTL-6363 or equivalent.

Motor load, dc: Not applicable.

Inductive load, ac: Three MIL-PRF-39016/6 relays or equivalent.

Resistive load, ac: Not applicable.

Motor load, ac: Not applicable.

Load suppression: Suppression for inductive loads for output protection is provided within the unit.

Voltage drop: 2.5 volts maximum at -55°C and +25°C, 2.0 volts maximum at +125°C.

Leakage current: 1 microampere maximum at 25°C, 10 microamperes maximum at +125°C.

Continuous current: Not applicable.

Overload: Not applicable.

Electrical data:

Insulation resistance: 1,000 megohms minimum at 500 V dc. 1/

Dielectric withstanding voltage: 500 V rms, 60 Hz, (sea level). 1/

Transients: In accordance with MIL-STD-704 for 28 V dc system (see figure 11).

1/ Measured between all terminals tied together to the case.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:27Z
Check the source to verify that this is the current version before use.

Environmental data:

Temperature range: -55°C to +125°C.

Altitude: 80,000 feet.

Shock: 150 g's for 11 ±1 ms half-sine wave.

Vibration (sinusoidal): 10 Hz to 80 Hz at .06 inch DA. 80 Hz to 3,000 Hz at 20 g's.

Vibration scan: Not applicable.

Acceleration: Not applicable.

Seal: MIL-STD-202-112, condition C.

Solderability: Not applicable.

Physical data:

Dimensions and configuration: See figure 1.

Terminal strength: Bend test not applicable.

Weight: 12 grams maximum.

Verification:

Qualification: Group B and Group C are not applicable.

Conformance: Group A to MIL-PRF-83726 only.

Marking: See MIL-PRF-83726. In addition, relays shall be marked with the Electrostatic Discharge Sensitive (ESDS) identifier as specified in MIL-STD-1285.

Electrostatic discharge (ESD) control program: Applicable (see MIL-PRF-83726).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:27Z
Check the source to verify that this is the current version before use.

Part or Identifying Number (PIN): Consists of the prefix M83726/13-, a four-digit dash number expressed in milliseconds as follows:



Examples

The first three digits of the dash number are significant; the fourth digit is the number of zeros to follow the first three digits. The time delay is expressed in milliseconds and converted to seconds.

M83726/13 - 0500 - 50 millisecond time delay
M83726/13 - 1001 - 1 second time delay
M83726/13 - 6003 - 600 second time delay

Quality assurance provisions: Group B and group C testing are not required.

NOTE: As of 15 June 1999, MIL-PRF-83726 no longer specifies Quality Levels, but existing order configurations may still include them. Relays with a "W" quality level indicator at the end are interchangeable with relays without a quality level letter.

Referenced documents. In addition to MIL-PRF-83726, this document references the following:

MIL-DTL-6363 MIL-PRF-39016/6 MIL-STD-1285 MIL-STD-704
MIL-STD-202-112 ASTM-B488

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire contect irrespective of the marginal notations and relationship to the previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:27Z
Check the source to verify that this is the current version before use.

Custodians:
Army - AT
DLA - CC

Preparing activity:
DLA - CC

(Project 5945-2016-035)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:27Z
Check the source to verify that this is the current version before use.