SS-C-1960/4B
May 24, 1977
SUPERSEDING
SS-C-1960/4A
September 21, 1976

FEDERAL SPECIFICATION SHEET

CEMENTS, HYDRAULIC, BLENDED

This specification sheet was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

The complete requirements for procuring blended hydraulic cements described herein shall consist of this document and the issue in effect of SS-C-1960/GEN.

APPLICABLE DOCUMENTS

Latest issue of SS-C-1960/GEN and documents referenced therein and the additional document specified herein.

American Society for Testing and Materials (ASTM) Standard:

C 595-76 - Blended Hydraulic Cements.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

REQUIREMENTS

The blended cement shall conform to ASTM C 595 with the following additional requirement:

Table 3 - Change Pozzolanic strength, minimum, psi, to "900" and (MPa) to "(6.2)", and use 2-inch cubes (see ASTM C 595, 7.9) instead of cylinders.

FSC 5610

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:14Z
Check the source to verify that this is the current version before use.

MILITARY CUSTODIANS:

Army - CE
Navy - YD
Air Force - 99

CIVIL AGENCY COORDINATING ACTIVITIES:

AGR - AFS
COM - NBS
DOT - FIS
GSA - FSS, PCD
INT - BOR

Preparing Activity:

Navy - YD

Project No. 5610-0118

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 25 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:14Z
Check the source to verify that this is the current version before use.