SS-P-1540
CANCELLATION
October 10, 1985

FEDERAL SPECIFICATION

PIPE, BITUMINIZED FIBER (AND FITTINGS)

This cancellation is approved by the Assistant Administrator, Office of Federal Supply and Services, General Services Administration.

Federal Specification SS-P-1540B, dated September 25, 1973, is hereby canceled.

The American Society for Testing and Materials (ASTM) Standards listed below adequately cover the requirements for these materials.

	Superseded By	Subject
Type I, Class 1	D 1861	Specification for Homogeneous Fiber Drain and Sewer Pipe.
Type I, Class 2, Style A	D 2311	Specification for Homogeneous Perforated Bituminized Fiber Pipe for General Drainage.
Type I, Class 2, Style B	D 2312	Specification for Homogeneous Perforated Bituminized Fiber Pipe for Septic Tank Disposal Fields.
Type I, Class 2, Style C	D 2818	Specifications for Homogeneous Perforated Bituminous Fiber Pipe Systems for Highway, Airport, and Similar Drainage.
Type II, Class 1	D 1862	Specification for Laminated-Wall Bituminized Fiber Drain and Sewer Pipe.
Type II, Class 2, Style A	D 2417	Specification for Laminated-Wall Bituminized Fiber Perforated Pipe for Agricultural, Land, and General Drainage.
Type II, Class 2, Style B	D 2313	Specification for Laminated-Wall Perforated Bituminized Fiber Pipe for Septic Tank Disposal Fields.
Type II, Class 2, Style C	D 2418	Specification for Laminated-Wall Bituminized Fiber Perforated Pipe for Airport and Roadway Drainage.

FSC 5630

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:14Z
Check the source to verify that this is the current version before use.