H-B-001139(GSA-FSS)
December 1, 1966

INTERIM FEDERAL SPECIFICATION

BRUSH, CLEANING, PORT AND TUBE

This Interim Federal Specification was developed by the General Services Administration, Federal Supply Service, Standardization Division, Washington, D. C. 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE AND CLASSIFICATION

1.1. Scope. This specification covers a small double-end cleaning brush, with synthetic bristles, of one type and grade.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on the date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

H-S-951 - Synthetic Filaments for Brushes; General Specification for.
PPP-B-636 - Box, Fiberboard.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C., 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Preproduction sample. When specified (see 6.2), before production is commenced, a sample brush covered by this specification shall be submitted or made available to the contracting officer or his authorized representative for approval in accordance with 4.2. The

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:07Z
Check the source to verify that this is the current version before use.

approval of the preproduction sample authorizes the commencement of production, but does not relieve the supplier of responsibility for compliance with all applicable provisions of this specification. The preproduction sample shall be manufactured in the same facilities to be used for the manufacture of the production item.

3.2 Standard product. The brushes delivered under this specification shall be the manufacturer's standard commercial product except for any design modification and additional requirements specified herein.

3.3 Materials. Materials shall conform to the requirements specified hereinafter. Materials not definitely specified shall be of the quality used for the purpose in commercial practice.

3.3.1 Brush wire. The brush wire shall be zinc (galvanized) coated soft steel brush quality used for the purpose in commercial practice and shall have a minimum diameter of 0.0605 inches.

3.3.2 Filament (bristles) material. Filament material shall be level, natural colored (white), made of a synthetic polymeric amide, conforming to type II, class N of H-S-951. The diameter shall be 0.014 inches.

3.4 Construction. The brush shall meet the requirements specified herein and in table I.

3.4.1 Wire part. The wire part for the brush heads and twisted-wire stem shall be formed from two (2) pieces of wire specified in 3.3.1. The cut-ends of the wire at the small diameter brush head end shall be neatly and securely joined with a composition of 50 percent tin and 50 percent lead solder. The cut-ends of the wire at the large diameter, tufted tip brush head end shall be free of sharp edges, points, burrs, etc. and finished so it shall not come in contact with the surface being cleaned. Both brush head ends shall have a minimum of 18 twist each excluding the tuft-end. The twisted-wire stem shall have a minimum of 10 twist per inch.

3.4.2 Brush heads. Both brush head filaments (3.3.2) shall be evenly distributed and securely spiral-wound within the twisted-wire at an angle of approximately 90 degrees to the wire and shall not pull loose when tested as specified in 4.4.1. In addition to the spiral-wound filaments, the large brush head end shall have a tufted-end.

Table I. Physical requirements.

Brush part	Required
Brush heads:	
Tufted tip head	
Length, o/a, minimum inches	3
Diameter, o/a, minimum inches	1
Length of tuft end (beyond wire), minimum inches	1/2
Straight head:	
Length, o/a, minimum inches	2
Diameter, o/a, minimum inches	1/2
Wire:	
Diameter (minimum), single strand	0.0605
Length wire stem between brush heads, minimum inches	6-1/2
Brush length, o/a, minimum inches	12

3.5 Workmanship. The brush shall be free from defects which affect the appearance, serviceability, or durability. The brush shall be neatly assembled and finished, and shall have no sharp edges. The filler material shall be free of foreign and loose material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:07Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Preproduction sample inspection. When a preproduction sample is required, it shall be examined for the defects in table II and specified dimensions. The preproduction sample shall be tested in accordance with 4.4.1.

4.3 Sampling for inspection and acceptance. Sampling for inspection and acceptance shall be performed in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated hereinafter.

4.3.1 Component and material inspection. In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

4.3.2 End item inspection. The lot shall consist of all brushes offered for inspection at one time. The sample unit shall be one completely fabricated brush.

4.3.2.1 Visual examination. Examination shall be made of the end item for the defects in table II. The inspection level shall be level II with and AQL of 4.0 expressed in terms of defects per hundred units.

Table II. Visual Defects.

Examine	Defects
Construction and workmanship	Not type brush covered by specification. Sharp protrusions (wire), rough or nicked wire ends, tuft tip not formed to prevent wire contacting surfaces being cleaned. Surfaces. Cut-ends not neatly and securely soldered. Filler filament embedded with foreign matter, dirty, not evenly distributed or spiral-wound. Filament burnt or otherwise damaged by soldering process.

4.3.2.2 Dimensional examination. Inspection shall be made of the end item for compliance with table I. Any deviation from specified requirements shall constitute a defect. The inspection level shall be S-2 with an AQL of 4.0 expressed in terms of defects per hundred units.

4.3.2.3 Testing of the end item. The end item shall be tested as specified in 4.4.1. The inspection level shall be S-2 with an AQL of 4.0 expressed in terms of defects per hundred units.

4.3.3 Examination of preparation for delivery. An examination shall be made to determine that packaging, packing and marking comply with the requirements of section 5 of this specification. Defects will be scored as listed in table III. The lot shall be the number of containers offered for delivery at one time. The sample unit shall be one shipping container fully prepared for delivery except it need not be sealed. The inspection level shall be S-2 with an AQL of 4.0 expressed in terms of defects per hundred units. Examination for closure and strapping shall be in accordance with applicable box specifications.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:07Z
Check the source to verify that this is the current version before use.

Table III. Examination of preparation for delivery.

Examine	Defects
Markings (exterior and interior)	Missing; incorrect; illegible; of improper size, location, sequence or method of application.
Materials	Component missing, damaged, or otherwise defective.
Contents (exterior and interior)	Content per container is more or less than specified.

4.4 Test.

4.4.1 Retention of filler filament material. Grasp the strands of filler filament between the thumb and finger and apply a pulling force in a direction tending to pull the filaments from between the twisted-wire core to determine compliance with 3.4.2. A minimum of five determinations shall be made per brush head. Failure of one or more determinations shall constitute a defect.

5. PREPARATION FOR DELIVERY

5.1 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.1.1 Level A. The brushes in quantities as specified (see 6.2) shall be packed in a close-fitting box conforming to PPP-B-636, class weather-resistant. Cushioning shall be provided. The box shall be closed, waterproofed and strapped in accordance with the appendix to the box specification. The gross weight shall not exceed the weight limitations of the box specification.

5.1.2 Level B. Twenty-four brushes shall be packed in a close-fitting box conforming to PPP-B-636, class domestic. Cushioning shall be provided. The box shall be closed in accordance with the appendix to the box specification.

5.1.3 Level C. The brushes shall be packed to insure carrier acceptance and safe delivery at destination in containers complying with the rules and regulations applicable to the mode of transportation.

5.2 Marking.

5.2.1 Civil agencies. In addition to markings required by the contract or order, the shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.2.2 Military agencies. In addition to markings required by the contract or order, the shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES.

6.1 Intended use. The brushes covered by this specification are intended for cleaning small outlets, spouts, and tubes on percolators, coffee-creamers, hot beverage servers, etc., normally used to serve large quantities of food.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Selection of applicable level packing required (see 5.1).
(c) Quantity of brushes required in the shipping container (see 5.1.1).
(d) When a preproduction sample is required (see 3.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:07Z
Check the source to verify that this is the current version before use.