H-B-00681d(GSA-FSS)
September 24, 1968
SUPERSEDING
Int. Fed. Spec. H-B-00681c(GSA-FSS)
September 12, 1963

INTERIM FEDERAL SPECIFICATION

BRUSHES, TYPEWRITER

This Interim Federal Specification was developed by the General Services Administration, Federal Supply Service, Washington, D.C. 20405, based on currently available technical information. It is recommended that Federal agencies use it in procurement and forward any recommendations for changes to the preparing activity at the address shown above. The General Services Administration has authorized Federal agencies to use Specification H-B-681b dated February 15, 1956.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers brushes used for dusting typewriters and for cleaning the type faces of typewriter keys.

1.2 Classification.

1.2.1 Types and styles. The typewriter dusting and cleaning brushes covered by this specification shall be of the following types and styles as specified (see 6.1) (figures 1 and 2):

Type I - Machine dusting.

Style C - Cone-shape, wire handle.
Bristle or Synthetic filament.

Style P - Paintbrush-shape, wood or plastic handle (ferrule set).
Bristle or Synthetic filament.

Type II - Type cleaning.

Style PS - Paintbrush-shape, short wood or plastic handle (staple set).
Bristle or Synthetic filament.

Style PLP- Paintbrush-shape, long plastic handle (removable handle).
Synthetic filament.

Style RH - Round-handle, wood or plastic handle.
Synthetic filament.

Style T - Toothbrush-shape, wood or plastic handle.
Synthetic filament or Horsetail hair.

2. APPLICABLE DOCUMENTS

2.1 Specifications and standards. The following specifications and standards, of the issues in effect on date of solicitation for offers or requests for proposals, form a part of this specification to the extent specified herein:

Federal Specifications:

H-S-951 - Synthetic Filaments for Brushes; General Specification for.
L-P-394 - Plastic Molding Material, Polypropylene, Injection and Extrusion.

PPP-B-636 - Box, Fiberboard.
PPP-B-676 - Boxes, Setup.
UU-P-268 - Paper, Kraft, Untreated, Wrapping.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:07Z
Check the source to verify that this is the current version before use.

Federal Standards:

Fed. Std. 123 - Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards and Handbooks as outlined under General Information in the Index of Federal Specifications, Standards and Handbooks at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Auburn, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specification:

MIL-W-6110 - Wood, Determination of Moisture Content.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with a specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated the issues in effect on the date of invitation for bid or request for proposal shall apply:

American Society for Testing and Materials (ASTM) Standards:

D256-56 - Impact Resistance of Plastic and Electrical Insulating Materials.
D638-61T - Tensile Properties of Plastics.
D785-62 - Test for Rockwell Hardness of Plastics and Electrical Insulating Materials.
D792-60T - Specific Gravity and Density of Plastics.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pa. 19103.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Standard product. The brushes delivered under this specification shall be the manufacturer's standard commercial product that comply with specification requirements.

3.2 Materials. Materials shall conform to the applicable specifications and requirements specified hereinafter. Materials not specifically defined shall be of a quality equal to those specified.

3.2.1 Polypropylene. Polypropylene used for handles or blocks shall be virgin general purpose polypropylene meeting the requirements of L-P-394; except the physical requirements shall be limited to those specified in table I (see 4.4.4). Clean, unburned plastic material in the form of imperfect parts, sprues, runners, or other scrap of the same composition as the virgin material and produced in molding or finishing operations, may be reground and mixed with the virgin material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:07Z
Check the source to verify that this is the current version before use.

TABLE I. Requirements for polypropylene plastic

Property 23°C (73°F.)	Units	Property Values
Density	grams/ml.	0.900 min. 0.915 max.
Tensile Yield Strength	psi	4500 min.
Izod Impact Strength	ft. lb./in.	0.5 min.
Rockwell Hardness	R scale	85 min. 100 max.

3.2.2 Wood. Wood handles or blocks shall be of dense, close-grained hardwood and shall be sanded or tumbled smooth. At the option of the manufacturer they shall either be coated with a clear organic coating or tumbled wax. Prior to machining the wood shall be thoroughly and uniformly dried to a moisture content not exceeding 12 percent when tested as specified in 4.2.2..

3.2.3 Wire. The wire used for the twisted-wire brush shall be steel brush wire, corrosion-resistant or zinc coated to resist corrosion normally used by the manufacturer.

3.2.4 Staple wire. Staple wire shall be steel staple wire, corrosion-resistant or treated to resist corrosion normally used by the manufacturer.

3.2.5 Bristle. The bristle shall be stiff sterilized hog bristle of uniform length, diameter, and quality. (See 4.2.1.1).

3.2.6 Horsehair. The horsehair shall be extra stiff sterilized horse-tail hair. (See 4.2.1.1)

3.2.7 Synthetic filament. The synthetic filament shall be level, black or natural colored, made of a synthetic polymeric amide conforming to class N, type II of H-8-951 (see 4.4.2), except the modulus of elasticity requirements shall not apply. The diameter shall be as specified in the applicable physical requirements table.

3.2.7.1 Fastness to boiling water, and stiffness. The synthetic filament shall withstand being immersed in boiling water for 5 minutes without showing marked discoloration or bleeding. It shall show no appreciable change in stiffness after being removed from the boiling water and drying at 70°C. for 3 hours (see 4.4.2.1).

3.2.8 Ferrules. Ferrules shall be non-corrosive metal or metal nickel plated to resist corrosion.

3.3 Design. The brushes shall be of the general designs illustrated in figures 1 and 2. Figures 1 and 2 are intended for illustration purposes only and are not intended to preclude similar designed brushes otherwise meeting the requirements of this specification.

3.4 Construction. The brushes shall conform to the requirements specified herein and in the applicable requirement tables. The brushes shall be similar to the designs shown in figures 1 and 2.

3.4.1 Style C, cone-shape, twisted-wire handle, for machine dusting (type I). The bristle or synthetic filament shall be securely spiral-wound within the twisted wire (3.2.3) which shall also form the handle of the brush. The hand end of the handle shall have a loop. The bristles or filaments shall be approximately parallel to each other and at an angle of approximately 90° to the wire. The bristles or filaments shall be evenly distributed in the brush head and shall have a taper at the brush-head tip (see figure 1).

3.4.1.1 Brush head filler material. The filler material. The filler material shall be either bristle specified in 3.2.5 or synthetic filament specified in 3.2.7, at the option of the supplier.

3.4.1.2 Physical requirements. The brushes shall conform to the physical requirements specified in table II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:07Z
Check the source to verify that this is the current version before use.

TABLE II. Minimum physical requirements for style C brushes

Requirement		Style C
Length, over-all	inches	11-1/2
Brush head:		
Length, over-all	inches	3-3/4
Length before taper	do	2-3/4
Diameter before taper	do	1-1/2
Diameter at tip (end of taper)	do	1/2
Bristle or synthetic filament:		
Weight of bristle (finished brush)	ounce	7/64
Weight of synthetic filament (finished brush)	do	9/64
Diameter of synthetic filament	inch	0.012
Wire (twisted):		
Diameter, single strand	do	0.072 1/

1/ Commercial tolerances apply.

3.4.2 Style P, paintbrush-shape, wood or plastic handle, for machine dusting (type I). The brush filler material shall be set in a ferrule attached to the handle. The ends of the brush heads shall be trimmed square and shall have a flare (see figure 1).

3.4.2.1 Brush head filler material.

3.4.2.1.1 Style P. The filler material shall be either bristle specified in 3.2.5 or synthetic filament specified in 3.2.7, at the option of the supplier.

3.4.2.2 Handle. The handle shall be the standard artist type. The handles shall be either polypropylene specified in 3.2.1 or wood specified in 3.2.2, at the option of the supplier.

3.4.2.3 Ferrules. The ferrules shall be of the material specified in 3.2.8. The handle end of the ferrule shall be round and the brush end oval. The seam shall be closed by soldering, interlocking, or spot welding. It shall be attached to the handle by swaging, crimping, or screw type nails or rivets.

3.4.2.4 Set. The butt ends of the bristle or the synthetic filament shall be set in rubber or other suitable setting compound which will not become brittle.

3.4.2.5 Physical requirements. The brushes shall conform to the physical requirements specified in table III.

TABLE III. Minimum physical requirements for style P brush

Requirement		Style P
Length, over-all	inches	11-3/4
Bristle or synthetic filament		
Length clear of ferrule	inches	1-1/2
Hold in ferrule	do	1/2
Width, brushing surface	do	1
Weight of bristle in finished brush	ounce	3/32
Weight of synthetic filament in finished brush	ounce	7/64
Diameter of synthetic filament	inch	0.012
Ferrule:		
Depth	inches	1-5/8
Thickness of metal	inch	0.006
Diameter, handle end, outside	do	0.374
Handle:		
Length clear of ferrule	inches	8-1/2

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:07Z
Check the source to verify that this is the current version before use.

3.4.3 Style PS, paintbrush-shape, short handle, for type cleaning (type II). The bristle or synthetic filament shall be stapled in the block which shall also serve as a handle (see figure 2).

3.4.3.1 Brush head filler material. The filler material shall be either bristle specified in 3.2.5 or synthetic filament specified in 3.2.7, at the option of the supplier.

3.4.3.2 Handle (block). The handle shall be a short single piece, flat paintbrush-shape and the sides shall be rounded. The bristle face end shall be cut square and shall have holes for staple-setting the filler material. The handles shall be either polypropylene specified in 3.2.1 or wood specified in 3.2.2, at the option of the supplier.

3.4.3.3 Set. The filler material shall be cut to double length and folded in the center and stapled into the holes of the handle. The staples shall be made of the wire specified in 3.2.4. The tufts shall not loosen, nor pull out of the brush when tested as specified in 4.4.6.

3.4.3.4 Physical requirements. The brushes shall conform to the physical requirements specified in table IV.

TABLE IV. Minimum physical requirements for Style PS brush

Requirement		Style PS
Length, over-all	inches	5-3/16
Bristles or Synthetic filament:		
Length clear of block	inch	9/16
Weight of bristle in finished brush	ounce	0.04
Weight of synthetic filament in finished brush	do	0.04
Diameter of synthetic filament	inch	0.012
Block:		
Length	inches	4-5/8
Width, widest part, hand end	inch	7/8
Width, brush end	inches	1-1/16
Thickness	inch	15/32
Number of holes		10
Diameter of holes	inch	0.099
Staples:		
Diameter	do	0.018

3.4.4 Style PLP, paintbrush-shape, long plastic-handle, for type cleaning (type II). The synthetic filament shall be secured in the ferrule by crimping the metal ferrule around the filament in such a manner as to create a flare at the brush head end.

3.4.4.1 Brush head filler material. The filler material shall be the synthetic filament specified in 3.2.7.

3.4.4.2 Ferrule. The ferrule shall be of the material specified in 3.2.8. It shall be a round, seamless or crimped type shaped to produce a push-fit into the handle end.

3.4.4.3 Handle. The handle shall be the standard artist type made from the polypropylene specified in 3.2.1.

3.4.4.4 Set. The butt ends of the synthetic filaments shall be securely held in the ferrule by crimping the ferrule around the filament.

3.4.4.5 Tuft. The tuft shall be wedge-shaped, formed by gradual tapering from the center filaments downward to the outer filaments on the two sides of the tuft approximately 1/8 of an inch.

3.4.4.6 Physical requirements. The brushes shall conform to the physical requirements specified in table V.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:07Z
Check the source to verify that this is the current version before use.

TABLE V. Minimum physical requirements of Style PLP brush.

Requirement		Style PLP
Length, over-all	inches	6-1/4
Synthetic filaments:		
Length clear of ferrule (longest)	inch	11/16
Length clear of ferrule (shortest)	do	9/16
Hold in ferrule	do	1/8
Width, brushing surface	do	1/2
Weight of synthetic filament in finished brush	ounce	3/64
Diameter of synthetic filament	inch	0.014
Ferrule:		
Depth	inch	1/4
Thickness of metal	do	0.032
Diameter, handle end, outside	do	3/8
Diameter, brush end, outside	do	5/16
Handle:		
Length clear of ferrule	inches	5-1/2
Diameter, smallest part, hand end	inch	1/8
Diameter, brush end, outside	do	7/16

3.4.5 Style RH, roundhandle-shape for type cleaning (type II). The filler material shall be staple-set in the block which shall also serve as a handle (see figure 2).

3.4.5.1 Brush head filler material. The filler material shall be synthetic filament specified in 3.2.7, and shall be trimmed square to form the brush surface.

3.4.5.2 Handle and block. The handle and block shall be one piece construction made from either the polypropylene specified in 3.2.1 or wood specified in 3.2.2, at the option of the supplier. The handle portion shall be a spoke type design and the block portion shall be circular with a square (flat) bristle face. A flat surface at the handle end to serve as a thumb grip is permissable.

3.4.5.3 Set. The filler material shall be cut to double length and folded in the center and stapled into the holes of the block portion. The staples shall be made of the wire specified in 3.2.4. The tufts shall not loosen, not pull out of the brush when tested as specified in 4.4.6.

3.4.5.4 Physical requirements. The brushes shall conform to the physical requirements specified in table VI.

TABLE VI. Physical requirements of Style RH brush

Requirement		Style RH
Length, overall	inches	5 ± 1/4
Handle and block:		
Length of handle	inches	3-3/4 ± 1/4
Diameter of top of handle	inch	1/2 ± 1/8
Diameter of widest part (approximately 1/2 inch down the handle)	inch	15/16 ± 1/16
Diameter of base of handle	do	1/2 ± 1/16
Block diameter	inches	1-5/16 ± 1/16
Block thickness	inch	9/16 ± 1/32
Number of holes, minimum		31
Depth of holes, minimum		5/16
Distance of outside holes from edge of block, minimum	inch	1/8
Staples:		
Diameter, minimum	inch	0.020 1/
Synthetic filament:		
Length clear of block	inch	9/16 ± 1/16
Number of tufts, minimum	inch	31

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:07Z
Check the source to verify that this is the current version before use.

TABLE VI. Physical requirements of Style RH brush (con.)

Requirement		Style RH
Number of filament ends per tuft, minimum		40
Diameter of synthetic filament, minimum	inch	0.012

1/ Commercial tolerances apply.

3.4.6 Style T, toothbrush-shape, for type cleaning (type II). The brush filler material shall be staple-set perpendicularly in the block which shall also serve as the handle (see figure 2).

3.4.6.1 Brush head filler material. The filler material shall be either horsehair specified in 3.2.6 or synthetic filament specified in 3.2.7, at the option of the supplier.

3.4.6.2 Block. The block shall be a single piece construction made from either polypropylene specified in 3.2.1 or wood specified in 3.2.2, at the option of the supplier. All edges and corners shall either have radiuses or the sides and ends shall be rounded. The brush shall be flat, rectangular design, except the hand portion (handle) may have an angular offset.

3.4.6.3 Set. The filler material shall be cut to double length and folded in the center and stapled into the holes of the block. The staples shall be made of the wire specified in 3.2.4. The tufts shall not loosen, nor pull out of the brush when tested as specified in 4.4.6.

3.4.6.4 Physical requirements. The brushes shall conform to the physical requirements specified in table VII.

TABLE VII. Minimum physical requirements of Style T brushes

Requirement		Style T
Length, over-all	inches	6
Brush filler material:		
Length clear of block	inch	3/8
Weight of horsetail hair in finished brush	ounce	1/32
Weight of synthetic filament in finished brush	do	1/32
Diameter of synthetic material	inch	0.012
Block:		
Length	inches	6
Width	inch	1/2
Thickness	do	3/16
Number holes	--	38
Diameter holes	inch	0.078
Angular offset (hand portion approximately) 1/	degrees	25
Brushing surface:		
Total	square inch	3/4
Width	inch	3/8
Length	inches	1-1/2

1/ Optional

3.5 Marking for identification. Except for Style C, the supplier shall permanently and legibly indent his name, or trademark, of such known character that it is easily identifiable with said manufacturer, on the handle or block of each brush.

3.6 Sterilization. Horsetail hair and hog bristle used for brushes shall be sterilized (see 4.2.1.1).

3.7 Workmanship. The brushes shall be free from defects which affect their appearance, durability, or serviceability.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:07Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Sampling for inspection and acceptance. Sampling for inspection and acceptance shall be performed in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated.

4.2.1 Component and material inspection. In accordance with 4.1 above, the supplier is responsible for insuring that components and materials used are manufactured, tested, and inspected in accordance with requirements of referenced subsidiary specifications and standards to the extent specified, or if none, in accordance with this specification.

4.2.1.1 Certificate of compliance. The submittal of a certificate of compliance stating that horsetail hair and hog bristle used in construction of brushes covered herein has been sterilized and will be required by the contractor.

4.2.2 Moisture content of block and handle. Test shall be performed on each lot of wood offered for inspection prior to machining for moisture content in accordance with any method of MIL-W-6110 to determine compliance with 3.2.2. The sample unit shall be one piece of cut wood. Two determinations shall be made on each sample unit and the result shall be the average of the two determinations. The inspection level shall be S-2 with an acceptable quality level (AQL) of 2.5 defects expressed in terms of defects per hundred units.

4.2.3 End item inspection.

4.2.3.1 Examination of the end item. Examination of the end item shall be in accordance with the classification of defects, inspection levels and acceptable quality levels (AQL's) set forth below. The lot size, for the purpose of determining the sample size in accordance with MIL-STD-105, shall be expressed in units of brushes for examinations under 4.2.3.1.1 and 4.2.3.1.2, in units of intermediate containers for examination under 4.2.3.1.3 and in units of shipping containers for examination under 4.2.3.1.4.

4.2.3.1.1 Examination of the end item for defects in appearance, construction and workmanship. The sample unit for this examination shall be one brush of each type and style.

TABLE VIII. Visual examination

Examine	Defect
Material	Bristle not natural hog; not stiff and resilient.
	Synthetic filament not as specified.
	Horsehair not stiff and resilient; not natural horsehair
	Wire not zinc-coated (galvanized) steel brush wire; or corrosion-resistant brush wire.
	Wood handle (when applicable) not made of a close, straight grained hardwood.
	Plastic handle (when applicable) not solid plastic.
Construction and appearance:	Plastic handles not smooth finished.
	Wood handles not sanded or tumbled smooth, or void of finish.
	Brush filler material for specified style not properly set in block, twisted-wire, or ferrule.
	Push-fit type ferrule easily removed from handle.
	Exposed sharp wire, staples, sharp edges or splinters.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:07Z
Check the source to verify that this is the current version before use.

TABLE VIII. Visual examination (con.)

Examine	Defect
Design	Not type or style specified; incorrect design, handle, or filler material. Edges and ends of brushes not finished as specified, where applicable. Handle and block not-piece construction.
Workmanship:	Brush filler material not evenly distributed in brush head. Brush filler material not clean or properly trimmed. Identification marking omitted; incomplete or not as specified, where applicable.

4.2.3.1.2 Examination of the end item for dimensional defects. The sample unit for this examination shall be one brush.

Examine	Defect
Dimensions	Any dimension not in accordance with specifi- on requirements for ., style, and size brush specified (see tables I through IV).

4.2.3.1.3 Examination of the end item for count. The sample unit for this examination shall be one intermediate container. The average count per container shall be not less than the specified or indicated quantity.

4.2.3.1.4 Examination of preparation for delivery. An examination shall be made to determine that packaging, packing and marking requirements, as specified, are complied with. The sample unit for this examination shall be one shipping container fully prepared for delivery.

TABLE IX. Classification of preparation for delivery defects

Examine	Defect
Packaging	Not packaged as specified; intermediate container not as specified.
Packing	Not type shipping container specified. Any break, tear, hole or other defect in container which might cause damage to or loss of content. Waterproof case liner, when applicable, missing or not as specified.
Content	More or less than quantity of units or intermediate containers indicated or specified.
Marking	Omitted; incomplete, incorrect, illegible; not in accordance with contract requirements.

4.2.3.1.5 Inspection levels and acceptable quality levels (AQL's) for examinations.

Examination paragraph	Inspection level	AQL
4.2.3.1.1	I	4.0
4.2.3.1.2	S-1	2.5
4.2.3.1.3	S-2	---
4.2.3.1.4	S-2	4.0

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:07Z
Check the source to verify that this is the current version before use.

4.3.4 Testing of end item. The end item shall be tested for the applicable characteristics as specified in 4.4. The inspection level shall be S-2 and the AQL shall be 4.0 defects per hundred units.

4.4 Tests

4.4.1 Weight of horsehair, bristle, or filament. The filler material shall be removed from the brush or, at the option of the Government inspector, select the filler material just prior to assembly into the brush for weighing. The inspector shall exercise the option only when the amount of filler material is consistently controlled for each brush by the manufacturing process and weight loss due to trimming is negligible. The filler material shall be conditioned as specified in 4.4.1.1 or 4.4.1.2.

4.4.1.1 Horsehair and bristle. The horsehair or bristle shall be conditioned for not less than 16 hours in air at a relative humidity of 50 ± 4 per cent and at a temperature of 73° ± 2°F. The weight shall be determined in the same atmosphere for compliance with the applicable physical requirements table.

4.4.1.2 Polypropylene. Unconditioned polypropylene shall be weighed to determine compliance with the applicable physical requirements table.

4.4.1.3 Certificate of compliance. The contractor shall submit a certificate of compliance stating that sterilized horsetail hair or bristle, whichever is applicable, has been used in the construction of brushes.

4.4.2 Synthetic filament. Filaments shall be tested as described in H-S-951 to insure compliance with 3.2.7.

4.4.2.1 Fastness to boiling water, and stiffness. Not less than 5 synthetic filaments shall be immersed in boiling water for 5 minutes and then removed and allowed to dry for 3 hours at 70°C. to insure compliance with 3.2.7.1.

4.4.3 Length of bristle, filament, or horsehair. The length of the bristle, filament, or horsehair shall be determined by means of a scale or tape graduated in 1/16 inches or less.

4.4.4 Plastic properties. Plastic blocks and handles shall be tested for the following properties in accordance with the specified method for compliance with 3.2.1:

Property	ASTM Method
Density	D792-60T Method A
Tensile Yield Strength	D638-T Speed C (2.0 in per min.)
Izod Impact Strength	D256-56 Method A
Rockwell Hardness	D785-62 Procedure A

4.4.5 Diameter of wire. The diameter of the wire shall be measured with a micrometer caliper graduated to read to 0.001 inch or less.

4.4.6 Set retention. Grasp the tuft with a suitable clamping device and apply a force by using a scale or weight of not less than 5 pounds in the direction tending to pull the tuft from the block to determine compliance with 3.4.3.3, 3.4.5.3, or 3.4.6.3, whichever is applicable. This test shall be performed on two different tufts for each brush being tested.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C, as specified (see 6.1).

5.1.1 Level A. The fillers of each type, and style of typewriter brush shall be individually wrap wrapped in kraft paper conforming to UU-P-268, grade A, having a minimum basis weight of 60 pounds (24 x 36 - 500). The wrapper shall be held in place with twine or a rubber band. The wrapper shall be applied in such a manner as to protect the fillers from distortion or damage. Twelve brushes of one type and size shall be packaged in folding boxes or set-up boxes conforming to PPP-B-676. When typewriter brushes are comprised of animal fillers, each box shall contain not less than 3 balls of naphthalene or an equivalent quantity of flake napthalene or other suitable moth repellent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:07Z
Check the source to verify that this is the current version before use.

5.1.2 Level B. Twelve typewriter brushes, of one stock number, shall be placed in a paperboard box of the type normally used for commercial packaging. When brushes are comprised of animal fillers, each box shall contain not less than 3 balls of naphthalene or an equivalent quantity of flake naphthalene or other suitable moth repellent.

5.1.3 Level C. Brushes shall be packaged in accordance with the industry's practice.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.1).

5.2.1 Level A. Brushes of one type and style only, packaged as specified in 5.1.1, shall be packed in fiberboard shipping containers conforming to class weather-resistant, V3c or V3s, style RSC of PPP-B-636. Each shipping container shall be closed, waterproofed with a case liner or tape, and reinforced with flat steel strapping or tape banding in accordance with the appendix of the container specification.

5.2.2 Level B. Sixty boxes (720 brushes) of one stock number, packaged in accordance with 5.1.2, shall be packed into a fiberboard box conforming to PPP-B-636, class domestic, style optional. Bursting strength of the fiberboard shall be not less than 175 p.s.i.. Closure shall be in accordance with the appendix of PPP-B-636.

5.2.3 Level C. Brushes of one type and style only, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with rules and regulations of carriers applicable to the mode of transportation.

5.3 Marking.

5.3.1 Civil agencies. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with Standard No. 123.

5.3.2 Military agencies. In addition to any special marking required by the contract or order, marking shall be in accordance with the applicable sections of MIL-STD-129.

6. NOTES

6.1 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type and style of brush required (see 1.2.1).
(c) Selection of applicable levels of packaging and packing.

6.2 Standard packaging (civil agencies). The standard packaging and packing for civil agencies shall be as specified in 5.1.2 and 5.2.2.

6.3 Comparison of classification between H-B-00681c and H-B-00681d.

H-B-00681c	H-B-681d	
Type I	Type I	
Style C	Style C	1/
Class 1	None	
Class 2	None	
Style P	Style P	1/
Class 1	None	
Class 2	None	
Type II	Type II	
Style PSW	Style PS	1/
Class 1	None	
Class 2	None	
Style PSP	None	
Class 1		
Class 2		
Style PLP	Style PLP	1/
Class 2	None	1/
Style RH	Style RH	1/
Class 2	None	

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:07Z
Check the source to verify that this is the current version before use.

(con.)

H-B-00681c	H-B-00681d
Type II	Type II
Style T	Style T 1/
Class 2	None
Class 3	None
Style TP	None
Class 2	None

1/ See applicable specification requirements.



Style C,
cone-shape



Styles P
paintbrush-shape

FIGURE 1. Machine-dusting brushes.



Styles PS
paintbrush-shape



Style PLP
paintbrush- shape



Styles T
toothbrush-shape



Style RH
round handle shape

FIGURE 2. Type-cleaning brushes.

GSA DC 69-4001

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:07Z
Check the source to verify that this is the current version before use.