FEDERAL SPECIFICATION

BRUSH, ROOF, KNOTTED-STYLE, THREE KNOTS

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE

1.1 Scope. This specification covers roof brushes of one type and grade.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specification:

PPP-B-636 - Boxes, Shipping, Fiberboard.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Philadelphia, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Houston, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standard:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Motor Freight Traffic Association, Inc., (cont'd)

(Application for copies should be addressed to the American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:06Z
Check the source to verify that this is the current version before use.

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

3. REQUIREMENTS

3.1 Material.

3.1.1 Fiber. The brush shall be 100 percent black or gray Tampico fiber.

3.1.2 Ferrules. The round, ferrule shall be made of corrosion-resistant steel, or steel made corrosion-resistant by a coating which shall not wrinkle, blister, separate, or become soft or dull, when tested in accordance with 4.4.2.2.1.

3.1.3 Block. The block shall be made of close-grained hardwood, smoothly finished or lacquered. The clear coating shall not wrinkle, blister, separate, or become soft or dull, when tested in accordance with 4.4.2.2.2.

3.1.4 Plug. The plug shall be made of close-grained hardwood.

3.2 Construction.

3.2.1 Block. The block shall have a hole through the center as shown in figure 1. The hole is used to accomodate a broom handle of appropriate size. It shall be taper-bored from a diameter of 3/4 inch to a diameter of 13/16 inch at an angle of 60° to the side of the block. The bottom of the block shall have three holes for receiving the knot handles snugly. The center hole shall be placed midpoint between the ends and sides. Two holes, one on each side of the center hole, shall be aligned on the long axis, 2 ± 1/16 inch on centers.

3.2.2 Knots. The knots shall be plugged and driven open-center style. The handle of each knot shall be further secured in the block by one nail or screw through each side of the block into the knot handle.

3.3 Physical requirements. The brushes shall conform to the physical requirements in table I.

TABLE I. Physical requirements

Block (see figure 1):	
Length, minimum, inches	6
Thickness, minimum, inches	1-3/4
Width at center, minimum, inches	2-1/4
Ferrules:	
Diameter, inside, minimum, inches	1-1/4
Thickness, minimum, inch	1/32
Depth, minimum, inch	3/4
Knots:	
Knot handle:	
Diameter, minimum, equivalent to dowel, inch	9/16
Inserted into block, minimum, inch	3/4
Plug:	
Diameter, minimum, at extremity, which is bevelled to the knot handle, inch	15/16
Length in ferrule, minimum, inch	3/4
Fiber:	
Held in ferrule, minimum, inch	1/2
Weight, 3 knots, minimum, ounces	5-1/4
Length outside of ferrule, minimum, inches	3-1/4

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:06Z
Check the source to verify that this is the current version before use.

3.4 Workmanship. The brushes shall be free from defects which affect their appearance or their serviceability.

3.5 Marking. Unless otherwise specified (see 6.2), in addition to any special markings required by the contract or order, each brush shall be stamped or otherwise permanently marked with the contractor's name or trade mark.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government.

4.2 Examination of preparation for delivery. An examination shall be made to determine compliance with the requirements of Section 5. The sample unit shall be one shipping container fully prepared for delivery. Sampling shall be in accordance with MIL-STD-105. The inspection level shall be S-2 with an AQL of 4.0 expressed in terms of percent defective.

4.3 Inspection and testing of end item.

4.3.1 Visual inspection of brushes and components. The sample unit for this inspection is one complete brush. It shall be inspected for defects listed in table II. For major and minor defects, the inspection level shall be level S-2. The AQL for major defects shall be 2.5 percent defective and for minor defects the AQL shall be 6.5 percent defective.

TABLE II. Defects subjected to visual inspection

Defects	Classification Major	Classification Minor	Requirement paragraph
Fiber:			
Material not as specified.	X		3.1.1
Length of fiber out of ferrule, not minimum specified.		X	Table I
Hold in ferrule, less than minimum specified.	X		Table I
Weight of bristle, less than minimum specified.	X		Table I
Ferrule:			
Material not as specified.	X		3.1.2
Diameter, not minimum specified.		X	Table I
Depth, not minimum specified.		X	Table I
Coating wrinkles, blisters, separates, or becomes soft or dull	X		3.1.2
Thickness of metal, less than minimum specified.	X		Table I
Block:			
Material not as specified.	X		3.1.3
Not smoothly finished with varnish, lacquer, or other organic finish.		X	3.1.3
Dimensions, not minimum specified.		X	Table I
Knots:			
Not minimum dimensions specified.	X		Table I
Identification marking:			
Not properly marked.		X	3.5
Workmanship:			
Defects which affect serviceability.	X		3.4

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:06Z
Check the source to verify that this is the current version before use.

4.4 Test procedure. The tests listed below shall be conducted on the samples selected and examined in paragraph 4.3.1. Unless otherwise specified, standard laboratory conditions are 23° ± 1°C and a relative humidity of 50 ± 5 percent. All test reports shall contain the individual values utilized in expressing the final results. All tests shall be evaluated for conformance to the requirements specified in section 3. Failure to pass any test or noncompliance to the requirements shall be cause for rejection of the sample.

4.4.1 Weight of fiber. The fibers shall be removed from the brush, conditioned for 16 hours at standard laboratory conditions and weighed in that atmosphere to the nearest 0.1 ounce.

4.4.2 Solvent resistance test.

4.4.2.1 Composition of solvent. The solvent used shall be composed of the following mixture:

	Percent by volume
Normal butyl acetate	15 ± 1
Normal butyl alcohol	15 ± 1
Methyl ethyl ketone	10 ± 1
Toluene	Remainder

4.4.2.2 Test procedure. The brush shall be suspended sideways so that sack of fibers and approximately one-half of the ferrule and block are immersed in the solvent mixture for one hour at standard laboratory conditions. The brush shall be removed and examined as follows: As soon as the brush is removed from the solvent, the ferrule shall be examined for wrinkling, blistering, and separation of the coating. The brush shall then be dried for 2 hours at standard laboratory conditions and the coating re-examined for softening or dulling. As soon as the brush is removed from the solvent, the block shall be examined for wrinkling, blistering, and separation of the coating. The brush shall then be dried for 2 hours at standard laboratory conditions and the coating re-examined for softening or dulling.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or commercial, as specified (see 6.2).

5.1.1 Level A. Each brush shall be wrapped in kraft paper, secured in place with tape or placed in a wallet type envelope, sleeve or bag of kraft paper or polyethylene. The envelope, sleeve or bag shall be secured in accordance with industry practice. Six brushes of like description shall then be packaged in a close-fitting box conforming to PPP-B-636, class weather resistant, style optional. Prior to closure of the boxes, napthalene in the form of balls or flakes shall be placed in the box in the quantity and fashion considered to be industry practice. Closure and waterproof sealing of the boxes shall be in accordance with the appendix to PPP-B-636.

5.1.2 Commercial. The brushes shall be preserved and packaged in accordance with normal commercial practice. The complete package shall be designed to protect the brushes against damage during shipment, handling and storage.

5.2 Packing. Packing shall be level A or commercial, as specified (see 6.2).

5.2.1 Level A. Six unit packages (48 brushes) of like description packaged as specified in 5.1.1 shall be packed in a close-fitting box conforming to PPP-B-636, class weather resistant, style optional. Closure and waterproof sealing of the boxes shall be in accordance with the appendix to PPP-B-636. Alternatively, cleated plywood, wire bound or nailed wood boxes shall be acceptable shipping containers when lined with a waterproof barrier material. The edges of the barrier material shall be sealed with waterproof tape or adhesive.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:06Z
Check the source to verify that this is the current version before use.

5.2.2 Commercial. The brushes of like description, packaged as specified in 5.1.2, shall be packed in fiberboard boxes to insure delivery at destination, to provide for redistribution by the initial receiving activity, and shall be acceptable by common carrier under National Motor Freight Classification or Uniform Freight Classification.

5.3 Marking. Packages and shipping containers shall be marked as specified in the contract or order.

6. NOTES

6.1 Intended use. This specification covers brushes used primarily for painting metal roofs.

6.2 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Levels of packaging and packing required (see 5.1).

Preparing Activity:

GSA-FSS

CIVIL AGENCY COORDINATING ACTIVITIES:

GSA-FSS
JUS-FPI
COM-NBS,CPS
GPO
VA-DMS
USPS-POS
DCG-DC GOV'T



FIGURE 1

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See Section 2 of this specification to obtain extra copies and other documents referenced herein. Price cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:06Z
Check the source to verify that this is the current version before use.