INTERIM AMENDMENT

TO

FEDERAL SPECIFICATION

BRUSHES, SANITARY

H-B-481C
INT AMD 1
June 8, 1967

This interim amendment was developed by General Services Administration, Federal Supply Service, Washington, D. C. 20406, based upon currently available technical information. It is recommended Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this amendment as a valid exception to Federal Specification H-B-481c, dated August 31, 1965.

PAGE 1

Paragraph 1.2.1: Delete "Type III - Twisted-in wire, straight brush head, hog bristle" and substitute: "Type III - Twisted-in wire, straight brush head.

Class 1 - Hog bristle.
Class 4 - Nylon filament".

PAGE 2

Paragraph 3.3.1, second sentence: Delete and substitute: "The moisture content of the wood blocks, prior to use in the fabrication of handles shall be not less than 8 percent or more than 12 percent (see 4.3.2.)".

Paragraph 3.3.3.4: Delete and substitute: "3.3.3.4 Nylon. The nylon filament shall be black crimped filament, .012 inch diameter, conforming to class N, type III of Int. Amend. 1 to H-S-951 with a HD (Deep) crimp frequency of 13 and an amplitude, HD (Deep), of .010 inch".

Paragraph 3.3.3.5: Delete and substitute: 3.3.3.5 Polypropylene. The polypropylene filament shall be black, crimped filament, .012 inch diameter, conforming to class P, type III of H-S-951 with a No. 10 medium crimp frequency and an amplitude of 0.022 inch".

Paragraph 3.3.3.6: Delete in its entirety.

PAGE 4

Paragraph 3.4.3.1: Delete and substitute: "3.4.3.1 Brush part. Type III brushes shall have a straight brush part constructed of hog bristle or nylon, as specified (see 6.2). The bristle or filament shall be held at the center within the twists of 0.104 inch diameter single strand, steel brush handle wire specified in 3.3.2.1. The brush part shall project perpendicular to the twisted wire forming a spiral-wound shape. The ends of the twisted wire shall be turned back toward the handle end to form a fan-shaped end with the wire ends recessed within the brush part".

FSC 7920

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:06Z
Check the source to verify that this is the current version before use.

TABLE III, add the following at end of table:

Components	Ounces per brush (minimum)	Dimensions (inches)
Nylon, weight	1.00	----------

PAGE 6

Paragraphs 4.3.1.2 and 4.3.1.3: Delete in their entirety.

Paragraph 4.3.2: Delete and substitute: "4.3.2 Moisture content of wood. The moisture content of wood blocks shall be determined in accordance with MIL-W-6110. A certificate of compliance covering the moisture content of wood blocks ultimately used in the fabrication of handles shall be submitted by the supplier of brushes with each shipment or lot of brushes".

Paragraph 4.3.3.3, first sentence: Delete "4.4.7" and substitute "4.4.5".

PAGE 7

Paragraph 4.4.1, line 4: Delete "3.3.1" and substitute "3.3.3".

Paragraph 4.4.5, line 5: After the word "brush" insert the word "part".

Paragraphs 4.4.6 and 4.4.7: Delete in their entirety.

PAGE 8

Paragraph 6.5: Delete in its entirety.

GSA DC 67-19756

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:06Z
Check the source to verify that this is the current version before use.