H-B-00571B (GSA-FSS)
June 2, 1969
INTERIM REVISION OF
Fed. Spec. H-B-571a
June 30, 1941

INTERIM FEDERAL SPECIFICATION

BRUSH, SHAVING

This Interim Federal Specification was developed by General Services Administration, Federal Supply Service, Washington, D.C. 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this Interim Federal Specification as a valid exception to Federal Specification H-B-571a, dated June 30, 1941.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers brushes for applying soap lather for shaving purposes.

1.2 Classification.

1.2.1 Types. Shaving brushes covered by this specification shall be of the following types, as specified (see 6.1):

Type I - Plastic ferrule with wood or plastic handle.
Type II - One-piece plastic handle and ferrule.

1.2.2 Classes. Shaving brushes covered by this specification shall be of the following classes, as specified (see 6.1):

Class 1 - Bleached white solid hog bristle.
Class 2 - Unbleached white or unbleached yellow solid hog bristle.
Class 3 - Pure badger hair.
Class 4 - Synthetic filament.

2. APPLICABLE DOCUMENTS

2.1 Specifications and standards. The following documents of the issue in effect on date of invitation to bid or request for proposal form a part of this specification to the extent specified herein.

Federal Specifications:

H-S-951 - Synthetic Filaments for Brushes; General Specifications for.
R-N-91 - Naphthalene, Technical.
PPP-B-566 - Boxes, Folding, Paperboard.
PPP-B-665 - Boxes, Paperboard, Metal-Stayed (Including Stay Material).
PPP-B-676 - Boxes, Setup.

Federal Standards.

Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).

FSC 8530

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:06Z
Check the source to verify that this is the current version before use.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402.)

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, Washington.)

(Federal Government activities may obtain copies of Federal Specifications, Standards and Handbooks and the Index of Federal Specification and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by the contractor in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply:

Code of Federal Regulations, Title 42 - Public Health, Section 72.21 - Interstate Quarantine Regulations.

(Application for copies should be addressed to the Office of the Federal Register, National Archives and Records Service. General Services Administration, Washington, D.C. 20402)

American Society for Testing and Materials (ASTM) Standards:

ASTM D 9 - Standard Definitions of Terms Relating to Timber.
ASTM D 2016 - Test for Moisture Content of Wood.

(Applications for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania 19103.)

National Classification Board:

National Motor Freight Classification Rules.

(Application for copies should be addressed to the National Classification Board, 1616 P Street, N. W., Washington, D.C. 20036.)

Uniform Classification Committee:

Uniform Freight Classification Rules.

(Application for copies should be addressed to the Uniform Classification Committee, 202 Union Station, Chicago, Illinois 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Materials.

3.1.1 Bristles. The bristles in classes 1 and 2 brushes shall be solid hog bristles, free from reconditioned bristles and adulterants, straightened so that they will not twist or curl, and sterilized (see 3.7) In addition, bristles shall meet the following requirements for each class as specified in 3.1.1 1 and 3 1.1.2.

3.1 1.1 Class 1 Hog bristles in class 1 brushes shall be bleached white

3 1 1.2 Class 2. Hog bristles in class 2 brushes shall be undyed, unbleached white, or undyed, unbleached yellow.

3.1 2 Hair The hair in class 3 brushes shall be undyed, unbleached, solid badger hair (see 3 7).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:06Z
Check the source to verify that this is the current version before use.

3.1.3 Synthetic filament. The synthetic filament in class 4 brushes shall be a synthetic polymeric amide in compliance with the requirements for class N - nylon, Type II - level in Federal Specification H-S-951. The filament shall be natural color, undyed. The diameter of the filament shall be 0.005 ± 0.001 inch.

3.1.4 Wood. The wood handle of type I brushes shall be close-grain hardwood such as beech, birch, or maple, free from decay, knots, wanes, heart center, and brashness. (See ASTM D 9 - Standard Definitions of Terms Related to Timber.) Prior to fabrication into handles (see 4.2.1.1), the wood shall be dried so that the moisture content shall not be less than 8 percent and not more than 12 percent when tested by the method specified in 4.2.1.1.

3.1.5 Coating on wood handle. The coating on the wood handle shall be clear waterprooof lacquer, varnish, or other suitable transparent organic finish in compliance with the requirements in 3.9.

3.1.6 Plastic. The plastic in the handle and ferrules of brushes shall be an organic polymeric or copolymeric material formulated to meet the requirements of this specification. The material shall be free from disagreeable odor.

3.1.7 Metal. The metal in the ring used in the ferrule of type I brushes shall be a corrosion resisting material such as aluminum alloy, zinc alloy, or other nonferrous metal.

3.1.8 Setting compound. The setting compound for securing the bristle, hair, or filament in the ferrule of shaving brushes shall be an epoxy resin or other suitable setting compound that will not become brittle and complies with the requirements in 3.9.

3.1.9 Bonding agent. The bonding agent for joining the brush parts shall be a waterproof synthetic resin adhesive or other suitable bonding agent which will result in a finished brush meeting the requirements in 3.9.

3.2 Design. The brushes shall be designed to be gripped in the fingers and stand in an upright position when resting on the end. The brush head shall have a slightly domed top. Suitable designs are shown in figure 1.

3.3 Construction.

3.3.1 Type I brushes.

3.3.1.1 Handle and ferrule. The handle and ferrule shall be constructed separately. The handle shall fit neatly into the ferrule and shall be joined to the inside ferrule wall by a bonding agent as described in 3.1.9. The handle and ferrule shall be seamless. The ferrule shall be reduced in circumference at the brush end to fit tightly over a metal ring. The metal ring shall completely encircle and secure that portion of the bristle, hair, or filament set in the ferrule and shall be entirely covered by the ferrule. Wood handles shall be smoothly finished and evenly coated with a transparent material as specified in 3.1.5.

3.3.1.2 Set. The butt ends of the bristle, hair, filament shall extend into the ferrule at least 3/8 inch and shall be set to a slightly domed top. The setting compound shall at least fill the metal ring and cover the bristle, hair, or filament at the butt ends so that not less than 1/4 inch is set in the setting compound. The setting compound shall not extend beyond the brush end of the ferrule.

3.3.2 Type II brushes.

3.3.2.1 Handle and ferrule. The plastic handle and ferrule shall be seamless one-piece construction except for a flat or concave top cap joined to the end of the handle by a bonding agent as described in 3.1.9.

3.3.2.2 Ring. The use of the ring construction (see 3.3.1.1) in type II brushes shall be at the option of the manufacturer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:06Z
Check the source to verify that this is the current version before use.

3.3.2.3 Set. The butt ends of the bristle, hair, or filament shall extend into the ferrule at least 1/4 inch and shall be set to a slightly domed top. The setting compound shall secure that portion of the bristle, hair, or filament inside the ferrule and shall fill the ferrule to a depth of at least 1/2 inch measured from the brush end of the ferrule, but shall not extend beyond the ferrule.

3.4 Dimensions. The dimensions of the brushes shall be as specified in table I.

TABLE I. Dimensional requirements for shaving brushes

Brush component	Dimensions, minimum, inch	
	Type I	Type II
Handle:		
Length outside of ferrule	1-7/8	--
Set into ferrule	5/16	--
Diameter, inside, ferrule end	13/16	--
Diameter, shoulder, outside, at ferrule	1-1/8	1-1/4
Diameter, inside, flat or concave end	15/16	1-1/4
Diameter at narrowest point, outside	5/8	1-1/16
Handle and ferrule length, one-piece, overall	--	1-7/8
Brush length, overall	4-9/16	3-3/4
Ferrule:		
Length	13/16	13/16
Diameter, outside, at widest point	1-1/16	1-1/4
Diameter, inside at brush part	3/4	3/4
Diameter, inside (body)	13/16	--
Metal ring:		
Thickness	0.025	See 3.3.2.3
Width	0.25	See 3.3.2.3
Bristle, hair, or filament:		
Length outside of ferrule	1-7/8	1-7/8
Set into ferrule	See 3.3.1.2	See 3.3.2.3
Plastic wall thickness:		
Handle and ferrule	0.09	0.075
Cap	--	0.060

3.5 Color and finish of plastic. Unless otherwise specified, the color of plastic handles and plastic ferrules shall be black. The plastic shall have a smooth polished finish.

3.6 Weight of bristle, hair, or filament. The weight of the bristle, hair, or filament shall be as specified in table II when determined as described in 4.3.2.

TABLE II. Weight of bristle, hair, or filament

Class	Weight, minimum, oz.	
	Type I	Type II
Bristle, classes 1 and 2	7/16	3/8
Hair, class 3	1/4	1/4
Synthetic filament, class 4	7/16	7/16

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:06Z
Check the source to verify that this is the current version before use.

3.7 Quarantine Regulations. Brushes and brush materials shall meet the requirements of the Code of Federal Regulations, Title 42, Section 72.21, or later effective issues, on Interstate Quarantine.

3.8 Cleanness of finished brush. After testing the bristle, hair, or filament as specified in 4.3.3, the wash solution shall be clear and free of sediment.

3.9 Performance characteristics.

3.9.1 Resistance to impact. When the brush is subjected to impact as specified in 4.3.4, (1) the material in the handle and ferrule shall not crack, chip, break, or deform in any way that would impair the serviceability of the brush, (2) the bonding agent shall not permit loosening or separation of the handle and ferrule, (3) the varnish or lacquer shall not crack, chip, and peel, and (4) the setting compound shall not permit loosening of the bristle, hair, or filament.

3.9.2 Resistance to hot water. After immersion in hot water, 54° ± 2° C. (130° ± 3.6° F.) as described in 4.3.5, (1) the adhesive shall not soften or show any signs of deterioration that would permit turning, loosening, or separation of brush parts, (2) plastic handles and ferrules shall not soften or deform in any way that would impair the serviceability of the brush, (3) wood handles shall not warp or crack, (4) the varnish or lacquer on the wood handles shall not crack, wrinkle, blister, peel, or soften, and (5) each specimen of bristle, hair, or filament shall remain firmly embedded in the setting compound when subjected to a pulling force of 8 pounds as described in 4.3.6.

3.10 Identification marking. Marking shall be as specified in the Code of Federal Regulations (see 3.7).

3.11 Workmanship. Brushes shall be free from defects which may affect their appearance, serviceability, or durability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Sampling for inspection and acceptance. Sampling for inspection and acceptance shall be performed in accordance with the provisions set forth in MIL-STD-105 except where otherwise indicated hereinafter.

4.2.1 Component and material inspection. In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with all requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

4.2.1.1 Moisture content of wood handles. Prior to fabrication into handles, test for moisture content in accordance with method B of ASTM D 2016 shall be performed on each lot of wood offered for inspection to determine compliance with 3.1.4. The sample unit shall be one piece of wood. Two determinations shall be made on each sample unit and the results averaged. The inspection level shall be S-2 with an acceptable quality level (AQL) of 2.5 defects expressed in terms of defects per 100 units.

4.2.2 End item inspection.

4.2.2.1 Lot. For the purpose of examination and testing, a lot shall consist of all brushes of the same type and class presented for delivery at one time.

4.2.2.2 Examination for visual defects and for odor. Examination shall be made of the brushes for defects listed in table III. The inspection level shall be II, acceptable quality level (AQL) 4.0, expressed in terms of defects per 100 units. The unit for examination shall be one brush. If the number of defects in the sample for inspection exceeds the acceptance number, the entire lot of brushes shall be considered as having failed to meet the requirements of the specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:06Z
Check the source to verify that this is the current version before use.

TABLE III. Classification of defects

Examination	Defects
Wood handle, type I	Not free from defects listed in 3.1.4. Not close-grain hardwood. Not natural color. Cracked or split. Not coated with transparent lacquer or varnish. Coating not smooth and even. Coating tacky. Will not stand upright on end. Cannot be gripped comfortably.
Plastic handle, type I	Finish not smooth and polished. Sharp edges. Will not stand upright on end. Cannot be gripped comfortably. Disagreeable odor.
Plastic ferrule, type I	Color not as specified (see 3.5). Not seamless. Sharp edges. Disagreeable odor.
Bristle, hair, or filament, types I and II	Not specified class. Does not fill ferrule. Not slightly domed. Loose. Setting compound extends outside ferrule.
Handle and ferrule, type I	Not securely bonded. Can be moved or separated.
Handle and ferrule, type II	Not seamless plastic in one piece. Finish not smooth and polished Sharp edges. Color not as specified (see 3.5). Cap missing or loose. Disagreeable odor.

4.2.2.3 Dimensional examination requiring destruction of brush. Examination shall be made of brushes for the dimensions listed below to determine compliance with the applicable requirements in table I, or as otherwise indicated. The unit for examination shall be one brush. The inspection level shall be S-2, acceptable quality level (AQL) 2.5, expressed in terms of percent defective. If any brush in the sample for inspection fails to meet any of the requirements for which examination is made, the brush shall be considered as defective. If the number of defective brushes in the sample for inspection exceeds the acceptance number in MIL-STD-105, the entire lot of brushes shall be considered as having failed to meet the requirements of this specification.

1. Set of handle into ferrule, minimum, inch.
2. Extension of bristles into ferrule, minimum, inch.
3. Set of bristles in ferrule, minimum, inch.
4. Depth of setting compound (see 3.3.1.2 and 3.3.2.3).
5. Thickness of metal ring, minimum, inch
6. Width of metal ring, minimum, inch.
7. Diameter of ferrule, inside (body), minimum, inch (Type I).

4.2.2.4 Nondestructive dimensional examination. Examination shall be made of brushes for compliance with the dimensional requirements in table I not covered in 4.2.2.3 The unit for examination shall be one brush. The inspection level shall be S-3, acceptable quality level (AQL) 6.5 expressed in terms of defects per 100 units. If the number of defects in the sample for inspection exceeds the acceptance number in MIL-STD-105, the entire lot of brushes shall be considered as having failed to meet the requirements of the specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:06Z
Check the source to verify that this is the current version before use.

4.2.2.5 Sampling for test. Brushes shall be tested for compliance with the specified requirements in 3.6, 3.8, 3.9.1 and 3.9.2. The test unit shall be four brushes. The inspection level shall be S-2 and the acceptable quality level (AQL) 2.5, expressed in terms of percent defective. If any brush in the test unit fails to meet any of the requirements for which tests are made, the test unit shall be considered defective. If the number of defective test units in the sample exceeds the acceptance number of MIL-STD-105, the entire lot of brushes shall be considered as having failed to meet the requirements of the specification.

4.2.2.6 Examination of preparation for delivery. An examination shall be made to determine that packaging, packing, and marking requirements, as specified below, are complied with. The sample unit shall be one shipping container fully prepared for delivery. The inspection level shall be S-2, AQL 4.0, based on defects per 100 units.

Examination	Defects
Packaging	Unit package not as specified. Intermediate container not as specified. Naphthalene balls or flakes missing or not as specified.
Packing	Breaks, tears, holes, or other defects which could cause damage to or loss of contents. Waterproof tape, when applicable, missing or not as specified. More or less than quantity of units or intermediate containers.

4.3 Tests. Unless otherwise specified herein tests shall be made at room temperature, 27° ± 5°C. (80° ± 9°F.).

4.3.1 Synthetic filament. The filaments shall be tested as specified in H-S-951 for compliance with the requirements therein for melting point, specific gravity, and moisture absorption.

4.3.2 Weight of bristle, hair, or filament.

4.3.2.1 Removal of setting compound. The ferrule and handle shall be removed from the bristle, hair, or filament and setting compound. The setting shall be broken, without injury to the bristle, hair, or filament, into small pieces. The butt ends of the bristle, hair, or filament shall be immersed in a suitable solvent to a depth of 1/8 inch above the setting compound. For epoxy resin, a solvent such as methylene chloride or dimethyl formamide will dissolve the setting compound. For other setting compounds such as vulcanized rubber, chloroform is suitable. After soaking for approximately 15 minutes, the bristle, hair, or filament shall be removed from the solvent and the butt ends grasped between the forefinger and thumb and gently rolled back and forth. The setting compound will become loose and can be shaken off. This treatment shall be repeated until the setting compound has been entirely removed. Usually four treatments are sufficient. After the setting compound has been removed, the solvent shall be allowed to evaporate and the bristle or hair shall be conditioned as described in 4.3.3.2. The weight of the nylon filament shall be determined on the unconditioned filaments.

4.3.2.2 Conditioning. The bristle or hair shall be conditioned for not less than 16 hours in air at a relative humidity of 50 ± 4 percent and at a temperature of 23° ± 1.1°C. (73.5° ± 2°F.). The weight of the bristle or hair shall be determined in the same atmosphere.

4.3.3 Cleanness test. The bristle, hair, or filament shall be cut from one sample brush so as to include as much of the length out as possible and yet exclude the portion secured in the setting compound, and immersed in 250 cc. of distilled water for 5 minutes. The mass shall be agitated thoroughly to separate dirt and impurities from the bristle, hair, or filament, strained through a piece of clean muslin, and the wash water allowed to stand for 24 hours in a covered container at a temperature of 21° to 24°C (69.8° to 75.2°F.). At the end of the 24-hour period, the wash water shall be examined for conformance with 3.8.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:06Z
Check the source to verify that this is the current version before use.

4.3.4 Resistance to impact. One brush from the test unit shall be dropped five times from a height of approximately 48 inches on a stone or concrete surface so that the handle strikes the surface each time. After each drop, the brush shall be examined for compliance with 3.9.1.

4.3.5 Resistance to hot water. One brush from the test unit shall be immersed so that the bristle, hair, or filament and ferrule is covered by hot water, 55° ± 1°C. (131° ± 1.8°F.) and allowed to remain in the water for 2 minutes. The brush shall be removed from the water and allowed to rest for 2 minutes. The above procedure shall be repeated until the brush has been immersed a total of five times. At the end of the fifth immersion, the brush shall be removed from the water, allowed to cool for 15 minutes, examined for compliance with 3.9.2 and then tested for efficiency of the setting compound as specified in 4.3.6.

4.3.6 Efficiency of setting compound. The specimen for test shall consist of approximately 1/8 of the bristle, hair, or filament in the brush. Two specimens shall be tested, one at approximately the center of the brush and one at the periphery. The handle shall be secured in a suitable clamping device and the specimen in another so that the ends of the bristle, hair, or filament are evenly distributed and so as to prevent distortion or cutting. A pulling force of 8 pounds shall be applied by means of a scale or weight in a direction tending to pull the specimen from the ferrule. If either specimen fails to meet the requirement in 3.9.2, the brush from which the specimen was taken shall be considered defective.

5. PREPARATION FOR DELIVERY

5.1 Packaging.

5.1.1 Level A or B.

5.1.1.1 Unit packaging. Each shaving brush shall be packaged in a box, wrapper, or bag of the type normally used commercially for the item.

5.1.1.2 Intermediate packaging. Twelve (12) shaving brushes, of one type, shall be packaged in a closed-fitting box conforming to PPP-B-566, PPP-B-665, or PPP-B-676. Each package of classes 1, 2, and 3 brushes shall contain 3 balls or equivalent of naphthalene flakes, conforming to R-N-91, to protect the brushes from moths.

5.1.3 Standard pack (civil agency procurements). The standard pack for civil agency procurements shall be as specified in paragraphs 5.1.1.1 and 5.1.1.2.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.1).

5.2.1 Level A. Twelve (12) intermediate boxes of brushes shall be packed in a close-fitting box conforming to PPP-B-636, class weather resistant. The box shall be waterproofed with tape in accordance with the appendix to the box specification.

5.2.2 Level B. Twelve (12) intermediate boxes of brushes shall be packed as specified in 5.2.1 except that the box shall be class domestic and waterproofing with tape will not be required.

5.2.3 Level C. Shaving brushes, packaged as specified in 5.1, shall be packed to insure carrier acceptance and safe delivery at destination at lowest rate, in containers complying with the Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

5.3 Marking.

5.3.1 In addition to any special marking required by the contract or order, interior and shipping containers shall be marked in accordance with Federal Standard No. 123 or MIL-STD-129, as applicable.

6. NOTES

6.1 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type and class (see 2.1).
(c) Color of plastic handles and ferrules if other than black (see 3.5).
(d) Level of packaging and packing required (see 5.1 and 5.2)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:06Z
Check the source to verify that this is the current version before use.

6.2 Standard pack for civil agencies. The standard pack requirements in 5.1.3 are intended for use in procurements of stores stock replenishments. Procuring officers should use the standard pack requirements when it is known that the material will be shipped from a supplier to a domestic warehouse, supply depot, or intermediate storage point for temporary storage, subsequent issue, or shipment to eventual user.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:08Z
Check the source to verify that this is the current version before use.



Type I



Type II

FIGURE 1. Shaving brushes

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:06Z
Check the source to verify that this is the current version before use.

GENERAL SERVICES ADMINISTRATION - FEDERAL SUPPLY SERVICE

SPECIFICATION COMMENT SHEET

BUDGET BUREAU NO. 29-R0175

INSTRUCTIONS

This form provides a way for users of this specification to inform the originator of problems encountered in its use. It is not to be used to request changes to accommodate proprietary features All comments will be considered and appreciated, but please do not expect a reply. To comment detach, complete, fold, staple, and mail.

NOTE. Comments on this form do not constitute or imply authorization to waive any part of the document or serve to amend contractual requirements.

1. SPECIFICATION

H-B-00571B - BRUSH, SHAVING

2. CONTRACT NO *(If any)*	3. QUANTITY ON CONTRACT *(Optional)*	4. DOLLAR VALUE *(Optional)*

5. GENERAL NATURE OF PROBLEM *(e.g., inspection difficulties, manufacturers unable to meet tolerances, containers collapse under normal warehousing conditions, etc.)*

6. SPECIFIC REQUIREMENTS AFFECTED *(Include paragraph number and lines of wording)*

7. SPECIFIC PROBLEMS *(e.g. tests in 4.2.2 will not assure that the battery will last required time, temperature ranges in table 2 do not conform to commercially available items.)*

8 RECOMMENDATIONS

9 NAME OF MANUFACTURER ASSOCIATION GOVT AGENCY ETC	10 ADDRESS *(Number, Street, City, State and Zip Code)*

11 NAME AND TITLE OF SUBMITTER	12 DATE

FORM GSA FEB 69 2200

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:06Z
Check the source to verify that this is the current version before use.

FOLD

GENERAL SERVICES ADMINISTRATION

OFFICIAL BUSINESS

POSTAGE & FEES PAID
GENERAL SERVICES ADMINISTRATION

General Services Administration
Federal Supply Service FMSO
Washington, D. C. 20406

FOLD

GSA FORM FEB 69 2200

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:06Z
Check the source to verify that this is the current version before use.