[METRIC]
H-B-731H
December 6, 1994
Superseding
H-B-731G
June 10, 1978

FEDERAL SPECIFICATION

BRUSH, WHITEWASH

The General Services Administration has authorized the use of this federal specification for all federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers whitewash brushes, for the application of whitewash, cemetitious, and casein base paints mainly to paint rough texture wooden and masonry surfaces.

1.2 Classification. Whitewash brushes covered by this specification shall be on one type.

2. APPLICABLE DOCUMENTS.

2.1 The following documents, of the issure in effect on date of invitation for bids, or request for proposal, form a part of this specification to the extent specified herein:

Federal Specification:

PPP-B-1880 -Brushes, Preparation for Delivery of

H-S-951 - Synthetic Filaments for Brushes, General Spec For

(Copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available from the following address: GSA Specifications Section (3FBP-W), Suite 8100, 470 L'enfant Plaza SW, Washington, DC 20407.)

Military Standards:

MIL-STD-105 -Sampling Procedures and Tables for Inspection by Attributes

(Copies of specifications and standards required by contractors in connection with specific acquisition functions should be obtained from the contracting officer.)

2.2 Other Publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shal apoly.

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification

Beneficial comments, recommendations, additions, deletions, clarification, etc., and any data which may improve this document, should be sent to: GSA, Paints and Chemicals Commodity Center, 400 15th Street, S.W., Auburn, WA 98001.

DISTRIBUTION STATEMENT: Approved for public release.
Distribution is unlimited.

FSC 8020

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:07Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the American Trucking Association, Inc., 2200 Mill Rd., Alexandria, VA 22314).

American Society for Testing and Materials:

ASTM D13 – Specification for Spirits of Turpentine

(Application for copies of ASTM Standards should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

3. Materials. The manufacturer is given latitude in the selection of materials and components, as long as the finished item meets all the requirements of this specification..

3.1 Fibers. The fibers for whitewash brushes shall be Tampico.

3.1.1 Block. The block shall be made of close grained hardwood, smoothly finished, or synthetic material with all sprues and runners removed.

3.2 Physical Requirements. Brushes covered by this specification shall conform to the requirements specified in Table 1.

Table 1. Physical Requirements

Block:	
Width, min., mm, (inches)	178 (7)
Thickness, min., mm, (inches)	27 (1-1/16)
Fiber:	
Weight, min., grams, (ounces)	93 (3)
Length outside of block, min., mm, (inch)	76 (3-3/8)
Filling Hole:	
Number, min.	34
Diameter, min., mm, (inch)	6.4 (1/4)
Depth, min., mm, (inch)	8 (5/16)
Staples:	
Diameter of wire, min., mm, (inch)	1 (0.040)
Tennon:	
Length, min., mm, (inch)	76 (3)
Taper, mm., (inch)	28..6 to 15.9 (1-1/8 to 5/8)

3.3 Marking for identification. Unless otherwise specified (see 6.2), in addition to any special marking required by the contract or order, each brush shall be stamped or otherwise permanently marked with the manufacturer's name or trademark and National Stock Number.

3.4 Workmanship. The finished brushes shall be clean, well made, and free from any defects which may affect appearance or serviceability. There shall be no sharp edges, burrs or other imperfections. The brushing part shall be trimmed evenly and uniformly to the finished length outside the ferrule.

4. QUALITY ASSURANCE PROVISIONS

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:07Z
Check the source to verify that this is the currentversion before use.

4.1 Responsibility for inspection. Unless otherwise specified in the contract or order, the supplier is responsible for the performance of all inspection requirements specified herein, using facilities acceptable to the Government. The Government reserves the right to perform any inspection herein, when deemed necessary to assure that the brushes conform to prescribed requirements.

4.2 Inspection of preparation for delivery. An examination shall be made to determine compliance with 3.2 and section 5 of this specification. The examination shall be conducted as specified in PPP-B-1880.

4.3 Inspection of the end item. Lots shall be assembled and randomly sampled in accordance with MIL-STD-105, inspection level II, with an acceptable quality level (AQL) OF 2.5 percent defective. Sample brushes shall be examined for the following attributes:

Fiber
Construction and assembly
Set
Trim
Workmanship
Identification markings

Any brush in the sample containing one or more visual or dimensional defects shall be considered a defective brush.

4.3.1 Sampling for testing of the end item. A random sample of brushes shall be selected from each lot in accordance with MIL-STD-105, inspection level S-2, with an acceptable quality level (AQL) of 2.5 percent defective.

4.4 Testing procedure. Samples selected in accordance with 4.3.1 shall be subjected to the following tests. Failure to pass any test shall be cause for rejection of the lot. All tests shall be evaluated for conformance to the requirements in section 3.

4.4.1 Weight of fiber. The fiber weight shall be in compliance with physical requirements in Table 1.

4.4.2 Pull test. A group of fibers, 6 mm (1/4 inch) in diameter, shall be given a tensile pull of 4.5 kg. (10 lbs) in a direction away from the block. Repeat this tensile pull test, at random places, one time for each 25 mm (1-inch) of brush width.

5. PREPARATION FOR DELIVERY.

5.1 Preservation, packaging, packing and marking. The preservation, packaging, packing, and marking shall be in accordance with PPP-B-1880. The level of packaging and packing shall be A, B, C or otherwise specified in the contract or order (see 6.2). The marking shall be civil, military, or as specified (see 6.2).

6 NOTES

6.1 Intended use. The brushes covered by this specification are used for the application of whitewash calcimine coatings and casein paints over large, flat areas.

6.2 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(a) Title, number, and date of this specification
(b) Type, grade, and size required (see 1)
(c) Levels of packaging and packing required, (see 5.1)
(d) Marking required (see 5.1)

PREPARING ACTIVITY

GSA - FSS

CIVIL AGENCIES COORDINATING ACTIVITY

GSA - FSS
JUS - FPI

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:07Z
Check the source to verify that this is the current version before use.