INCH-POUND
MIL-DTL-17/225
AMENDMENT 3
22 January 2002
SUPERSEDING
AMENDMENT 2
21 October 1999

DETAIL SPECIFICATION SHEET

CABLE, RADIO FREQUENCY, FLEXIBLE, COAXIAL, 50 OHMS, LOW SMOKE, LOW LOSS DIAMETER .590

This amendment forms a part of MIL-DTL-17/225, dated 26 August 1998, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Table I, Construction detail column; delete “Solid bare copper” and substitute “Copper covered aluminum”.

PAGE 2

* Engineering information, Continuous working voltage; delete “3,750 V rms, maximum” and substitute “2,800 V rms, maximum”.

Requirements, Environmental and mechanical, Out-of-roundness; delete “Applicable” and substitute “Not applicable”.

PAGE 3

* Electrical, Voltage withstanding; delete “6,250 V rms, minimum” and substitute “5,000 V rms, minimum”.

* Electrical, Corona extinction voltage; delete “5,000 V rms, minimum” and substitute “3,750 V rms, minimum”.

NOTE: The margin of this amendment is marked with an asterisk to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the material notations and relationship to the last previous amendment.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 6145-2322-006)

Review activities:
Army - AR, AT, CR4, MI
Navy - AS, MC, OS, SH
Air Force - 19, 99
NASA - NA

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:36Z
Check the source to verify that this is the current version before use.