INCH-POUND
MIL-DTL-17/229
AMENDMENT 2
17 December 2002
SUPERSEDING
AMENDMENT 1
22 January 2002

DETAIL SPECIFICATION SHEET

CABLE, RADIO FREQUENCY, FLEXIBLE, COAXIAL,
75 OHMS, LOW SMOKE, LOW LOSS DIAMETER .242

This amendment forms a part of MIL-DTL-17/229, dated 8 June 2000, and
is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

Engineering information, Continuous working voltage; delete “1,200 V rms, maximum” and substitute 900 V rms, maximum.”

* Operating temperature range; delete “-30° to +85°C” and substitute “-30°C to +105°C”.

Requirements, Environmental and mechanical, Adhesion of conductors, Inner conductor to core; delete
* “2 pounds, minimum; 15 pounds maximum” and substitute “5 pounds, minimum; 50 pounds, maximum”.

PAGE 3

Electrical, Voltage withstanding; delete “1,875 V rms, minimum” and substitute “1,500 V rms, minimum.

Electrical, Corona extinction voltage; delete “1,500 V rms, minimum” and substitute “1,125 V rms, minimum.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 6145-2349-010)

Review activities:
Army - AR, AT, CR4, MI
Navy - AS, MC, OS, SH
Air Force - 19, 99
NASA -NA
DLA - IS

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:37Z
Check the source to verify that this is the current version before use.