MIL-L-24532(SH)
AMENDMENT-1
8 February 1980

MILITARY SPECIFICATION

LIGHT, MARKER, DISTRESS, FLOATING,

FLASHING, AUTOMATIC

This amendment forms a part of Military Specification MIL-L-24532(SH), dated 17 May 1976.

PAGE 2

3.3.2.2: Add as second sentence: "(Ultraviolet stabilized polycarbonate may be used.)"

3.3.2.5.1, line 3: Delete "± 5 percent".

PAGE 3

3.3.2.7: Delete and substitute:

"3.3.2.7 Mounting bracket. The mounting bracket shall hold the light in the inverted position and prevent free movement of the light when properly secured within the bracket. With the bracket mounted in its normal position on a vertical supporting surface, the inserted light shall separate from the bracket with a pull of not less than 20, nor more than 50 pounds, when such a pull is applied horizontally and directly away from the vertical supporting device. Metal parts of the mounting bracket shall be painted gray. Plastic parts of the mounting bracket shall be gray in color. The mounting bracket shall prevent scratching of the lens at any point where the lens of the light could make contact with the bracket."

3.3.2.7.1: Delete.

3.5.3, lines 3 and 4: Delete "3.6.1, 3.6.2, and 3.6.4 through 3.6.6" and substitute "3.5.1, 3.5.2, and 3.5.4 through 3.5.6".

PAGES 7 through 11

Figures 1 through 5: Add "Unless otherwise specified, dimensional tolerances shall be plus or minus 1/64 inch for fractions and plus or minus 0.005 inch for decimals."

PAGE 8

Figure 2: Add "Angle tolerances shall be plus or minus 1/2 degree."

Preparing activity:
Navy - SH
(Project 6230-N252)

FSC 6230

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T22:24Z
Check the source to verify that this is the current version before use.