INCH-POUND
MIL-PRF-24236/19J
AMENDMENT 1
25 June 2003

PERFORMANCE SPECIFICATION SHEET

SWITCHES, THERMOSTATIC, (BIMETALLIC), (SUBMINIATURE),
TYPE I, HERMETICALLY SEALED,
SINGLE POLE, SINGLE THROW (SPST), 1 AMPERE AND LOW LEVEL

This amendment forms a part of MIL-PRF-24236/19J, dated 22 January 2001, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

Class: Delete and substitute:

"Class: 6, vibration 10 to 2,000 Hz, 30 G.
Notes:
1. Devices with open on temperature rise should not be subjected to vibration while at temperatures of 75°F or more below the opening temperature.
2. Devices with close on temperature rise should not be subjected to vibration while at temperatures of 75°F or more above the opening temperature. "

Add after Low level paragraph:

"Contact resistance: In accordance with MIL-PRF-24236, except close on temperature rise devices with set points greater than 175°F shall not exceed 100 milliohms."

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Review activities:
Army - AR, AT, AV, MI
Navy - AS, MC, OS, SH
Air Force - 99

Preparing activity:
DLA - CC

(Project 5930-1775-02)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T20:31Z
Check the source to verify that this is the current version before use.