NOTE: The document identifier and heading have been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

INCH-POUND
MIL-PRF-24236/24C
AMENDMENT 2
10 November 1995
SUPERSEDING
AMENDMENT 1
31 December 1992

PERFORMANCE SPECIFICATION SHEET

SWITCHES, THERMOSTATIC, (BIMETALLIC), SUBMINIATURE, TYPE I, HERMETICALLY SEALED, SINGLE POLE, DOUBLE THROW (SPDT), 2 AMPERES AND LOW LEVEL

This amendment forms a part of MIL-S-24236/24C, dated 25 July 1990, and is approved for use by all Departments and Agencies of the Department of Defense

PAGE 1

FIGURE 1: Configuration A, terminal height dimension:, delete ".285" and substitute ".285 MAX".

PAGE 2

FIGURE 1: Configuration A1, dimensions, delete "1.260/1.200" and substitute "1.260/1.160".

PAGE 3

FIGURE 1: Configuration A3, stud length dimension:, delete and substitute ".160 ± .007".

FIGURE 1: Configuration A3, dimensions:, delete ".460/.375" and substitute ".437 MAX".

The margins of this amendment are marked with an asterisk to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire contact irrespective of the marginal notations and relationship to the last previous amendment.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Preparing activity:
DLA - ES

(Project 5930-1589)

Review activities:
Army - AR, AT, AV, ME, MI
Navy - MC. OS

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T20:33Z
Check the source to verify that this is the current version before use.