INCH-POUND
MIL-PRF-24236/25D
1 October 2010
SUPERSEDING
MIL-PRF-24236/25C
3 September 1999

PERFORMANCE SPECIFICATION SHEET

SWITCHES, THERMOSTATIC, (BIMETALLIC TYPE I, HERMETICALLY SEALED SINGLE POLE, SINGLE THROW (SPST), 2 AMPERES

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the switches described herein shall consist of this specification sheet and MIL-PRF-24236.





FIGURE 1. Switches.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T20:34Z
Check the source to verify that this is the current version before use.



Inches	mm	Inches	mm
.052	1.32	.648	16.46
.072	1.83	.665	16.89
.360	9.14	.772	19.61
.390	9.91	.990	25.15
.394	10.01	1.010	25.65
.50	12.7	12.00	304.8

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are based upon 1.00 inch = 25.4 mm.

FIGURE 1. Switches - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T20:34Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1 and table 1.

Operating temperature range: -10°F to +400°F.

Class: Class 4, except vibration 10 - 2,000 Hz, 10 g's.

Mounting: See figure 1.

Weight: Approximately .22 pound.

Dielectric withstanding voltage: 70,000 ft - 350 V ac.

Operating temperature and tolerance: See tables II, III, and IV.

Electrical ratings: See table VI.

Endurance: See table VI.

QUALIFICATION:

Group submission: See table VII.

Part number: Consists of the prefix "M24236/25-" and a five letter code.

EXAMPLE:




TABLE I. Configuration and contact action.

	Configuration				Contact Action
	A	B	C	D	
Code	A	C	E	G	Close on increasing temperature (open decreasing on temperature)
Code	B	D	F	H	Close on decreasing temperature (open on increasing temperature)

NOTE: The manufacturer calibrates these switches by setting the closing temperature. The opening temperature will then depend on the differential selected (see table IV).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T20:34Z
Check the source to verify that this is the current version before use.

TABLE II. High temperature setting to the nearest 25°F.

Temperature (°F)	Code	Temperature (°F)	Code
0	A	225	K
25	B	250	L
50	C	275	M
75	D	300	N
100	E	325	P
125	F	350	Q
150	G	375	R
175	H	400	S
200	J		

TABLE III. Temperature setting to the nearest 5°F.

Unit	Tolerance		
	1/ ±3°F	±4°F	±5°F
-10	A	F	L
-5	B	G	M
0	C	H	N
+5	D	J	P
+10	E	K	Q

1/ Available to 250°F only.

TABLE IV. Temperature differential.

Closing temperature range	Code	Available differential
+10°F to 250°F	A	2-4°F
	B	2-5°F
-251°F to 400°F	C	3-7°F

TABLE V. Probe length.

Code	Length ±.030	Code	Length ±.030
A	1.5	F	4.0
B	2.0	G	4.5
C	2.5	H	5.0
D	3.0	J	5.5
E	3.5	K	6.0

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T20:34Z
Check the source to verify that this is the current version before use.

TABLE VI. Electrical submission.

Load	28 V dc	115 V ac, 60 Hz	Life cycle
	(amperes)	(amperes)	
Resistive	2.0	2.0	250,000
Inductive	1.0	1.5	250,000
Lamp	1.0	0.5	250,000

TABLE VII. Group submission.

Configuration	Number of samples required	Tests	Extent of approval
A B	3 each	Visual and mechanical examination, torque, vibration, shock, and seal	All 1/
C D	2 each	Torque	

1/ Qualification is based on prior approval of MIL-PRF-24236/20.

Reference Documents:
MIL-PRF-24236
SAE-AS22759/9

The margins of this specification are marked with vertical lines to indicate where modifications from this revision were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Custodians:
Army - CR
Navy - EC
Air Force – 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5930-2009-034)

Review activities:
Army – AR, AT, AV, MI
Navy – MC, SH
Air Force – 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.daps.dla.mil/ .

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T20:34Z
Check the source to verify that this is the current version before use.