MIL-B-60298A(MU)
AMENDMENT 3
28 April 1972
SUPERSEDING
AMENDMENT 2
31 December 1971

MILITARY SPECIFICATION

BATTERY, NICKEL - CADMIUM, VENTED: 10541198

This amendment forms a part of Military Specification MIL-B-60298A(MU), dated 18 June 1970.

Page 3, paragraph 3.5.1: Delete and substitute the following:

Full capacity charge.- From an initial terminal voltage of 7.0 ± 0.2 volts obtained while under a discharge load specified in 3.5.2.1 and 3.5.2.2, each section of the battery shall be capable of attaining the voltage specified below when recharged at a constant current of 500 ma to 120% of the 1.5 ampere hour capacity of section 10541201 and 10558189 and the 2.0 ampere hour capacity of section 10541200.

11.9 ± 0.7V	at	70°F
11.2 ± 0.7V	at	155°F
12.3 ± 0.7V	at	-25°F

* Page 3, paragraph 3.4.4.1: Delete and substitute the following:

Operation.- The Battery shall meet the requirements of 3.5.2.1 when elevated from ground level to the conditions encountered at an altitude of 10,000 feet above sea level within a period of 10 minutes and maintained at these conditions while meeting these requirements.

* Page 3, paragraph 3.5: Delete and substitute the following:

Performance.- Full capacity charge. Each section of the battery shall become fully charged when it has attained the minimum voltage level specified below when charged at the temperature specified at a constant current of 500 ± 25 MA.

10.5V	AT	70°F
10.0V	AT	130°F
12.5V	AT	-25°F

* Page 3, paragraph 3.5.2.1 a,b,c and Page 4, paragraph 3.5.2.2 a,b,c: Add the word "Minimum" in front of the phrase "Constant Current."

* Page 8, paragraph 4.5.3 Test Equipment: Add the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:26Z
Check the source to verify that this is the current version before use.

NOMENCLATURE	DESCRIPTION
1. Voltmeter, Digital D.C.	Minimum input resistance of 1 Megohm, capable of measuring to 15 Volts with accuracy of .1% of reading and .1% of range.

* Page 9, paragraph 4.6.2 Shock: Delete the second sentence and substitute the following:

"The test shall be performed as specified in Procedure I of MIL-F-13926 except the shock pulse shall comply with the wave form, time duration and peak "G" value specified in 3.4.2."

* Page 9, paragraph 4.6.5 Altitude, Non-operating: Delete and substitute the following:

Conduct this test after the battery has been discharged at 70°F as in 4.6.7. Perform this test in accordance with Procedure II of the altitude test in MIL-F-13926, with conditions specified in 3.4.4.2. The battery shall conform to the requirements of 3.4.4.2 when rotated to any position.

* Page 9, paragraph 4.6.6 Full Capacity Charge: Delete and substitute the following:

Discharge the 3 sections of the battery at the rates specified in 3.5.2.1, and 3.5.2.2 to lower the terminal voltage of each section to 7.0 ± 0.1 V. Charge each section at the rate specified in 3.5.1 until the terminal voltage of each section, measured with the voltmeter (Item 1 of 4.5.3), attains the level specified in 3.5.1. Repeat for each temperature.

Paragraph 4.6.6: Change first sentence: Discharge the 3 sections of the battery at the rates specified in 3.5.2.1 and 3.5.2.2 for a period of time sufficient to lower the terminal voltage of each section as specified in 3.5.1.

Paragraph 4.6.9: Change "4.4.6" to "4.6.6."

*"The margin of this specification is marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue."

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 6240-A367

Source: https://assist.dla.mil -- Downloaded: 2026-10-27T00:26:
Check the source to verify that this is the current version before use.