MILITARY SPECIFICATION SHEET

CIRCUIT CARD ASSEMBLY, 9290618
(INPUT BUFFER "B")

This specification is approved for use by the US Army Armament Research and Devlopment Command and is available for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the circuit card assembly described herein shall consist of this document and the latest issue of specification MIL-C-63371(AR).

Electrical Requirements

All input and output levels shall be consistent with IC operating levels and power supply regulation but shall not exceed plus or minus one percent (± 1.0%) of the indicated nominal value, unless otherwise specified.

FSC: 1095

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:43Z
Check the source to verify that this is the current version before use.

NOTE: 1. Maintain the following input voltages throughout all tests.

Pin No.	Voltage
2	14
4	24 @ 5A Min.
35	0
37	14
39	24 @ 5A Min.
70	0

2. Pins 63 and 64 shall have loads of 12 ohms, 60 watts to ground.

3. Inputs to Pins 50 and 59 shall be capable of "sinking" 14 mA, minimum, each.

4. Pin 65 shall have a load of 8 ohm, 75 watt to ground.

5. A reset pulse of 0.5 to 1.0 seconds at 0V shall be applied to Pin 47 after satisfying all input conditions, then returning to 14V. This input shall be capable of "sinking" 14 mA mininum.

Test 1

INPUT		OUTPUT	
Pin No.	Voltage	Pin No.	Voltage
41	14	43	14
42	14	44	14
60	0	57	14
62	0	63	0
		64	0
		51	14

Test 2

INPUT		OUTPUT	
Pin No.	Voltage	Pin No.	Voltage
41	14	43	0
42	14	44	14
60	14	57	0
62	0	63	0
		64	0
		51	0

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:43Z
Check the source to verify that this is the current version before use.

Test 3

INPUT		OUTPUT	
Pin No.	Voltage	Pin No.	Voltage
41	0	43	14
42	14	44	14
60	14	57	14
62	0	63	0
		64	24
		51	14

Test 4

INPUT		OUTPUT	
Pin No.	Voltage	Pin No.	Voltage
41	0	43	14
42	14	44	14
60	0	57	14
62	0	63	0
		64	24
		51	14

Test 5

INPUT		OUTPUT	
Pin No.	Voltage	Pin No.	Voltage
41	14	43	14
42	14	44	14
60	0	57	14
62	0	63	0
		64	0
		51	14

Test 6

INPUT		OUTPUT	
Pin No.	Voltage	Pin No.	Voltage
41	14	43	14
42	14	44	0
60	0	57	0
62	14	63	0
		64	0
		51	0

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:43Z
Check the source to verify that this is the current version before use.

Test 7

INPUT		OUTPUT	
Pin No.	Voltage	Pin No.	Voltage
41	14	43	14
42	0	44	14
60	0	57	14
62	14	63	24
		64	0
		51	14

Test 8

INPUT		OUTPUT	
Pin No.	Voltage	Pin No.	Voltage
41	14	43	14
42	0	44	14
60	0	57	14
62	0	63	24
		64	0
		51	14

Test 9

INPUT		OUTPUT	
Pin No.	Voltage	Pin No.	Voltage
46	0	45	0
47	Note 5	48	0
50	14	55	14
58	24 @ 3A Min.	57	14
59	14	65	24
61	22	68	0

Test 10

INPUT		OUTPUT	
Pin No.	Voltage	Pin No.	Voltage
46	0	45	0
47	Note 5	48	14
50	0	55	0
58	24 @ 3A Min.	57	0
59	14	65	0
61	22	68	0

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:43Z
Check the source to verify that this is the current version before use.

Test 11

INPUT		OUTPUT	
Pin No.	Voltage	Pin No.	Voltage
46	14	45	14
47	Note 5	48	0
50	14	55	14
58	24 @ 3A Min.	57	0
59	14	65	0
61	22	68	0

Test 12

INPUT		OUTPUT	
Pin No.	Voltage	Pin No.	Voltage
46	14	45	0
47	Note 5	48	0
50	14	55	14
58	24 @ 3A Min.	57	14
59	0	65	24
61	22	68	0

Test 13

INPUT		OUTPUT	
Pin No.	Voltage	Pin No.	Voltage
46	14	45	0
47	Note 5	48	0
50	14	55	14
58	24 @ 3A Min.	57	14
59	0	65	24
61	18.77	68	14

Test 14

INPUT		OUTPUT	
Pin No.	Voltage	Pin No.	Voltage
46	14	45	0
47	Note 5	48	0
50	14	55	14
58	24 @ 3A Min.	57	0
59	0	65	0
61	17.55	68	14

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project No: 1095-A-124/2

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:43Z
Check the source to verify that this is the current version before use.