INCH-POUND

MIL-P-70526A (AR)
AMENDMENT 4
18 Dec 1998
SUPERSEDING
AMENDMENT 3
30 May 1997

MILITARY SPECIFICATION

PROJECTILE, 105MM, HE, RA, M913/XM927
DELAY ASSEMBLY FOR

MIL-P-70526 was inactivated after 21 August 1998 for new design.

This amendment forms a part of Military Specification MIL-P-70526A (AR), dated 6 July 1994, and is approved for use by the US Army Armaments, Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

Title: Change “XM927” to “M927” (and wherever it appears).

PAGE 5

3.7.1 Third line from the last line: Delete “(see 6.11)” and substitute “4.5.8”.

3.7.1.1 Delete “Government” and substitute “contractor”.

PAGE 8

4.3.2.1 Last line: Delete “4.3.1.1” and substitute “4.3.2”.

PAGE 10

4.4.1b: Delete in its entirety and substitute the following:

“b. Flash composition from not more than one raw material constituent ingredient lot.”

DISTRIBUTION STATEMENT A. **Approved for public release; distribution is unlimited.**

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:38Z
Check the source to verify that this is the current version before use.

4.4.1d: Delete in its entirety and substitute the following:

"d. Igniter composition from not more than one raw material constituent ingredient lot."

PAGE 17

4.4.2.6: Add the following new inspections:

"103..Rocket selector cap O-ring or gasket missing — Level III — 3.2 — Visual

104 Lubricant not applied to O-ring — Level III — 3.2 — Visual

105 Lubricant on face of rocket cap assembly" — Level III — 3.2 — Visual

PAGE 20

4.4.3.8.1 Delete second sentence, "Five pilot batches are to be produced at tungsten contents differing from sample to sample by at least one-half part by weight." And substitute, "Five pilot batches are to be produced at tungsten contents differing from sample to sample by a constant difference selected by the contractor. The difference shall not exceed one part by weight."

PAGE 20

* Add paragraph 4.4.3.8.2.1 as follows:

"4.4.3.8.2.1 Additional test for outliers. If the spin test data meets the requirement for standard deviation, but one or more outliers are detected, the 15 remaining samples may be

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:38Z
Check the source to verify that this is the current version before use.

spin tested. The mean time, standard deviation and presence of long time outliers per 4.5.7.1 shall be calculated for the sample of 30. If the standard deviation requirement is met and no outliers are detected, 15 additional complete delay assemblies shall be produced and forwarded for ballistic testing per 4.4.3.8.2."

PAGE 24

* Paragraph 4.5.7 Delete "and the batch shall be rejected."

* Add paragraph 4.5.7.1 as follows:

"4.5.7.1 Dixon test for sample size of 30. Order the delay burn times from longest to shortest (T1 – T30 with T1 being the longest). Calculate the Dixon ration (R) by the following:

$$R = \frac{(T3 - T1)}{(T28 - T1)}$$

If R is greater than .376, then the longest time is an outlier"

The margins of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing Activity:
Army-AR

(Project 1315-0208)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:38Z
Check the source to verify that this is the current version before use.