INCH-POUND

MIL-P-70526A (AR)
AMENDMENT 5
20 August 2002
SUPERSEDING
AMENDMENT 4
18 December 1998

MILITARY SPECIFICATION

PROJECTILE, 105MM, HE, RA, M913/XM927
DELAY ASSEMBLY FOR

MIL-P-70526A was inactivated after 21 August 1998 for new design.

This amendment forms a part of MIL-P-70526A (AR), dated 6 July 1994, and is approved for use by the US Army Armament Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

Title: Change "XM927" to "M927" wherever it appears.

PAGE 4

* 3.6, Delete the 5th sentence in its entirety and substitute the following:

"The boron potassium nitrate, shall not be missing, contain voids greater than 1/64th square inch, or have a gap between the top of the closure greater than 1/18th inch."

PAGE 5

3.7.1:

Line 15, delete: "(see 6.1.1)" and substitute "4.5.8".

* Line 3, delete "15.4 ± 1.0 seconds" and substitute "15.25 ± .75 seconds"

3.7.1.1 Delete "Government" and substitute "contractor"

* 3.7.2, Line 3, delete "15.4 seconds +/- 1 second" and substitute "15.25 ± .75 seconds"

* 3.7.3, Line 3, delete "15.4 seconds +/- 1 second" and substitute "15.25 ± .75 seconds"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:38Z
Check the source to verify that this is the current version before use.

PAGE 6

* Add new paragraph 3.12.3 as follows:

"3.12.3 Boron potassium nitrate. The boron potassium nitrate pellets shall not have flashing or any other form of protrusion attached thereto. The boron potassium nitrate charge shall be free of dust, shards, and other types of particles at the time of loading into the delay assembly."

PAGE 8

4.3.2.1, Last line, Delete "4.3.1.1" and substitute "4.3.2"

PAGE 10

4.4.1b: Delete in its entirety and substitute the following:

"b. Flash composition from not more than one raw material constituent ingredient lot."

4.4.1d: Delete in its entirety and substitute the following:

"d. Igniter composition from not more than one raw material constituent ingredient lot."

PAGE 15

* 4.4.2.4, Add the following major classifications:

"103 Presence of flashing or other protrusions on the boron potassium nitrate pellets prior to loading Level III 3.12.3 Visual with Magnification

104 Presence of dust, shards, or other particles in the boron potassium nitrate charge at the time of loading 100% 3.12.3 Visual"

PAGE 17

4.4.2.6: Add the following new classifications:

"103 Rocket selector cap O-ring or gasket missing Level III 3.2 Visual

104 Lubricant not applied to O-ring Level III 3.2 Visual

105 Lubricant on face of rocket cap assembly Level III 3.2 Visual"

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:38Z
Check the source to verify that this is the current version before use.

PAGE 20

4.4.3.8.1 Delete second sentence, “Five pilot batches are to be produced at tungsten contents differing from sample to sample by at least one-half part by weight.” and substitute “Five pilot batches are to be produced at tungsten contents differing from sample to sample by a constant difference selected by the contractor. The difference shall not exceed one part by weight.”

* 4.4.3.8.1, Second sentence, delete “by at least one half part by weight” and substitute “by at least one quarter part by weight.”

Add new paragraph 4.4.3.8.2.1 as follows:

“4.4.3.8.2.1 Additional test for outliers. If the spin test data meets the requirement for standard deviation, but one or more outliers are detected, the 15 remaining samples may be spin tested. The mean time, standard deviation and presence of long time outliers per 4.5.7.1 shall be calculated for the sample of 30. If the standard deviation requirement is met and no outliers are detected, 15 additional complete delay assemblies shall be produced and forwarded for ballistic testing per 4.4.3.8.2.”

PAGE 22

* 4.5.2 Add the following at the end:

“The delay assemblies shall be radiographed in the vertical orientation with the tube end up. Prior to fixing the delay assemblies for radiographic examination, each delay shall be gently tapped on the cap end to settle the boron potassium nitrate charge in the delay tube. After tapping, the delay assemblies shall be maintained in a tube end up orientation until fixtured.”

PAGE 24

4.5.7.1 Delete “and the batch shall be rejected.”

Add paragraph 4.5.7.1 as follows:

“4.5.7.1 Dixon test sample size of 30. Order the delay burn times from longest to shortest (T1 – T30 with T1 being the longest). Calculate the Dixon ration (R) by the following:

$$R = \frac{(T3 - T1)}{(T28 - T1)}$$

If R is greater than .376, then the longest time is an outlier. “

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:38Z
Check the source to verify that this is the current version before use.

* 4.5.8:

Third sentence, delete “20,000 RPM for M913 application or at 15,000 RPM for M927 application” and substitute “the applicable spin rate ± 200 RPM.”

Fourth sentence, delete “20,000 ± 200 RPM…” and substitute “the applicable spin rate ± 200 RPM.”

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army – AR

Preparing activity:
Army – AR

(Project 1315 - 0273)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:38Z
Check the source to verify that this is the current version before use.