# MILITARY SPECIFICATION

## FIRING ATTACHMENT, BLANK AMMO: M19

This Amendment forms a part of Military Specification MIL-F-63337(AR), dated 19 October 1979, and is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Throughout the specification, change all "XM19" to "M19" wherever it appears.

2.1 SPECIFICATIONS, MILITARY: Delete "MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For" and substitute "MIL-W-63150 - Weapons and Support Materiel, Standard Quality Assurance Provisions For".

PAGE 3

4.1: Delete "MIL-A-48078" and substitute "MIL-W-63150".

PAGE 4

4.3.2: Delete "MIL-A-48078" and substitute "MIL-W-63150".

4.3.3: Delete "See MIL-A-48078" and substitute

"If any assembly, component or test specimen fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of an assembly, component, or test specimen in the sampel to comply with any of the stated requirements."

FSC 1005



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:41Z
Check the source to verify that this is the current version before use.

PAGE 5

TABLE I. First article inspection: Under CHAMBER add "Salt Spray Test"; for NO. OF SAMPLE UNITS, add "(a)"; for REQUIREMENT PARAGRAPH add "3.2"; for PARAGRAPH REFERENCE/ INSPECTION METHOD add "4.5.2".

PAGE 7

4.4.1: Delete in its entirety and substitute the following:

"4.4.1 Inspection lot formation. The term "inspection lot" is defined as a homogeneous collection of units of product from which a representative sample is drawn or which is inspected 100 percent to determine conformance with applicable requirements. Units of product selected for inspection shall represent only the inspection lot from which drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, using the same materials and methods, in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions, and complies with the provisions for submission of product as specified in MIL-STD-105. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein, regardless of the type of inspection procedure which is being applied to determine conformance wth requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168. Blank firing attachments shall be assembled from component parts that have met all inspection requirements specified herein."

4.4.2: Delete in its entirety and substitute the following:

"4.4.2 Examination. The examinations listed in the item detail specification for Classification of Defects shall be performed on inspection lots as defined in 4.4.1 of this specification.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for Major and Minor defects shall be in accordance with MIL-STD-105, Inspection Level II, attributes inspection, unless 100% is indicated.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:41Z
Check the source to verify that this is the current version before use.

b. Critical defects. Unless otherwise specified, inspection for critical defects shall be 100 percent."

PAGE 8

4.4.2.1: Delete "None defined" and substitute under CRITICAL the following:

"1. Diameter of smallest hole in center 100% 3.2 Gage"

Delete MAJOR "102. Diameter of ... Gage"

PAGE 19

4.4.4: Delete "See Section 6 of MIL-A-48078 and 6.3 herein" and substitute "See MIL-W-63150 and 6.3 herein."

PAGE 20

4.5.4: Delete in its entirety and substitute the following:

"4.5.4 Functioning. The assemblies selected for the functioning test shall be assembled to the .50 Caliber M2, Heavy Barrel Machine Gun. Government standard Caliber .50, M1A1 blank cartridges shall be used for this test. A standard belt, consisting of one hundred (100) rounds, shall be fired in approximately twenty (20) round bursts. Any assembly which fails to comply with the requirements specified in 3.5 shall be classed defective. All test results shall be recorded."

6.2: Delete in its entirety and substitute the following:

"6.2 Ordering data. Procurement documents shall specify the following:

6.2.1 Procurement requirements.

a. Title, number and date of this and the item detail specifications.

b. Quantity required and delivery schedules.

c. Serialization requirements, is applicable.

d. Quality Conformance Inspection, if other than specified in Section 4 of item detail specification.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:41Z
Check the source to verify that this is the current version before use.

e. First Article Sample requirements, if other than specified in Section 4 of item detail specification.

f. Packaging requirements, if other than specified in Section 5 of item detail specification.

g. Certificates of conformance for each lot or shipment of product.

6.2.2 Contract data requirements.

a. Contract data requirements for inspection equipment designs (conforming to Data Item Description DI-E-1118 or DI-R-1714 with appropriate addendum to each).

b. Data cards. When required by incorporation of DD Form 1423 into the contract, data cards shall be prepared for each lot in accordance with Data Item Description DI-L-1410."

6.3: Delete "MIL-A-48078" and substitute "MIL-W-63150".

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1005-A620)



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:41Z
Check the source to verify that this is the current version before use.