INCH-POUND

MIL-I-58067A(AV)
AMENDMENT 2
27 February 1990
SUPERSEDING
AMENDMENT 1
20 JUN 1977

MILITARY SPECIFICATION

INDICATOR, VERTICAL VELOCITY, RAPID RESPONSE,
ACCELERATION SENSITIVE
GENERAL SPECIFICATION FOR

This amendment forms a part of MIL-I-58067A(AV) dated 21 April 1977, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 15

4.4.9: Delete and substitute:

4.4.9 High Temperature. (This test may be combined with the high temperature exposure test at the discretion of the testing agency.) The indicator shall be subjected to an ambient temperature of 71 degrees ± 2 degrees C for a period of four hours. At the end of the four hour period and with the temperature maintained at 71 degrees ± 2 degrees C the indicator shall be subjected to and shall meet the requirements of the room temperature scale error test (4.4.4) except that the intervals and rates listed in Table II shall be used. The case leakage test (vacuum only) (4.4.3) shall also be repeated and may be performed coincident with the scale error test.

PAGE 16 AND 17

Renumber page 17 to read page 16 and page 16 to read page 17. (Transferred from amendment 1)

Custodian:
Army - AV

Preparing activity:
Army - AV
(Project No. 6610-A278)

AMSC N/A 1 of 1 FSC 6610
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:59Z
Check the source to verify that this is the current version before use.